

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of BLM18BD601SH1# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=BLM18BD601SH1%23

## BLM18BD601SH1#

"#" indicates a package specification code.

#### In Production RoHS REACH AEC-Q200

< List of part numbers with package codes > BLM18BD601SH1J BLM18BD601SH1D BLM18BD601SH1B

0.4±0.2

1.6±0.15





0.8±0.

: Electrode

(in mm)

0.8±0.15

The chip ferrite beads BLM series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted. BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground. The nickel barrier structure of the external

electrodes provides excellent solder heat resistance. BLM\_B series can minimize attenuation of the signal waveform due to its sharp impedance characteristics. Various impedances are available to match signal frequency.



Automotive Usage	Powertrain/Safety
---------------------	-------------------

#### Packaging Information

Packaging	Specifications	Minimum Order Quantity
J	330mm Paper Tape	10000
D	180mm Paper Tape	4000
В	Bulk(Bag)	1000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of BLM18BD601SH1# from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM18BD601SH1%23

# BLM18BD601SH1#

"#" indicates a package specification code.



#### SMD Shape 1608 Size Code (in mm) Size Code (in inch) 0603 Length 1.6mm Length Tolerance ±0.15mm Width 0.8mm Width Tolerance ±0.15mm Thickness 0.8mm Thickness Tolerance ±0.15mm Impedance (at 100MHz) 600Ω Impedance (at 100MHz) Tolerance ±25% 200mA Rated Current (at 85°C) Rated Current (at 125°C) 200mA DC Resistance(max.) 0.65Ω Operating Temperature Range -55℃ to 125℃ Mass(typ.) 0.005g Number of Circuit 1

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of BLM18BD601SH1# from the official website of Murata Manufacturing Co. Ltd.


Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM18BD601SH1%23

### BLM18BD601SH1#


"#" indicates a package specification code.



<sup>0</sup>1



10



Impedance-Frequency Characteristics

100

Frequency (MHz)

1000 3000

Equivalent Circuit

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3