


Note: This datasheet may be out of date. Please download the latest datasheet of MYMGC3R32EFPF2RV from the official website of Murata Manufacturing Co., Ltd.

MYMGC3R32EFPF2RV













Input voltage ranges from 4.3 to 5.5V Fixed 4 outputs voltage, 1.2V, 1.8V, 3.3V and 2.5V Quick tansient response to load change Small package, 11.9 ×15 ×2.4mm Over current protection Thermal Protection Enable control Power Good signal I2C function High Reliability / Heat Shock Testing, 700 cycle (-40 to +125degC)

1 of 2

Attention


1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



MYMGC3R32EFPF2RV



lout(A)Max	2.5A
Vin(V)	4.3V to 5.5V
Vin(V)typ	5V
Vout(V)	1.2V
Vout(V)typ	1.2V
LineRegulation(%)	-1% to 1%
LoadRegulation(%)	-1% to 1%
Outputs(#)	4
Efficiency(%)	91%
Switching frequency(kHz)	2000kHz
Size(mm)W	11.9mm
Size(mm)L	15.0mm
Size(mm)T	2.4mm
Operatingtemperature(degC)	-40°C to 85°C
Circuit topology	Buck(Step-down)
Package	SMD
Туре	Modules (integrated components)
Productseries	MYMGC
Product Series Features	MYMGC series which is POL(Point of Load) is multiple output MonoBK with I2C interface
lout2(A)Max	1A

Vout2(V)	1.8V
Vout2(V)typ	1.8V
LineRegulation2(%)	-1% to 1%
LoadRegulation2(%)	-1% to 1%
Iout3(A)Max	2A
Vout3(V)	3.3V
Vout3(V)typ	3.3V
LineRegulation3(%)	-1% to 1%
LoadRegulation3(%)	-1% to 1%
lout4(A)Max	1.5A
Vout4(V)	2.5V
Vout4(V)typ	2.5V
LineRegulation4(%)	-1% to 1%
LoadRegulation4(%)	-1% to 1%
Brand	Murata

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

