Note: This datasheet may be out of date.

Please download the latest datasheet of DLW32MH101XT2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=DLW32MH101XT2%23

"#" indicates a package specification code.

DLW32MH101XT2#

For 1000Base-T1










< List of part numbers with package codes > DLW32MH101XT2B DLW32MH101XT2L



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard
		Packing
		Quantity
В	Bulk(Bag)	500
L	180mm Embossed Tape	1500



Features

- 1. Suitable for noise suppression at car area networks.
- 2. Compliant with 1000Base-T1 of automotive Ethernet standard.
- Wide operating temperature range meet automotive application.
 (-40 to +125 degrees C)



Applications

Automotive Usage

Powertrain/Safety

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



DLW32MH101XT2#

Note: This datasheet may be out of date.

Please download the latest datasheet of DLW32MH101XT2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=DLW32MH101XT2%23

"#" indicates a package specification code.



Specifications

Shape	SMD	
Size Code (in mm)	3225	
Size Code (in inch)	1210	
Length	3.2mm	
Length Tolerance	±0.2mm	
Width	2.5mm	
Width Tolerance	±0.2mm	
Thickness	2.5mm	
Thickness Tolerance	max.	
Rated Current	100mA	
Derating of Rated Current	No	
Rated Voltage	50Vdc	
Withstanding Voltage	125Vdc	
DC Resistance(max.)	3.12Ω	
DC Resistance	2.6Ω±20%	
Insulation Resistance(min.)	10ΜΩ	
Operating Temperature Range	-40°C to 125°C	
Mass(typ.)	0.064g	
Number of Circuit	1	
Common Mode Inductance	100μH (Typ.) at 500mV,0. 1MHz 80μH -25%/+50% at 100mV,0. 1MHz	
Operating Temperature Range(Self-temperature rise is included)	No	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



DLW32MH101XT2#


Note: This datasheet may be out of date.


Please download the latest datasheet of DLW32MH101XT2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=DLW32MH101XT2%23

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

