

# LQM21NN1R5K10#

Note: This datasheet may be out of date.

Please download the latest datasheet of LQM21NN1R5K10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQM21NN1R5K10%23

"#" indicates a package specification code.

Size Code 2012 (0805) in mm (in inch)

















< List of part numbers with package codes >

LQM21NN1R5K10B


LQM21NN1R5K10D

LQM21NN1R5K10J



# Appearance & Shape





### References

| Packaging | Specifications   | Standard<br>Packing<br>Quantity |
|-----------|------------------|---------------------------------|
| В         | Bulk(Bag)        | 1000                            |
| D         | 180mm Paper Tape | 4000                            |
| J         | 330mm Paper Tape | 10000                           |

| Mass (typ.) |       |       |
|-------------|-------|-------|
| 1 p         | viece | 0.01g |

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# LQM21NN1R5K10#

Note: This datasheet may be out of date.

Please download the latest datasheet of LQM21NN1R5K10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQM21NN1R5K10%23

"#" indicates a package specification code.



# **Specifications**

| L size   | 2.0±0.2mm      |
|--|----------------|
| W size   | 1.25±0.2mm     |
| T size   | 0.85±0.2mm     |
| 1 5126   | 0.0310.2111111 |
| Size code inch (mm)  | 0805 (2012)    |
| Inductance   | 1.5μH±10%      |
| Inductance Test Frequency  | 10MHz          |
| Rated current (Isat) (Based on Inductance change)                  | 50mA           |
| Rated current (Itemp) (Based on Temperature rise)                  | 50mA           |
| Max. of DC resistance  | 0.5Ω           |
| Class of magnetic shield   | Ferrite Core   |
| Q(min.)  | 45             |
| Q Test Frequency   | 10MHz          |
| Self resonance frequency (min.)                                    | 87MHz          |
| Operating Temperature Range(Self-temperature rise is not included) | -40°C to 85°C  |
| Series   | LQM21NN_10     |

2 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



## 1 Todadi Odaron Bata Onioc

Please download the latest datasheet of LQM21NN1R5K10# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQM21NN1R5K10%23


Note: This datasheet may be out of date.


"#" indicates a package specification code.



# Characteristic Data

LQM21NN1R5K10#





Impedance - Current Characteristics

Q-Frequency Characteristics

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

