

LLL03TR61E333KE01#

“#” indicates a package specification code.

In Production

New

General

RoHS

REACH

85
°C max.

Low
ESL


Reflow
OK

Derating
1

< List of part numbers with package codes >

LLL03TR61E333KE01L

Appearance & Shape



References

Packaging	Specifications	Standard Packing Quantity
L	180Embossed Tape	20000

Mass (typ.)	
1 piece	0.18mg

Notices

Derating1

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

LLL03TR61E333KE01#

“#” indicates a package specification code.



Specifications

Length	0.3±0.03mm
Width	0.6±0.03mm
Thickness	0.18±0.02mm
Capacitance	33000pF ±10%
Distance between external terminals g	0.05mm min.
External terminal size e	0.1±0.05mm
Operating Temperature Range	-55°C to 85°C
Rated Voltage	25Vdc
Size code in inch(mm)	0102 (0306M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X5R(EIA)
Temperature range of temperature characteristics	-55°C to 85°C

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.