

**Product Search Data Sheet** 

Note: This datasheet may be out of date. Please download the latest datasheet of NXFT15XH103FA2B100 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NXFT15XH103FA2B100

## NXFT15XH103FA2B100










## Appearance & Shape







Manufacturing Co., Ltd.

### **Features**

- 1. High accuracy and high sensibility temperature sensing is available by the small size and high accuracy NTC Thermistor.
- 2. Narrow space temperature sensing is available by the small sensing head and the thin lead wire.
- 3. You can choose the optimum length according to the design
- 4. This product is compatible with our 0402 (EIA) size chip Thermistor.
- 5. Excellent long time aging stability
- 6. This is halogen free product (CI= max.900ppm
- Br=max.900ppm and Cl+Br=max.1500ppm).
- 7. Lead is not contained in the product.
- 8. UL/cULcertified product.(UL1434, File No. E137188)



## **Applications**

Limited Usage Consumer Grade



### **Packaging Information**

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	1000

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





### Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NXFT15XH103FA2B100 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NXFT15XH103FA2B100

# NXFT15XH103FA2B100



# **Specifications**

Resistance (25°C)	10kΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C) (Reference Value)	3428K
B-Constant(25/85°C) (Reference Value)	3434K
B-Constant(25/100°C) (Reference Value)	3455K
Maximum Operating Current (25°C)	0.12mA
Rated Electric Power (25°C)	7.5mW
Typical Dissipation Constant (25°C)	1.5mW/°C
Operating Temperature Range	-40°C to 125°C
Thermal Time Constant	4s
Lead Shape	Lead Wire type
Size Code (in mm)	100 = 100mm
Size Code (in inch)	100 = 100mm
Shape	Lead
Mass	0.1g
MSL	N

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sheet


#### Note: This datasheet may be out of date. Please download the latest datasheet of NXFT15XH103FA2B100 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NXFT15XH103FA2B100

# NXFT15XH103FA2B100



## **Product Data**



Resistance-Temperature Characteristics

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

