

Product Search Data Sheet


# NFA21SL307X1A45#


In Production RoHS REACH

< List of part numbers with package codes > NFA21SL307X1A45B NFA21SL307X1A45L

Appearance & Shape







- 1. Steep insertion loss characteristics
- 2. Suitable for noise suppression in 800MHz or higher frequency
- 3. Size: 2.0x1.25mm
- 4.4 circuits in one package

Applications Noise suppression for LCD line

 Applications

 Other Usage
 For general

### Packaging Information

Packaging	Specifications	Standard
		Packing
		Quantity
В	Bulk(Bag)	1000
L	180mm Embossed Tape	4000

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date. Please download the latest datasheet of NFA21SL307X1A45# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL307X1A45%23

"#" indicates a package specification code.



# NFA21SL307X1A45#

Note: This datasheet may be out of date. Please download the latest datasheet of NFA21SL307X1A45# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL307X1A45%23

"#" indicates a package specification code.



### Specifications

Shape	SMD	
Size Code (in inch)	0805	
Length	2.0mm	
Length Tolerance	±0.1mm	
Width	1.25mm	
Width Tolerance	±0.1mm	
Thickness	0.5mm	
Thickness Tolerance	±0.1mm	
Operating Temperature Range	-55℃ to 125℃	
Mass(typ.)	0.007g	
Number of Circuit	4	
Rated Current	100mA	
Rated Voltage	10Vdc	
Withstanding Voltage	30Vdc	
Insulation Resistance(min.)	1000ΜΩ	
Insertion Loss	2dB to 7dB(at Cut-off Frequency),7dB min.(at 500MHz),20dB min.(at 800MHz),25dB min.(at 1000MHz)	
Nominal Cut-off Frequency	300MHz	
Size Code (in mm)	2012	

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.







Note: This datasheet may be out of date. Please download the latest datasheet of NFA21SL307X1A45# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NFA21SL307X1A45%23


"#" indicates a package specification code.



INNOVATOR IN ELECTRONIC


Product Data





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



**Equivalent Circuit** 

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

