

LFD21829MDPFC270

In Production

Recommended

RoHS

REACH



Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	180mm Embossed Tape	4000



Features

Adiplexer branching low and high band.

1. Low insertion loss.
2. Small size, low-profiled and light weight.
3. Absolutely no adjustment required.
4. Reflow solderable.

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

LFD21829MDPFC270



Specifications

Applications	LTE
Center Frequency(f1)	2200.00MHz
Frequency Range(f1)	1710.00MHz to 2690.00MHz
Center Frequency(f2)	829.00MHz
Frequency Range(f2)	698.00MHz to 960.00MHz
Insertion Loss I)(in f1)	0.45dB max. (at 25°C)
Insertion Loss II)(in f1)	0.55dB max. (-40 to +85°C)
Insertion Loss I)(in f2)	0.27dB max. (at 25°C)
Insertion Loss II)(in f2)	0.32dB max. (-40 ~ +85°C)
Attenuation(in f2)	15.0dB min.
Attenuation(in f1)	10.5dB min.
VSWR{P1}(in f1)	2.00 max.
VSWR{P2}(in f2)	1.60 max.
VSWR{P3}(in f1,f2)	(f1)2.00 max., (f2)1.60 max.
Power Capacity	3W
Operating Temperature Range	-40°C to 85°C
L x W (size)	2.00x1.25mm
Thickness(max.)	1.0mm

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.