

Product Search Data Sheet

LFB182G45SG9A272

In Production Recommended RoHS REACH

Appearance & Shape





(in mm)





Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.

Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|------------------|---------------------------------|
| - | 180mm Paper Tape | 4000 |

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



http://www.murata.com/en/products/productdetail?partno=LFB182G45SG9A272



Product Search Data Sheet

LFB182G45SG9A272

Note: This datasheet may be out of date. Please download the latest datasheet of LFB182G45SG9A272 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LFB182G45SG9A272

Specifications

| Applications | WLAN / for Bluetooth® products | |
|-------------------------------------|---|--|
| Nominal Center Frequency (fo) | 2450.00MHz | |
| Bandwidth(BW) | fo±50.00MHz | |
| Insertion Loss in BW I) | 1.80dB max. (at 25°C) | |
| Insertion Loss in BW II) | 2.10dB max. (-40 to +85°C) | |
| Attenuation(Absolute Value) I) | 25.0dB min. at 800.00 to 1000. 00MHz | |
| Attenuation(Absolute Value) II) | 22.5dB min. at 1200.00 to 1300.00MHz | |
| Attenuation(Absolute Value) III) | 5.5dB min. at 2000.00MHz | |
| Attenuation(Absolute Value) IV) | 10.5dB min. at 3000.00MHz | |
| Attenuation(Absolute Value) V) | 23.5dB min. at 3600.00 to 3800.00MHz | |
| Attenuation(Absolute Value) VI) | 35.0dB min. at 4800.00 to 5000.00MHz | |
| Attenuation(Absolute Value) VII) | 35.0dB min. at 7200.00 to 7500.00MHz | |
| Ripple(max.) | 0.7dB | |
| VSWR(max.) | 2.0 | |
| Characteristic Impedance (Nom.) | 50Ω | |
| Power Capacity | 500mW | |
| Operating Temperature Range | -40°C to 85°C | |
| L x W (size) | 1.60x0.80mm | |
| Thickness(max.) | 0.7mm | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

LFB182G45SG9A272

Note: This datasheet may be out of date. Please download the latest datasheet of LFB182G45SG9A272 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LFB182G45SG9A272

Product Data





Frequency Characteristics

Spurious Response

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3