


Product Search Data Sheet

LFB215G12SG8A178

In Production Recommended RoHS REACH

Appearance & Shape





A : Directional Input Mark

All the technical data and information contained herein are subject to change without prior notice. (in mm) Features

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.

Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	180mm Embossed Tape	4000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. Please download the latest datasheet of LFB215G12SG8A178 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LFB215G12SG8A178



Product Search Data Sheet

LFB215G12SG8A178

Note: This datasheet may be out of date. Please download the latest datasheet of LFB215G12SG8A178 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LFB215G12SG8A178

Specifications

Applications	WLAN / for Bluetooth® products	
Nominal Center Frequency (fo)	5125.00MHz	
Bandwidth(BW)	fo±225.00MHz	
Insertion Loss in BW I)	1.50dB max. (at 25°C)	
Insertion Loss in BW II)	1.80dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	25.0dB min. at 4200.00MHz	
Attenuation(Absolute Value)	17.0dB min. at 2x(fo±225)MHz	
Ripple(max.)	1.2dB	
VSWR(max.)	2.0	
Characteristic Impedance (Nom.)	50Ω	
Power Capacity	500mW	
Operating Temperature Range	-40°C to 85°C	
L x W (size)	2.00x1.25mm	
Thickness(max.)	1.05mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Product Search Data Sheet


LFB215G12SG8A178

Note: This datasheet may be out of date. Please download the latest datasheet of LFB215G12SG8A178 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LFB215G12SG8A178

Product Data





Frequency Characteristics

Spurious Response

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3