

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of LFB155G37CB1C032 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LFB155G37CB1C032

LFB155G37CB1C032












Appearance & Shape





(in mm)



Features

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.



Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	180mm Paper Tape	10000

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ LFB155G37CB1C032\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LFB155G37CB1C032

LFB155G37CB1C032



Specifications

Applications	WLAN / for Bluetooth® products	
Nominal Center Frequency (fo)	5375.00MHz	
Bandwidth(BW)	fo±475.00MHz	
Insertion Loss in BW I)	1.50dB max. (at 25°C)	
Insertion Loss in BW II)	1.70dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	10.0dB min. at 3800.00MHz	
Attenuation(Absolute Value)	5.0dB min. at 7500.00MHz	
VSWR(max.)	2.1	
Characteristic Impedance (Nom.)	50Ω	
Power Capacity	500mW	
Operating Temperature Range	-40°C to 85°C	
L x W (size)	1.00x0.50mm	
Thickness(max.)	0.4mm	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet


Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ LFB155G37CB1C032\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=LFB155G37CB1C032

LFB155G37CB1C032



Product Data





Frequency Characteristics

Spurious Response

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

