

TWR-5/3000-15/500-D12A-

In Production

RoHS



Appearance & Shape



Features

Not Recommended for new design

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

TWR-5/3000-15/500-D12A-



Specifications

Output power (W)Max	20W
Vin(V)	9V to 36V
Vin(V)typ	24V
Vout(V)	5V
Vout(V)typ	5V
Isolation Voltage (V)	1500V
Efficiency (%)	82%
Size(mm)W	50.8mm
Size(mm)L	50.8mm
Size(mm)T	11.43mm
Operatingtemperature(degC)	-40°C to 55°C
Outputs (#)	3
Iout(A)Max	3A
Form	2 x 2
Package	DIP
Productseries	TWR
Product Series Features	20W, Triple Output DC-DC Converters
Iout2(A)Max	0.5A
Vout2 (V)	15V
Vout2 (V)typ	15V
Iout3(A)Max	-0.5A
Vout3 (V)	-15V
Vout3 (V)typ	-15V
Brand	Murata Power Solutions

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.