Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.
Please download the latest datasheet of 935246521437-xxT from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=935246521437-xxT

935246521437-xxT

There can be several part numbers depending on packing configurations and electrode surface materials.
Please see the following part number for standard product of this item.
935246521437-T3T

In Production | Recommended


Applications

Unsuitable Applications	Please be sure to read and comply with these "Precautions for use."
Specific Applications	Consumer equipment,Industrial Equipment,Medical equipment [GHTF A/B],Medical equipment [GHTF C], Mobile Electronics Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.
Recommended Applications	Optical Module,Broadband communication,Base Station,RF Power Amplifier

Features

l Ultra low profile 100μm.
l Low leakage current.
l High stability (temperature and voltage).
l Negligible capacitance loss through aging.
l Compatible with standard wire bonding assembly (ball and wedge).
(please refer to our Assembly Application Note for more details)

Appearance & Shape



Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.
Please download the latest datasheet of 935246521437-xxT from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=935246521437-xxT

935246521437-xxT

Specifications

Series	WLSC
Applications	Power Amp for RF
Mounting Method	Wire-bonding vertical
Operating Temperature Range	-55℃ to 150℃
Size Code (in inch)	02065
L x W (size)	0.50 x 1.624mm
Breakdown Voltage (For the rated voltage, please see the FAQ.)	150Vdc
Capacitance	3.7nF
Thickness	100μm

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.