

Home	Products	Search	Support	About Us
----------------------	--------------------------	------------------------	-------------------------	--------------------------

[Home](#) > [Search Engine](#) > Catalog: CSTCR_G

Resonators > CERALOCK (MHz) > Series

 How to check EU RoHS Compliance of Our Products is [here](#).

Product Lifecycle Stage	in Production
Recommended Rank	Preferred

Specification

Global Part Number	CSTCR_G
Previous Part Number	
Oscillating Frequency	4.00 to 7.99MHz
Initial Tolerance	±0.5%
Temp. Stability	±0.2%
Operating Temperature Range	-20 to 80•
Wash	Not Available
Ultrasonic Wash	Not Available
Capacitor	Built in
Frequency Tolerance	Tight tolerance frequency(Intra ±0.1%)
Use	The size of external electrode is not same as CSTCR_G15C and CSTCR_G15L.
Applications	For consumer electronics

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	3000
330mm Paper Tape	
330mm Embossed Tape	9000
Bulk Case	
Bulk(Bag)	500
Ammo Pack	
320Reel	
Magazine	

Details

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Features, Applications](#)
-  [Temperature Characteristics](#)
-  [Basic Oscillation Circuit](#)
-  [Standard Land Patterns](#)
-  [Notice \(Storage and Operating Conditions\)](#)
-  [Notice \(Rating\)](#)
-  [Notice \(Soldering and Mounting\)](#)
-  [Notice \(Handling\)](#)
-  [Packaging](#)
-  [Minimum Quantity \(Supplementation\)](#)