


General Specifications

Motor Protection: Auto Restart/Polarity Protection
Insulation Resistance: 10M Ohm or over with a DC500V Megger
Dielectric Withstand Voltage: AC 700V 1st
Allowable Ambient Temperature Range:
L~M Class: -10 degree C ~ +70 degree C (Operating)
N Class: -10 degree C ~ +70 degree C (Operating)
All Class: -40 degree C ~ +70 degree C (Storage)
(non-condensing environment)

order part 04015SS-12L-AL-00 Sleeve Bearing Fan DC Fans




04015SS panel cut out




Material

Casing: Aluminum (Black)
Impeller: Plastic (Black) UL94V-0
Lead Wire: UL10368, AWG22, +Red, -Black

04015SS characteristics curve



04015SS product drawing



Detailed Specifications

DC Fans

Expected Life:	40 degree C 40,000 Hours (L10)
DC Fan:	Sleeve Bearing Fan
Nominal Voltage:	12[V]
Operating Voltage Lower:	6[V]
Operating Voltage Upper:	13.8[V]
Current:	0.04[A]
Input Power:	0.5[W]
Speed:	6300[min^{-1}]
Max. Air Flow:	0.16[m ³ /min]
Max. Air Flow:	5.7[CFM]
Max. Static Pressure:	40[Pa]
Max. Static Pressure:	0.16[In H ₂ O]
Noise:	26[dB]
Mass:	23[g]
Fan Size:	40[mm]
Fan Width:	15[mm]
Life Expectancy L10:	40 degree C 40,000 Hours (L10)
Series:	04015SS