

Products Lineup

Aluminum Electrolytic Capacitors



85°C Snap-in Type Aluminum Electrolytic Capacitors SMQ Series  
ESMQ251VSN182MA455

Standard  
Switching Power Supply, Inverter Controller etc.

RoHS

Part Number	<b>ESMQ251VSN182MA455</b>
Status	In Production
Series	SMQ
Polarity	Polar
Category Temperature Range	-25~85 °C
Rated Voltage	250 Vdc
Capacitance	1800 µF
Capacitance Tolerance	-20~20%(M) / 20°C, 120Hz
Dimensions ø D	35mm
Dimensions L	45mm
Rated Ripple Current	4550mA rms / 85°C / 120Hz
Leakage Current	2010 µA max / 20°C, after 5 minutes
Dissipation Factor (tanδ)	0.15 max / 20°C, 120Hz
Endurance Temperature/Time/Overload	85°C / 2000hrs / DC+Ripple
Shelf Life Temperature/Time	85°C / 1000hrs
Terminal Coating	Sn
Reference Weight	65g
Minimum Order Quantity	200 pcs
RoHS Compliant	Compliant

Print Preview >

Stock at Distributors

Distributors	Stock quantity	Buy
Loading...		

Powered by netCOMPONENTS

Design Tools · Documents

- Catalog Data
- Lifetime Estimation
- 3D-CAD Data
- Reliability Data
- RoHS, REACH/SVHC Reports (Downloads)
- Information on Chemical Substances In Products chemSHERPA Data (IEC 62474)


Products Guide

- Product Code Guide
- Precautions And Guidelines
- Available Terminals
- Minimum Order Quantity
- Recommended Soldering Conditions
- Standardization And Obsolete Products
- Overseas Production Base
- Technical Notes
- About Environmental Measures
- Catalog (Full Page)


Rated Ripple Current Multipliers

Frequency [Hz]	50	120	300	1k	10k	50k
Multipliers	0.81	1.00	1.17	1.32	1.45	1.50

Dimension [mm]



Part Numbering System



<b>Products Lineup</b>	Product Search/Purchase Samples	Aluminum Electrolytic Capacitors	Multilayer Ceramic Capacitors	Film Capacitors
	Supercapacitors	Metal Oxide Varistors	Inductors (Coils/Cores)	Camera Module
	Wafer	Module		

<b>Products Lineup</b>	Company/IR
Product Search/Purchase Samples > Aluminum Electrolytic Capacitors > Multilayer Ceramic Capacitors >	
Film Capacitors > Supercapacitors > Metal Oxide Varistors >	
Inductors (Coils/Cores) > Camera Module > Wafer >	News >
Module >	

<b>Design Tools</b>	<b>Distributors</b>	Company >
Lifetime Estimation > SPICE/S parameters >	in US >	
3D-CAD > Application guides >	in Europe >	Sustainability >
Reliability test data >		

<b>Downloads</b>	Investor Relations >
<b>FAQ/Contact us</b>	
Products FAQs > Products Inquiries >	Material Procurement >