

Last Revised: 2017-06-14 08:23:34.0

1.73 GHz Quad-Core Real-Time Embedded Controller for PXI Express

NI PXIe-8133 RT



- Intel Core i7-820QM quad-core processor (1.73 GHz (base), 3.06 (single-core turbo))
- 2 GB (1 x 2 GB DIMM) dual-channel 1333 MHz DDR3 standard, 4 GB (2 x 2 GB DIMM) maximum
- Execution target for NI LabVIEW Real-Time Version 2010 or later applications
- Execution target for NI LabWindows/CVI Real-Time 2010 or later applications
- Reliable and deterministic operation
- 172 kHz single PID loop rate, maximum
- Two 10/100/1000BASE-TX Ethernet ports and four Hi-Speed USB ports
- Other peripherals (ExpressCard/34 slot, DVI-I video connector, IEEE 1284 ECP/EPP parallel port, GPIB (IEEE 488) controller, and RS232C serial port)
- Complete PXI system configuration at ni.com/pxiadvisor

Overview

National Instruments RT Series PXI embedded controllers deliver a flexible, rugged platform for your deterministic, real-time measurement and control applications. The NI PXIe-8133 RT controller with 1.73 GHz base frequency, a 3.06 GHz (single-core turbo) quad-core processor, dual-channel 1333 MHz DDR3 memory, and high-performance 7200 rpm hard drive offers a high-performance platform ideal for demanding real-time test and control applications. You can develop your LabVIEW application with the LabVIEW Real-Time Module on Windows and download the program to your NI PXIe-8133 RT controller via Ethernet. The embedded code executes on a real-time OS. Thus, you use the powerful and flexible development tools of LabVIEW to build reliable, real-time solutions.

LabVIEW Real-Time applications running on PXI systems achieve millisecond loop rates with only 3 to 4 μ s of system jitter. These real-time measurement and control systems capitalize on the latest processors combined with the advanced timing, triggering, and I/O synchronization benefits of PXI. Furthermore, NI measurement services software extends the timing capabilities of PXI to deliver tight integration with LabVIEW Real-Time applications through operations such as hardware-timed software loops.

[Back to Top](#)

Requirements and Compatibility

OS Information

Software Compatibility

- LabVIEW
- LabVIEW Real-Time Module

[Back to Top](#)

Application and Technology

NI PXIe-8133 RT Features

| | |
|--|--|
| CPU | Intel Core i7-820QM, 1.73 GHz (base), 3.06 GHz (single-core turbo mode), 2.8 GHz (dual-core turbo mode), 2.0 GHz (quad-core turbo mode) ¹ |
| PXI Express 4-link configuration | Four x4 links |
| Dual-channel 1333 MHz DDR3 RAM, standard | 2 GB (1 x 2 GB) |
| Dual-channel 1333 MHz DDR3 RAM, maximum | 4 GB (2 x 2 GB) |

| | |
|--|------------------------|
| Hard drive (standard option), minimum | 120 GB SATA (7200 rpm) |
| Hard drive (extended temperature and 24/7 option), minimum | 80 GB SATA (5400 rpm) |
| 10/100/1000BASE-TX (Gigabit) Ethernet ports | 2 |
| Hi-Speed USB ports | 4 |
| GPIO (IEEE 488) controller | |
| Serial port (RS232) | |
| Parallel port | |
| ExpressCard/34 slot | |
| Watchdog/trigger SMB | |

¹ Processor should not throttle CPU frequency under reasonable, worst-case processor workloads in high operating temperature.

Table 1. NI PXIe-8133 RT Features

Run Parallel Tasks on Separate Processor Cores

The LabVIEW Real-Time Module takes advantage of the available quad cores on the Intel processor to increase performance and determinism for large real-time test and control applications. You can either explicitly assign certain tasks to run on specific cores of the processor or let the real-time operating system manage this assignment for you.

The NI PXIe-8133 RT features Intel Turbo Boost technology, which provides performance benefits for all types of applications without requiring the application to be optimized for multicore processors. The NI PXIe-8133 has a 1.73 GHz base clock frequency, and, with Intel Turbo Boost technology, the frequency automatically increases based on the application type. For example, when running applications that generate only a single processing thread, the CPU places the three unused cores into an idle state and increases the active core's clock frequency from 1.73 to 3.06 GHz.¹ For applications that are processing two threads, the CPU places the two unused cores into an idle state and increases the active core's clock frequency from 1.73 to 2.80 GHz.¹ For applications using four threads, the CPU increases from 1.73 to 2.0 GHz¹. Turbo Boost provides performance increases for all types of applications and can significantly reduce test times for applications that are processor-intensive.

Note: Intel Turbo Boost technology can increase application jitter, so be careful when enabling this setting on real-time systems.

¹Processor should not throttle CPU frequency under reasonable, worst-case processor workloads in high operating temperatures.

Connect to Any I/O

The modularity of PXI and open development environment of LabVIEW make it easy to integrate a variety of I/O within your application. Create a custom real-time embedded solution using an NI PXIe-8133 RT with any number and combination of PXI/CompactPCI plug-in modules. With built-in LabVIEW libraries, you can create applications with data acquisition, dynamic signal acquisition, motion control, image acquisition, reconfigurable I/O, and instrumentation. Communicate with peripheral devices through CAN, GPIB, Ethernet, or serial protocols. And use NI-VISA to integrate third-party PXI/CompactPCI modules into your application.

In addition, the NI PXIe-8133 RT controller includes an external SMB connection for use as a trigger input, output, or watchdog timer. Use the external SMB to pass trigger and timing signals into and out of the PXI trigger bus in your system.

Create Reliable Stand-Alone Systems

To ensure reliable operation, embedded LabVIEW Real-Time applications continue to run even if the host PC is interrupted or rebooted. Because the NI PXIe-8133 RT embedded controller runs in a separate chassis with a dedicated power supply, the operator can shut down the host computer entirely without disrupting the real-time program.

For stand-alone operation, you can embed code in the system so that it starts automatically when the system boots, requiring no human interaction. Use the LabVIEW Professional Development System and LabVIEW Real-Time Module to compile your LabVIEW application into an executable and download it to your NI PXIe-8133 RT controller.

Dual-Boot Option

You can configure NI PXI embedded controllers to boot into Windows or the real-time OS. NI Measurement & Automation Explorer (MAX) includes features for installing and configuring PXI embedded controllers as LabVIEW Real-Time targets. The controllers use a hardware switch or BIOS setting to boot into the desired OS.

The result is a PXI embedded controller that can run embedded LabVIEW Real-Time or Windows applications. When the controller is in real-time mode, you need another Windows computer to develop and debug the LabVIEW Real-Time code for the PXI controller. To enable a Windows PXI embedded controller to dual-boot with the real-time OS, you must purchase the LabVIEW Real-Time embedded deployment software for the controller.

Extended Temperature and 24/7 Operation Option

The NI PXIe-8133 RT embedded controller is available in two versions to address different environmental and usage conditions. The primary difference is that the version for extended temperature and 24/7 operation uses a different hard drive designed for reliability in both low- and high-temperature extremes and 24/7 operation. The standard version of the controllers has an operating temperature of 5 to 50 °C and a storage temperature of -40 to 65 °C. The extended temperature and 24/7 operation version has an operating temperature of 0 to 55 °C and a storage temperature of -40 to 70 °C.

You can also use the extended temperature and 24/7 operation version for applications that require continuous operation for up to 24 hours/day, seven days/week because the hard drive is rated for 24/7 operation. The hard drive in the standard version of the controllers is designed to be powered on for eight hours/day, five days/week. Additionally, 24/7 operation applications may subject the hard drive to a high duty cycle (the percentage of the maximum sustained throughput of the hard drive). The hard drive in the standard version of the controllers is designed for a 20 percent duty cycle. The hard drives in the extended temperature and 24/7 operation version and the standard version have a capacity of 80 GB (minimum) with a SATA interface.

Real-Time Performance Benchmarks

Table 2 contains the PID loop rate benchmark numbers for the NI PXIe-8133 RT. For a direct comparison, the benchmarks for the NI PXIe-8133 RT embedded controller were artificially restricted to exercise only the first CPU cores on the Intel i7-820QM quad-core processor. Also, the NI PXIe-8133 RT had Intel Turbo Boost technology enabled, which can increase application jitter, so be careful when enabling this setting on real-time systems.

| Benchmark | Processing | Channels | DAQ I/O Mode | Loop Rate (kHz) | |
|------------|------------|----------|--------------|-----------------|-----------------|
| | | | | NI PXIe-8108 RT | NI PXIe-8133 RT |
| Analog I/O | PID | 1 | Polling | 114 | 172 |

| | | | | | |
|------------|-----|----|-----------|----|-----|
| Analog I/O | PID | 1 | Interrupt | 64 | 101 |
| Analog I/O | PID | 4 | Polling | 94 | 105 |
| Analog I/O | PID | 4 | Interrupt | 57 | 87 |
| Analog I/O | PID | 16 | Polling | 33 | 37 |
| Analog I/O | PID | 16 | Interrupt | 29 | 35 |

Table 2. Maximum loop rates for LabVIEW Real-Time PXI systems are shown. All benchmarks use the LabVIEW 2010 Real-Time Module with NI-DAQmx 9.1.5. Benchmarks were revised to adhere to the architecture recommended by NI for symmetric multiprocessing enabled systems. Benchmarks that do not test network performance run on a headless target without a direct Ethernet connection for maximum performance. Benchmarks that do test network performance use interrupt-mode Ethernet via a direct connection between the host PC and real-time target with a crossover cable. Visit ni.com or contact National Instruments for additional benchmarks.

In-ROM Memory and Hard-Drive Diagnostics

To improve the serviceability of the NI PXIe-8133 RT, In-ROM diagnostics for the hard drive and memory can be quickly accessed without requiring external third-party tools. By running these diagnostics, the results of analysis can determine if replacement of the hard drive or memory is required. The design of the controller allows for quick field replacement of critical components such as the hard drive and the memory without affecting the warranty. To ease the process of buying spare components, you can purchase hard drive and memory upgrades with the NI PXIe-8133 RT. The combination of this and the In-ROM diagnostics significantly improves NI PXIe-8133 RT serviceability.

Memory

The NI PXIe-8133 RT uses dual-channel 1333 MHz DDR3 SDRAM, which makes the controller ideal for data-intensive applications requiring significant analysis. It has two SO-DIMM sockets for the DDR3 SDRAM. 2 GB (1 x 2 GB DIMM) of RAM is standard with upgrade options to 4 GB.

| Memory Options | Configuration | Part Number | |
|-----------------|---------------|-----------------|-------------------------|
| | | Included in Kit | Additional P/N Required |
| Standard - 2 GB | 1 x 2 GB DIMM | 1 x 2 GB DIMM | N/A |
| 4 GB | 2 x 2 GB DIMM | 1 x 2 GB DIMM | Add 1 x 781403-2048 |

Table 3. Memory Upgrade Options

[Back to Top](#)

Ordering Information

For a complete list of accessories, visit the product page on ni.com.


| Products | Part Number | Recommended Accessories | Part Number |
|--|-------------|--------------------------|-------------|
| Hard-Drive Spare/Replacement and Upgrades | | | |
| 32 GB 2.5 in SATA Solid-State Drive Upgrade | 779175-08 | No accessories required. | |
| 250 GB 2.5 in MLC SATA Solid-State Drive Upgrade | 781945-01 | No accessories required. | |
| 80 GB (or greater) 2.5 in. SATA Ext Temp, 24/7 Blank HDD Spare/Replacement | 779175-07 | No accessories required. | |
| 250 GB (or Greater) 2.5 in SATA Hard Drive Upgrade | 779175-06 | No accessories required. | |
| 120 GB (or greater) 2.5 in. SATA Blank HDD Spare/Replacement | 780970-01 | No accessories required. | |
| 500 GB 2.5 in SATA Hard Drive Upgrade | 781946-01 | No accessories required. | |
| Other Accessories | | | |
| Micro-GPIB to GPIB cable (2 m) | 183285-02 | No accessories required. | |
| USB-to-dual-PS/2 keyboard/mouse adapter cable | 778713-02 | No accessories required. | |
| ExpressCard strain-relief accessory for embedded controllers | 192524-01 | No accessories required. | |
| External USB floppy drive | 778492-02 | No accessories required. | |
| USB English keyboard and optical mouse | 779660-01 | No accessories required. | |
| Micro-GPIB to GPIB cable (1 m) | 183285-01 | No accessories required. | |
| NI PXIe-8133 RT | | | |
| NI PXIe-8133 Real-Time Embedded SW | 781478-33 | No accessories required. | |
| NI PXIe-8133 Real-Time Embedded SW Extended Temp | 781479-33 | No accessories required. | |

[Back to Top](#)

Software Recommendations

LabVIEW Real-Time Module

- Design deterministic real-time applications with LabVIEW graphical programming
- Download to dedicated NI or third-party hardware for reliable execution and a wide selection of I/O
- Take advantage of built-in PID control, signal processing, and analysis functions
- Automatically take advantage of multicore CPUs or set processor affinity manually
- Includes real-time OS, development and debugging support, and board support
- Purchase individually or as part of the NI Embedded Control and Monitoring Software Suite



[Back to Top](#)

Support and Services

System Assurance Programs

NI system assurance programs are designed to make it even easier for you to own an NI system. These programs include configuration and deployment services for your NI PXI, CompactRIO, or Compact FieldPoint system. The NI Basic System Assurance Program provides a simple integration test and ensures that your system is delivered completely assembled in one box. When you configure your system with the NI Standard System Assurance Program, you can select from available NI system driver sets and application development environments to create customized, reorderable software configurations. Your system arrives fully assembled and tested in one box with your software preinstalled. When you order your system with the standard program, you also receive system-specific documentation including a bill of materials, an integration test report, a recommended maintenance plan, and frequently asked question documents. Finally, the standard program reduces the total cost of owning an NI system by providing three years of warranty coverage and calibration service. Use the online product advisors at ni.com/advisor to find a system assurance program to meet your needs.

Technical Support

Get answers to your technical questions using the following National Instruments resources.

- **Support** - Visit ni.com/support to access the NI KnowledgeBase, example programs, and tutorials or to contact our applications engineers who are located in NI sales offices around the world and speak the local language.
- **Discussion Forums** - Visit forums.ni.com for a diverse set of discussion boards on topics you care about.
- **Online Community** - Visit community.ni.com to find, contribute, or collaborate on customer-contributed technical content with users like you.

Repair

While you may never need your hardware repaired, NI understands that unexpected events may lead to necessary repairs. NI offers repair services performed by highly trained technicians who quickly return your device with the guarantee that it will perform to factory specifications. For more information, visit ni.com/repair.

Training and Certifications

The NI training and certification program delivers the fastest, most certain route to increased proficiency and productivity using NI software and hardware. Training builds the skills to more efficiently develop robust, maintainable applications, while certification validates your knowledge and ability.

- **Classroom training in cities worldwide** - the most comprehensive hands-on training taught by engineers.
- **On-site training at your facility** - an excellent option to train multiple employees at the same time.
- **Online instructor-led training** - lower-cost, remote training if classroom or on-site courses are not possible.
- **Course kits** - lowest-cost, self-paced training that you can use as reference guides.
- **Training memberships** and training credits - to buy now and schedule training later.

Visit ni.com/training for more information.

Extended Warranty

NI offers options for extending the standard product warranty to meet the life-cycle requirements of your project. In addition, because NI understands that your requirements may change, the extended warranty is flexible in length and easily renewed. For more information, visit ni.com/warranty.

OEM

NI offers design-in consulting and product integration assistance if you need NI products for OEM applications. For information about special pricing and services for OEM customers, visit ni.com/oem.

Alliance

Our Professional Services Team is comprised of NI applications engineers, NI Consulting Services, and a worldwide National Instruments Alliance Partner program of more than 700 independent consultants and integrators. Services range from start-up assistance to turnkey system integration. Visit ni.com/alliance.

[Back to Top](#)

Detailed Specifications

This topic lists the electrical, mechanical, and environmental specifications of the NI PXIe-8133 embedded controller.

Features

| NI PXIe-8133 | |
|--------------|----------------------|
| CPU | Intel Core i7 820 QM |

| NI PXIe-8133 | |
|--------------------------------------|--|
| CPU Frequency | 1.73 GHz (base), 3.06 GHz (single-core Turbo mode) |
| On-die L2 cache | 512 KB x2 (512 KB per core) |
| L3 cache | 8 MB shared Intel smart cache |
| Dual-Channel DDR3 RAM, PC3 10600 | 2 GB Standard, 8 GB Maximum |
| Hard Drive | 120 GB or larger Serial ATA ¹ |
| Ethernet | 10/100/1000 BaseTX, 2 ports |
| PXI Express 4 Link Configuration | x4, x4, x4, x4 |
| PXI Express 2 Link Configuration | x4, x4 |
| GPIB (IEEE 488 Controller) | Yes |
| Serial Ports (RS-232) | Yes (1) |
| Parallel Port | Yes (1) |
| Hi-Speed USB (2.0) Ports | Yes (4) |
| ExpressCard/34 Slot | Yes |
| PS/2 Keyboard/Mouse Connector | No |
| PXI Express Trigger Bus Input/Output | Yes |
| Installed Operating System | Windows 7 Professional, Windows XP Professional SP3 for Embedded Systems |

Electrical

| Voltage (V) | Current (Amps) | |
|-------------|----------------|---------|
| | Typical | Maximum |
| +3.3 V | 3.1 A | 4.6 A |
| +5 V | 2.2 A | 3.3 A |
| +12 V | 4.8 A | 7.2 A |
| -12 V | 0.00 A | 0.00 A |
| +5 V Aux | 0.29 A | 0.43 A |

Physical

| | |
|-------------------|--|
| Board dimensions | Four-wide 3U PXI Express module |
| Slot requirements | One system slot plus three controller expansion slots |
| Compatibility | Fully compatible with <i>PXI Express Specification 1.0</i> |
| Weight | 1.30 kg (2.87 lb) typical |

Environment

| | |
|------------------|---|
| Maximum altitude | 2,000 m (800 mbar) (at 25 °C ambient temperature) |
| Pollution Degree | 2 |
| Indoor use only. | |



Caution Clean the NI PXIe-8133 with a soft nonmetallic brush. Make sure that the device is completely dry and free from contaminants before returning it to service.

Operating Environment

| | |
|-----------------------------|--|
| NI PXIe-8133 | |
| Ambient temperature range | |
| Standard | 5 to 50 °C ² (Tested in accordance with IEC-60068-2-1 and IEC-60068-2-2. Meets MIL-PRF-28800F Class 3 high temperature limit.) |
| Extended Temperature Option | 0 to 55 °C ² (Tested in accordance with IEC-60068-2-1 and IEC-60068-2-2. Meets MIL-PRF-28800F Class 3 low temperature limit and MIL-PRF-28800F Class 2 high temperature limit.) |
| Relative humidity range | 10% to 90%, noncondensing (Tested in accordance with IEC-60068-2-56.) |



Caution The operating temperature must not be exceeded, even when used in a chassis with a higher temperature range.

Storage Environment

NI PXIe-8133

Ambient temperature range

| | |
|-----------------------------|---|
| Standard | –40 to 65 °C (Tested in accordance with IEC-60068-2-1 and IEC-60068-2-2. Meets MIL-PRF-28800F Class 3 low temperature limit.) |
| Extended Temperature Option | –40 to 71 °C (Tested in accordance with IEC-60068-2-1 and IEC-60068-2-2. Meets MIL-PRF-28800F Class 3 limits.) |
| Relative humidity range | 5% to 95%, noncondensing (Tested in accordance with IEC-60068-2-56.) |

Shock and Vibration

| | |
|------------------|--|
| Operating Shock | 30 g peak, half-sine, 11 ms pulse (Tested in accordance with IEC-60068-2-27. Meets MIL-PRF-28800F Class 2 limits.) |
| Random Vibration | |
| Operating | 5 to 500 Hz, 0.3 g _{rms} (with solid-state hard drive) |
| Nonoperating | 5 to 500 Hz, 2.4 g _{rms} (Tested in accordance with IEC-60068-2-64. Nonoperating test profile exceeds the requirements of MIL-PRF-28800F, Class 3.) |



Note Specifications are subject to change without notice.

Safety Standards

This product is designed to meet the requirements of the following standards of safety for electrical equipment for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1



Note For UL and other safety certifications, refer to the product label or the *Online Product Certification* section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- AS/NZS CISPR 11: Group 1, Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note For EMC declarations and certifications, refer to the *Online Product Certification* section.



Note When operating this product, use shielded cables and accessories.

CE Compliance

This product meets the essential requirements of applicable European Directives, as amended for CE marking, as follows:

- 2006/95/EC; Low-Voltage Directive (safety)
- 2004/108/EC; Electromagnetic Compatibility Directive (EMC)

Online Product Certification

To obtain product certifications and the DoC for this product, visit ni.com/certification, search by module number or product line, and click the appropriate link in the Certification column.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial not only to the environment but also to NI customers.

For additional environmental information, refer to the *NI and the Environment* Web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

Waste Electrical and Electronic Equipment (WEEE)



EU Customers At the end of the product life cycle, all products *must* be sent to a WEEE recycling center. For more information about WEEE recycling centers, National Instruments WEEE initiatives, and compliance with WEEE Directive 2002/96/EC on Waste Electrical and Electronic Equipment, visit ni.com/environment/weee.htm.

Battery Replacement and Disposal



Battery Directive This device contains a long-life coin cell battery. If you need to replace it, use the Return Material Authorization (RMA) process or contact an authorized National Instruments service representative. For more information about compliance with the EU Battery Directive 2006/66/EC about Batteries and Accumulators and Waste Batteries and Accumulators, visit ni.com/environment/batterydirective.

电子信息产品污染控制管理办法（中国 RoHS）



中国客户 National Instruments 符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。
关于 National Instruments 中国 RoHS 合规性信息，请登录 ni.com/environment/rohs_china。
(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)

¹ Extended-temperature 24/7 option provides 80 GB minimum hard drive. Controllers configured for LabVIEW RT provide a 80 GB (minimum) SATA hard drive.

² Processor should not throttle CPU frequency under reasonable, worst case processor work loads in high operating temperatures.

[Back to Top](#)

©2010 National Instruments. All rights reserved. CompactRIO, FieldPoint, LabVIEW, National Instruments, National Instruments Alliance Partner, NI, ni.com, and NI-DAQ are trademarks of National Instruments. Other product and company names listed are trademarks or trade names of their respective companies. A National Instruments Alliance Partner is a business entity independent from National Instruments and has no agency, partnership, or joint-venture relationship with National Instruments.

[My Profile](#) | [RSS](#) | [Privacy](#) | [Legal](#) | [Contact NI](#) © 2014 National Instruments Corporation. All rights reserved.