

Solid-state Timer

English

H3YN-21 DC100-110


Print Page



Analog Timer, DC100 to 110V

Rated supply voltage	100 to 110VDC If power supply incorporates a single-phase full-wave rectifier.
Control output (Type)	Time-limit: DPDT
External connection method	Plug-in terminal

Series



Solid-state Timer
H3YN

[Catalog](#)

[about this Product](#)

[Inquiry of this Product](#)

[Item list of H3YN](#)

Image

- Ratings/Performance
- Dimensions**
- Time ranges
- Operating chart
- Electrical life

As of November 11, 2015

Rated supply voltage	100 to 110VDC If power supply incorporates a single-phase full-wave rectifier.
Operating voltage range	85% to 110% of rated supply voltage
Power consumption (Relay ON)	1.6W(at 110 VDC)
Power consumption (Relay OFF)	0.4W(at 110 VDC)
Reset voltage	10% max. of rated supply voltage
Number of time ranges	4
Time ranges	0.1min~1min / 1min~10min / 0.1h~1h / 1h~10h
Operating mode	ON delay, Interval, Flicker OFF start, Flicker ON start, Pulse Operation (use in interval mode, connect power supply terminals as pulse operation)
Control output (Type)	Time-limit: DPDT
Control output (Contact output)	Switching capacities (resistive load (cos(phi) = 1)): 250VAC 5A Minimum applicable load: 1 mA at 5 VDC (failure level: P)
Ambient temperature	Operating: -10 to 50°C Storage: -25 to 65°C
Ambient humidity	使用時: 35~85%
Accuracy of operating time	+/- 1% max.(FS)
Setting error	-10 to 10% +/- 50 ms max. (FS)
Reset time	0.1 s max. (including halfway reset)
Influence of voltage	+/- 2% FS max.
Influence of temperature	+/- 2% FS max.
Insulation resistance	100 MΩ (at 500 VDC)
Dielectric strength	between current carrying terminals and exposed non-current carrying metal parts: 2000 VAC, 50/60 Hz for 1 min (Terminal screw sections are not excluded) between control output terminals and operating circuit: 2000 VAC, 50/60 Hz for 1 min between contacts of different poles: 2000 VAC, 50/60 Hz for 1 min between non-continuous contacts: 1000 VAC, 50/60 Hz for 1 min
Impulse withstand voltage	between power terminals: 3 kV between exposed non-current-carrying metal parts: 4.5 kV
Noise immunity	+/- 1.5 kV square-wave noise by noise simulator (pulse width: 100 ns/1 us, 1-ns rise)
Static immunity	Multifunction: 4 kV Destruction: 8 kV
Vibration resistance (Destruction)	10 to 55 Hz, 0.75 mm single amplitude each in X, Y, and Z directions for 1 hours
Vibration resistance	10 to 55 Hz, 0.5 mm single amplitude each in X, Y, and Z directions for 10 min

(Malfunction)	
Shock resistance (Destruction)	1000 m/s**2, 3 times each 6 directions
Shock resistance (Malfunction)	100 m/s**2, 3 times each 6 directions
Mechanical life expectancy (relayoutput)	10000000 operations min. (under no load at 1800 operations/h)
Electrical life expectancy (relay output)	500000 operations min. (5 A at 250 VAC, resistive load at 1800 operations/h)
Degree of protection	IP40
External connection method	Plug-in terminal
Case color	Munsell 5Y7/1 (Light gray)
Weight (Main)	Approx. 50 g

As of November 11, 2015

[▲ Top of page](#)[▶ OMRON Corporation](#)  [▶ Sitemap](#) [▶ Terms of Use](#) [▶ Privacy Policy](#)

© Copyright OMRON Corporation 2007 - 2012. All Rights Reserved.

realizing