



P2RFZ-05-E

Socket, DIN rail/surface mounting, 5-pin, screw terminals

Specifications

Applicable product family	G2R-1-S
Mounting method	DIN rail/screw
Product Depth (unpacked)	61.0 mm
Product Height (unpacked)	79 mm
Product Width (unpacked)	15.5 mm
Terminal type	Screw
Color	Black
Hold down clip included	✓
Release Lever included	✓
Applicable ferrules	Forked terminals, Round terminals

Fits to



G2R-1-S 120VAC (S)

Relay, plug-in, SPDT, 10 A, mechanical indicator, 120 VAC



G2R-1-S 12VDC (S)

Relay, plug-in, SPDT, 10 A, mechanical indicator, 12 VDC



G2R-1-S 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 230 VAC



G2R-1-S 24VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 24 VAC



G2R-1-SD 24VDC (S)

Relay, plug-in, SPDT, 10 A, mech. indicator, diode, 24 VDC



G2R-1-SN 120VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, 120 VAC



G2R-1-SN 240VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, 240 VAC



G2R-1-SN-AP3 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating



G2R-1-SN-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, gold-plated contacts, LED indicator



G2R-1-SND 48VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility



G2R-1-SND-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating



G2R-1-SNDI 12VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, lockable test button, label facility, 12 VDC



G2R-1-SNDI-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A gold plate contacts, mech & LED indicators, coil suppressor, lockable test button, label facility



G2R-1-SNI 110VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility, 110 AC



G2R-1-SNI 120VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, test button, 120 VAC



G2R-1-SNI 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility

	P2DN-CP100	Box of 100 caps for P2DN short bar: insulation cap for the short bar cut, blue color
	PFP-100N	DIN-rail mounting track, 35 x 7.3 mm, 1 m length
	PFP-100N2	DIN-rail mounting track, 35x16mm, 1m length
	PFP-50N	Din rail track, 500 mm
	PFP-M	End plate
	PFP-S	Spacer
	XW5Z-EP12	Separator Plate for terminal blocks, 12 mm width
	XW5Z-EP6	End bracket for terminal blocks, 6 mm width

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G2R-_S (S) General- purpose Relay Datasheet

EN PDF 3.31 MB