DBA250G

25.0A Single-Phase Bridge Rectifier

Features

- Plastic molded structure
- Glass passivation for high reliability
- Peak reverse voltage: V_{RM}=600V
- Average rectified current: IO=25A

SPECIFICATIONS

ABSOLUTE MAXIMUM RATINGS at Ta = 25°C (Note 1)

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V _{RM}	600	V
Average Rectified Current Ta = 40°C		6.0	А
Average Rectified Current Ta = 40° C With a $300 \times 300 \times 3.0$ mm ³ Cu fin			
Surge Forward Current 50Hz sine wave, 1cycle	IFSM	400	А
Junction Temperature	Тј	150	°C
Storage Temperature	Tstg	-40 to +150	°C
Insulation Voltage	VIS	2	kV


Note 1 : Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



ON Semiconductor®

www.onsemi.com

ELECTRICAL CONNECTION



MARKING



ORDERING INFORMATION

See detailed ordering and shipping information on page 4 of this data sheet

DBA250G


ELECTRICAL CHARACTERISTICS at Ta = 25°C (Note 2)

Parameter	Symbol	Symbol Conditions	Value			Unit
Falameter	Symbol		min	typ	max	UTIIL
Forward Voltage	٧F	I _F = 12.5A (Note 4)			1.05	V
Reverse Current	IR	V _R : At each V _{RM} (Note 4)			10	μA
Thermal Resistance	Rth(j-c)	Junction-Case			1.5	°C / W

Note 2 : Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Note 3 : Tightening torque : 0.98N·m max.


Note 4 : Per constituent element of bridge.



1.4

PACKAGE DIMENSIONS unit : mm

GBPC 32x32 / DBA250 CASE 160AC ISSUE O



米1 : Lot No. **米**2 : G

DBA250G

ORDERING INFORMATION

Device	Marking	Package	Shipping
DBA250G	BA250G	GBPC 32x32 / DBA250 (Pb-Free)	50pcs / Tray 250pcs / Box

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent re