

# MMBV2101LT1 Series, MV2105, MV2101, MV2109, LV2209

Preferred Device

## Silicon Tuning Diodes

These devices are designed in popular plastic packages for the high volume requirements of FM Radio and TV tuning and AFC, general frequency control and tuning applications. They provide solid-state reliability in replacement of mechanical tuning methods. Also available in a Surface Mount Package up to 33 pF.

### Features

- High Q
- Controlled and Uniform Tuning Ratio
- Standard Capacitance Tolerance – 10%
- Complete Typical Design Curves
- Pb-Free Packages are Available

### MAXIMUM RATINGS

| Rating                                                                                              | Symbol    | Value       | Unit                       |
|-----------------------------------------------------------------------------------------------------|-----------|-------------|----------------------------|
| Reverse Voltage                                                                                     | $V_R$     | 30          | Vdc                        |
| Forward Current                                                                                     | $I_F$     | 200         | mAdc                       |
| Forward Power Dissipation<br>@ $T_A = 25^\circ\text{C}$ MMBV21xx<br>Derate above $25^\circ\text{C}$ | $P_D$     | 225<br>1.8  | mW<br>mW/ $^\circ\text{C}$ |
| @ $T_A = 25^\circ\text{C}$ MV21xx<br>Derate above $25^\circ\text{C}$ LV2209                         |           | 280<br>2.8  | mW<br>mW/ $^\circ\text{C}$ |
| Junction Temperature                                                                                | $T_J$     | +150        | $^\circ\text{C}$           |
| Storage Temperature Range                                                                           | $T_{stg}$ | -55 to +150 | $^\circ\text{C}$           |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)



| Characteristic                                                                                    | Symbol      | Min      | Typ    | Max    | Unit                  |
|---------------------------------------------------------------------------------------------------|-------------|----------|--------|--------|-----------------------|
| Reverse Breakdown Voltage<br>( $I_R = 10 \mu\text{Adc}$ )<br>MMBV21xx, MV21xx<br>LV2209           | $V_{(BR)R}$ | 30<br>25 | –<br>– | –<br>– | Vdc                   |
| Reverse Voltage Leakage Current<br>( $V_R = 25 \text{ Vdc}$ , $T_A = 25^\circ\text{C}$ )          | $I_R$       | –        | –      | 0.1    | $\mu\text{Adc}$       |
| Diode Capacitance Temperature Co-efficient<br>( $V_R = 4.0 \text{ Vdc}$ , $f = 1.0 \text{ MHz}$ ) | $TC_C$      | –        | 280    | –      | ppm/ $^\circ\text{C}$ |



ON Semiconductor®


<http://onsemi.com>

## 6.8–100 pF, 30 VOLTS VOLTAGE VARIABLE CAPACITANCE DIODES



SOT-23 (TO-236)  
CASE 318-08  
STYLE 8

### MARKING DIAGRAMS



xxx = Specific Device Code

M = Date Code\*


▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or overbar may vary depending upon manufacturing location.



TO-92 (TO-226AC)  
CASE 182  
STYLE 1



yyyyyy = Specific Device Code

A = Assembly Location

Y = Year

WW = Work Week

▪ = Pb-Free Package

(Note: Microdot may be in either location)

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

Preferred devices are recommended choices for future use and best overall value.

## MMBV2101LT1 Series, MV2105, MV2101, MV2109, LV2209

| Device       | Marking | Package             | Shipping <sup>†</sup> | C <sub>T</sub> , Diode Capacitance<br>V <sub>R</sub> = 4.0 Vdc, f = 1.0 MHz<br>pF |     |      | Q, Figure of Merit<br>V <sub>R</sub> = 4.0 Vdc,<br>f = 50 MHz | TR, Tuning Ratio<br>C <sub>2</sub> /C <sub>30</sub><br>f = 1.0 MHz |     |     |
|--------------|---------|---------------------|-----------------------|-----------------------------------------------------------------------------------|-----|------|---------------------------------------------------------------|--------------------------------------------------------------------|-----|-----|
|              |         |                     |                       | Min                                                                               | Nom | Max  |                                                               | Min                                                                | Typ | Max |
| MMBV2101LT1  | M4G     | SOT-23              | 3,000 / Tape & Reel   | 6.1                                                                               | 6.8 | 7.5  | 450                                                           | 2.5                                                                | 2.7 | 3.2 |
| MMBV2101LT1G | M4G     | SOT-23<br>(Pb-Free) | 3,000 / Tape & Reel   | 6.1                                                                               | 6.8 | 7.5  | 450                                                           | 2.5                                                                | 2.7 | 3.2 |
| MMBV2101L    | M4G     | SOT-23              | Bulk (Note 1)         | 6.1                                                                               | 6.8 | 7.5  | 450                                                           | 2.5                                                                | 2.7 | 3.2 |
| MV2101       | MV2101  | TO-92               | 1,000 per Box         | 6.1                                                                               | 6.8 | 7.5  | 450                                                           | 2.5                                                                | 2.7 | 3.2 |
| MV2101G      | MV2101  | TO-92<br>(Pb-Free)  | 1,000 per Box         | 6.1                                                                               | 6.8 | 7.5  | 450                                                           | 2.5                                                                | 2.7 | 3.2 |
| MMBV2103LT1  | 4H      | SOT-23              | 3,000 / Tape & Reel   | 9.0                                                                               | 10  | 11   | 400                                                           | 2.5                                                                | 2.9 | 3.2 |
| MMBV2105LT1  | 4U      | SOT-23              | 3,000 / Tape & Reel   | 13.5                                                                              | 15  | 16.5 | 400                                                           | 2.5                                                                | 2.9 | 3.2 |
| MMBV2105LT1G | 4U      | SOT-23<br>(Pb-Free) | 3,000 / Tape & Reel   | 13.5                                                                              | 15  | 16.5 | 400                                                           | 2.5                                                                | 2.9 | 3.2 |
| MMBV2105L    | 4U      | SOT-23              | Bulk (Note 1)         | 13.5                                                                              | 15  | 16.5 | 400                                                           | 2.5                                                                | 2.9 | 3.2 |
| MV2105       | MV2105  | TO-92               | 1,000 per Box         | 13.5                                                                              | 15  | 16.5 | 400                                                           | 2.5                                                                | 2.9 | 3.2 |
| MV2105G      | MV2105  | TO-92<br>(Pb-Free)  | 1,000 per Box         | 13.5                                                                              | 15  | 16.5 | 400                                                           | 2.5                                                                | 2.9 | 3.2 |
| MMBV2107LT1  | 4W      | SOT-23              | 3,000 / Tape & Reel   | 19.8                                                                              | 22  | 24.2 | 350                                                           | 2.5                                                                | 2.9 | 3.2 |
| MMBV2107LT1G | 4W      | SOT-23<br>(Pb-Free) | 3,000 / Tape & Reel   | 19.8                                                                              | 22  | 24.2 | 350                                                           | 2.5                                                                | 2.9 | 3.2 |
| MMBV2107L    | 4W      | SOT-23              | Bulk (Note 1)         | 19.8                                                                              | 22  | 24.2 | 350                                                           | 2.5                                                                | 2.9 | 3.2 |
| MMBV2108LT1  | 4X      | SOT-23              | 3,000 / Tape & Reel   | 24.3                                                                              | 27  | 29.7 | 300                                                           | 2.5                                                                | 3.0 | 3.2 |
| MMBV2108LT1G | 4X      | SOT-23<br>(Pb-Free) | 3,000 / Tape & Reel   | 24.3                                                                              | 27  | 29.7 | 300                                                           | 2.5                                                                | 3.0 | 3.2 |
| LV2209       | LV2209  | TO-92               | 1,000 per Box         | 29.7                                                                              | 33  | 36.3 | 200                                                           | 2.5                                                                | 3.0 | 3.2 |
| MMBV2109LT1  | 4J      | SOT-23              | 3,000 / Tape & Reel   | 29.7                                                                              | 33  | 36.3 | 200                                                           | 2.5                                                                | 3.0 | 3.2 |
| MMBV2109LT1G | 4J      | SOT-23<br>(Pb-Free) | 3,000 / Tape & Reel   | 29.7                                                                              | 33  | 36.3 | 200                                                           | 2.5                                                                | 3.0 | 3.2 |
| MMBV2109L    | 4J      | SOT-23              | Bulk (Note 1)         | 29.7                                                                              | 33  | 36.3 | 200                                                           | 2.5                                                                | 3.0 | 3.2 |
| MV2109       | MV2109  | TO-92               | 1,000 per Box         | 29.7                                                                              | 33  | 36.3 | 200                                                           | 2.5                                                                | 3.0 | 3.2 |
| MV2109G      | MV2109  | TO-92<br>(Pb-Free)  | 1,000 per Box         | 29.7                                                                              | 33  | 36.3 | 200                                                           | 2.5                                                                | 3.0 | 3.2 |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

1. **MMBV2101LT1, MMBV2105LT1, MMBV2107LT1 thru MMBV2109LT1**, are also available in bulk. Use the device title and drop the "T1" suffix when ordering any of these devices in bulk.

### PARAMETER TEST METHODS

#### 1. C<sub>T</sub>, DIODE CAPACITANCE

(C<sub>T</sub> = C<sub>C</sub> + C<sub>J</sub>). C<sub>T</sub> is measured at 1.0 MHz using a capacitance bridge (Boonton Electronics Model 75A or equivalent).

#### 2. TR, TUNING RATIO

TR is the ratio of C<sub>T</sub> measured at 2.0 Vdc divided by C<sub>T</sub> measured at 30 Vdc.

#### 3. Q, FIGURE OF MERIT

Q is calculated by taking the G and C readings of an admittance bridge at the specified frequency and substituting in the following equations:

$$Q = \frac{2\pi f C}{G}$$

(Boonton Electronics Model 33AS8 or equivalent). Use Lead Length  $\approx 1/16''$ .

#### 4. TC<sub>C</sub>, DIODE CAPACITANCE TEMPERATURE COEFFICIENT

TC<sub>C</sub> is guaranteed by comparing C<sub>T</sub> at V<sub>R</sub> = 4.0 Vdc, f = 1.0 MHz, T<sub>A</sub> = -65°C with C<sub>T</sub> at V<sub>R</sub> = 4.0 Vdc, f = 1.0 MHz, T<sub>A</sub> = +85°C in the following equation, which defines TC<sub>C</sub>:

$$TC_C = \left| \frac{C_T(+85^\circ C) - C_T(-65^\circ C)}{85 + 65} \right| \cdot \frac{10^6}{C_T(25^\circ C)}$$

Accuracy limited by measurement of C<sub>T</sub> to  $\pm 0.1$  pF.

TYPICAL DEVICE CHARACTERISTICS




Figure 1. Diode Capacitance versus Reverse Voltage




Figure 2. Normalized Diode Capacitance versus Junction Temperature




Figure 3. Reverse Current versus Reverse Bias Voltage




Figure 4. Figure of Merit versus Reverse Voltage




Figure 5. Figure of Merit versus Frequency

# MECHANICAL CASE OUTLINE

## PACKAGE DIMENSIONS



ON Semiconductor®



SCALE 1:1

TO-92 (TO-226)  
CASE 182-06  
ISSUE L

DATE 04/18/1998



SECTION X-X

### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND ZONE R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.175     | 0.205 | 4.45        | 5.21  |
| B   | 0.170     | 0.210 | 4.32        | 5.33  |
| C   | 0.125     | 0.165 | 3.18        | 4.19  |
| D   | 0.016     | 0.021 | 0.407       | 0.533 |
| G   | 0.050 BSC |       | 1.27 BSC    |       |
| H   | 0.100 BSC |       | 2.54 BSC    |       |
| J   | 0.014     | 0.016 | 0.36        | 0.41  |
| K   | 0.500     | ---   | 12.70       | ---   |
| L   | 0.250     | ---   | 6.35        | ---   |
| N   | 0.080     | 0.105 | 2.03        | 2.66  |
| P   | ---       | 0.050 | ---         | 1.27  |
| R   | 0.115     | ---   | 2.93        | ---   |
| V   | 0.135     | ---   | 3.43        | ---   |

STYLE 1:  
PIN 1. ANODE  
2. CATHODE

STYLE 2:  
PIN 1. CATHODE  
2. ANODE

STYLE 3:  
PIN 1. MAIN TERMINAL 1  
2. MAIN TERMINAL 2

STYLE 4:  
CANCELLED

STYLE 5:  
PIN 1. INPUT  
2. OUTPUT

DOCUMENT NUMBER: 98ASB42118B

Electronic versions are uncontrolled except when accessed directly from the Document Repository.  
Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.

DESCRIPTION: TO-92 (TO-226)

PAGE 1 OF 1


ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

# MECHANICAL CASE OUTLINE

## PACKAGE DIMENSIONS

ON Semiconductor®

ON



### SOT-23 (TO-236) CASE 318-08 ISSUE AS

DATE 30 JAN 2018

SCALE 4:1




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 0.89        | 1.00 | 1.11 | 0.035  | 0.039 | 0.044 |
| A1  | 0.01        | 0.06 | 0.10 | 0.000  | 0.002 | 0.004 |
| b   | 0.37        | 0.44 | 0.50 | 0.015  | 0.017 | 0.020 |
| c   | 0.08        | 0.14 | 0.20 | 0.003  | 0.006 | 0.008 |
| D   | 2.80        | 2.90 | 3.04 | 0.110  | 0.114 | 0.120 |
| E   | 1.20        | 1.30 | 1.40 | 0.047  | 0.051 | 0.055 |
| e   | 1.78        | 1.90 | 2.04 | 0.070  | 0.075 | 0.080 |
| L   | 0.30        | 0.43 | 0.55 | 0.012  | 0.017 | 0.022 |
| L1  | 0.35        | 0.54 | 0.69 | 0.014  | 0.021 | 0.027 |
| HE  | 2.10        | 2.40 | 2.64 | 0.083  | 0.094 | 0.104 |
| T   | 0°          | ---  | 10°  | 0°     | ---   | 10°   |

#### GENERIC MARKING DIAGRAM\*



XXX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

#### RECOMMENDED SOLDERING FOOTPRINT



STYLE 1 THRU 5:  
CANCELLED

STYLE 6:  
PIN 1. BASE  
2. EMITTER  
3. COLLECTOR

STYLE 7:  
PIN 1. EMITTER  
2. BASE  
3. COLLECTOR

STYLE 8:  
PIN 1. ANODE  
2. NO CONNECTION  
3. CATHODE

STYLE 9:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 10:  
PIN 1. DRAIN  
2. SOURCE  
3. GATE

STYLE 11:  
PIN 1. ANODE  
2. CATHODE  
3. CATHODE-ANODE

STYLE 12:  
PIN 1. CATHODE  
2. CATHODE  
3. ANODE

STYLE 13:  
PIN 1. SOURCE  
2. DRAIN  
3. GATE

STYLE 14:  
PIN 1. CATHODE  
2. GATE  
3. ANODE

STYLE 15:  
PIN 1. GATE  
2. CATHODE  
3. ANODE

STYLE 16:  
PIN 1. ANODE  
2. CATHODE  
3. CATHODE

STYLE 17:  
PIN 1. NO CONNECTION  
2. ANODE  
3. CATHODE

STYLE 18:  
PIN 1. NO CONNECTION  
2. CATHODE  
3. ANODE

STYLE 19:  
PIN 1. CATHODE  
2. ANODE  
3. CATHODE-ANODE

STYLE 20:  
PIN 1. CATHODE  
2. ANODE  
3. GATE

STYLE 21:  
PIN 1. GATE  
2. SOURCE  
3. DRAIN

STYLE 22:  
PIN 1. RETURN  
2. OUTPUT  
3. INPUT

STYLE 23:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 24:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE

STYLE 25:  
PIN 1. ANODE  
2. CATHODE  
3. GATE

STYLE 26:  
PIN 1. CATHODE  
2. ANODE  
3. NO CONNECTION

STYLE 27:  
PIN 1. CATHODE  
2. CATHODE  
3. CATHODE

STYLE 28:  
PIN 1. ANODE  
2. ANODE  
3. ANODE

DOCUMENT NUMBER: 98ASB42226B

Electronic versions are uncontrolled except when accessed directly from the Document Repository.  
Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.

DESCRIPTION: SOT-23 (TO-236)

PAGE 1 OF 1

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**onsemi Website:** [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

**North American Technical Support:**

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

**Europe, Middle East and Africa Technical Support:**

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative