Single and Dual Low Voltage, Rail-to-Rail Input and Output, Operational Amplifiers

LMV931, LMV932

The LMV931 Single and LMV932 Dual are CMOS low−voltage operational amplifiers which can operate on single−sided power supplies (1.8 V to 5.0 V) with rail−to−rail input and output swing. Both devices come in small state−of−the−art packages and require very low quiescent current making them ideal for battery−operated, portable applications such as notebook computers and hand−held instruments. Rail−to−Rail operation provides improved signal−to−noise performance plus the small packages allow for closer placement to signal sources thereby reducing noise pickup.

The single LMV931 is offered in space saving SC70−5 package. The dual LMV932 is in either a Micro8 or SOIC package. These small packages are very beneficial for crowded PCB's.

Features

- Performance Specified on Single−Sided Power Supply: 1.8 V, 2.7 V, and 5 V
- Small Packages:
  - LMV931 in a SC−70
  - LMV932 in a Micro8 or SOIC−8
- No Output Crossover Distortion
- Extended Industrial Temperature Range: −40°C to +125°C
- Low Quiescent Current 210 μA, Max Per Channel
- No Output Phase−Reversal from Overdriven Input
- These are Pb−Free Devices

Typical Applications

- Notebook Computers, Portable Battery−Operated Instruments, PDA's
- Active Filters, Low−Side Current Monitoring





Figure 1. Output Voltage Swing vs. Supply Voltage


MARKING DIAGRAMS

LMV931 (Single)




SC−70
CASE 419A






TSOP−5
CASE 483





M = Date Code
A = Assembly Location
Y = Year
W = Work Week
▪ = Pb−Free Package
(Note: Microdot may be in either location)

LMV932 (Dual)




Micro8
CASE 846A





SOIC−8
CASE 751



A = Assembly Location
Y = Year
L = Wafer Lot
W = Work Week
▪ = Pb−Free Package
(Note: Microdot may be in either location)


ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 14 of this data sheet.

© Semiconductor Components Industries, LLC, 2014


PIN CONNECTIONS

SC70−5/TSOP−5



(Top View)

Micro8/SOIC−8



(Top View)

MAXIMUM RATINGS

Symbol	Rating	Value	Unit
V_S	Supply Voltage (Operating Range V_S = 1.8 V to 5.5 V)	5.5	V
V_{IDR}	Input Differential Voltage	±Supply Voltage	V
V_{ICR}	Input Common Mode Voltage Range	−0.5 to (V_{CC}) + 0.5	V
	Maximum Input Current	10	mA
t_{So}	Output Short Circuit (Note 1)	Continuous	
T_J	Maximum Junction Temperature (Operating Range −40°C to 85°C)	150	°C
θ_{JA}	Thermal Resistance: SC−70 TSOP−5 Micro8	280 333 238	°C/W
T_{stg}	Storage Temperature	−65 to 150	°C
	Mounting Temperature (Infrared or Convection ≤ 30 sec)	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

ESD data available upon request.

1. Continuous short−circuit operation to ground at elevated ambient temperature can result in exceeding the maximum allowed junction temperature of 150°C. Output currents in excess of 45 mA over long term may adversely affect reliability. Shorting output to either V_{CC} or V_{EE} will adversely affect reliability.

1.8 V DC ELECTRICAL CHARACTERISTICS (Note 2) Unless otherwise noted, all min/max limits are guaranteed for T_A = 25°C, V_S = 1.8 V, V_{CM} = V_S/2, V_O = V_S/2 and R_L > 1 MΩ. Typical specifications represent the most likely parametric norm.

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Input Offset Voltage	V_{IO}	LMV931 (Single) (−40°C to +125°C)		1	6	mV
		LMV932 (Dual) (−40°C to +125°C)		1	7.5	
Input Offset Voltage Average Drift	TCV_{IO}			5.5		μV/°C
Input Bias Current	I_B	−40°C to +125°C		< 1		nA
Input Offset Current	I_{IO}	−40°C to +125°C		< 1		nA
Supply Current (per Channel)	I_{CC}	In Active Mode		75	185	μA
		−40°C to +125°C			205	
Common Mode Rejection Ratio	CMRR	0 V ≤ V_{CM} ≤ 0.6 V, 1.4 V ≤ V_{CM} ≤ 1.8 V	50	70		dB
		− 40°C to +125°C	50			
		−0.2 V ≤ V_{CM} ≤ 0 V, 1.8 V ≤ V_{CM} ≤ 2 V	50	70		
Power Supply Rejection Ratio	PSRR	1.8 V ≤ V^+ ≤ 5 V, V_{CM} = 0.5 V	50	70		dB
		−40°C to +125°C	50			
Input Common−Mode Voltage Range	VCM	For CMRR ≥ 50 dB and T_A = 25°C	V_{EE} − 0.2	−0.2 to 2.1	V_{CC} + 0.2	V
		For CMRR ≥ 50 dB and T_A = − 40°C to +85°C	V_{EE}		V_{CC}	
		For CMRR ≥ 50 dB and T_A = − 40°C to +125°C	V_{EE} + 0.2		V_{CC} − 0.2	
Large Signal Voltage Gain LMV931 (Single)	A_V	R_L = 600 Ω to 0.9 V, V_O = 0.2 V to 1.6 V, V_{CM} = 0.5 V	77	101		dB
		−40°C to +125°C	73			
		R_L = 2 kΩ to 0.9V, V_O = 0.2 V to 1.6 V, V_{CM} = 0.5 V	80	105		
		−40°C to +125°C	75			
Large Signal Voltage Gain LMV932 (Dual)		R_L = 600 Ω to 0.9 V, V_O = 0.2 V to 1.6 V, V_{CM} = 0.5 V	75	90		
		−40°C to +125°C	72			
		R_L = 2 kΩ to 0.9 V, V_O = 0.2 V to 1.6 V,V_{CM} = 0.5 V	78	100		
		−40°C to +125°C	75			
Output Swing	V_{OH}	R_L = 600 Ω to 0.9V, V_{IN} = ±100 mV	1.65	1.72		V
		−40°C to +125°C	1.63			
	V_{OL}	R_L = 600 Ω to 0.9V, V_{IN} = ±100 mV		0.077	0.105	
		−40°C to +125°C			0.12	
	V_{OH}	R_L = 2 kΩ to 0.9V, V_{IN} = ±100 mV	1.75	1.77		
		−40°C to +125°C	1.74			
	V_{OL}	R_L = 2 kΩ to 0.9 V, V_{IN} = ±100 mV		0.24	0.035	
		−40°C to +125°C			0.04	
Output Short Circuit Current	I_O	Sourcing, Vo = 0 V, V_{IN} = +100 mV	4.0	30		mA
		−40°C to +125°C	3.3			
		Sinking, Vo = 1.8V, V_{IN} = −100 mV	7.0	60		
		−40°C to +125°C	5.0			

2. Guaranteed by design and/or characterization.

1.8 V AC ELECTRICAL CHARACTERISTICS Unless otherwise specified, all limits are guaranteed for T_A = 25°C, V_S = 1.8 V, V_{CM} = V_S/2, Vo = V_S/2 and R_L > 1 MΩ. Typical specifications represent the most likely parametric norm. Min/Max specifications are guaranteed by testing, characterization, or statistical analysis.

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Slew Rate	SR	(Note 3)		0.35		V/μS
Gain Bandwidth Product	GBWP			1.4		MHz
Phase Margin	Θm			67		°
Gain Margin	Gm			7		dB
Input−Referred Voltage Noise	e_n	f = 50 kHz, V_{CM} = 0.5 V		60		nV/$\sqrt{Hz}$
Total Harmonic Distortion	THD	f = 1 kHz, A_V = +1, R_L = 600 Ω, V_O = 1 V_{PP}		0.023		%
Amplifier−to−Amplifier Isolation		(Note 4)		123		dB

3. Connected as voltage follower with input step from V_{EE} to V_{CC}. Number specified is the slower of the positive and negative slew rates.
4. Input referred, R_L = 100 kΩ connected to V_S/2. Each amp excited in turn with 1 kHz to produce V_O = 3 V_{PP}. (For Supply Voltages < 3 V, V_O = V_{CC}).

2.7 V DC ELECTRICAL CHARACTERISTICS (Note 5) Unless otherwise noted, all min/max limits are guaranteed for T_A = 25°C, V_S = 2.7 V, V_{CM} = V_S/2, V_O = V_S/2 and R_L > 1 MΩ. Typical specifications represent the most likely parametric norm.

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Input Offset Voltage	V_{IO}	LMV931 (Single) (−40°C to +125°C)		1	6	mV
		LMV932 (Dual) (−40°C to +125°C)		1	7.5	
Input Offset Voltage Average Drift	TCV_{IO}			5.5		μV/°C
Input Bias Current	I_B	−40°C to +125°C		< 1		nA
Input Offset Current	I_{IO}	−40°C to +125°C		< 1		nA
Supply Current (per Channel)	I_{CC}	In Active Mode		80	190	μA
		−40°C to +125°C			210	
Common Mode Rejection Ratio	CMRR	0 V ≤ V_{CM} ≤ 1.5 V, 2.3 V ≤ V_{CM} ≤ 2.7 V	50	70		dB
		−40°C to +125°C	50			
		−0.2 V ≤ V_{CM} ≤ 0 V, 2.7 V ≤ V_{CM} ≤ 2.9 V	50	70		
Power Supply Rejection Ratio	PSRR	1.8 V ≤ V^+ ≤ 5 V, V_{CM} = 0.5 V	50	70		dB
		−40°C to +125°C	50			
Input Common−Mode Voltage Range	VCM	For CMRR ≥ 50 dB and T_A = 25°C	V_{EE} − 0.2	−0.2 to 3.0	V_{CC} + 0.2	V
		For CMRR ≥ 50 dB and T_A = −40°C to +85°C	V_{EE}		V_{CC}	
		For CMRR ≥ 50 dB and T_A = −40°C to +125°C	V_{EE} + 0.2		V_{CC} − 0.2	
Large Signal Voltage Gain LMV931 (Single)	A_V	R_L = 600 Ω to 1.35 V, V_O = 0.2 V to 2.5 V	87	104		dB
		−40°C to +125°C	86			
		R_L = 2 kΩ to 1.35 V, V_O = 0.2 V to 2.5 V	92	110		
		−40°C to +125°C	91			
Large Signal Voltage Gain LMV932 (Dual)	A_V	R_L = 600 Ω to 1.35 V, V_O = 0.2 V to 2.5 V	78	90		
		−40°C to +125°C	75			
		R_L= 2 kΩ to 1.35 V, V_O = 0.2 V to 2.5 V	81	100		
		−40°C to +125°C	78			
Output Swing	V_{OH}	R_L = 600 Ω to 1.35 V, V_{IN} = ±100 mV	2.55	2.62		V
		−40°C to +125°C	2.53			
	V_{OL}	R_L = 600 Ω to 1.35 V, V_{IN} = ±100 mV		0.083	0.11	
		−40°C to +125°C			0.13	
	V_{OH}	R_L = 2 kΩ to 1.35 V, V_{IN} = ±100 mV	2.65	2.675		
		−40°C to +125°C	2.64			
	V_{OL}	R_L = 2 kΩ to 1.35 V, V_{IN} = ±100 mV		0.025	0.04	
		−40°C to +125°C			0.045	
Output Short Circuit Current	I_O	Sourcing, Vo = 0 V, V_{IN} = ±100 mV	20	65		mA
		−40°C to +125°C	15			
		Sinking, Vo = 0 V, V_{IN} = −100 mV	18	75		
		−40°C to +125°C	12			

5. Guaranteed by design and/or characterization.

2.7 V AC ELECTRICAL CHARACTERISTICS Unless otherwise specified, all limits are guaranteed for T_A = 25°C, V_S = 2.7 V, V_{CM} = V_S/2 ,Vo = V_S/2 and R_L > 1 MΩ. Typical specifications represent the most likely parametric norm. Min/Max specifications are guaranteed by testing, characterization, or statistical analysis.

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Slew Rate	SR	(Note 6)		0.4		V/uS
Gain Bandwidth Product	GBWP			1.4		MHz
Phase Margin	Θm			70		°
Gain Margin	Gm			7.5		dB
Input−Referred Voltage Noise	e_n	f = 50 kHz, V_{CM} = 1.0 V		57		nV/$\sqrt{Hz}$
Total Harmonic Distortion	THD	f = 1 kHz, A_V = +1, R_L = 600 Ω, V_O = 1 V_{PP}		0.022		%
Amplifier−to−Amplifier Isolation		(Note 7)		123		dB

6. Connected as voltage follower with input step from V_{EE} to V_{CC}. Number specified is the slower of the positive and negative slew rates.
7. Input referred, R_L = 100 kΩ connected to V_S/2. Each amp excited in turn with 1 kHz to produce V_O = 3 V_{PP}. (For Supply Voltages < 3 V, V_O = V_{CC}).

5 V DC ELECTRICAL CHARACTERISTICS (Note 8) Unless otherwise noted, all min/max limits are guaranteed for T_A = 25°C, V_S = 5 V, V_{CM} = V_S/2, V_O = V_S/2 and R_L > 1 MΩ. Typical specifications represent the most likely parametric norm.

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Input Offset Voltage	V_{IO}	LMV931 (Single) (−40°C to +125°C)		1	6	mV
		LMV932 (Dual) (−40°C to +125°C)		1	7.5	
Input Offset Voltage Average Drift	TCV_{IO}			5.5		μV/°C
Input Bias Current	I_B	−40°C to +125°C		< 1		nA
Input Offset Current	I_{IO}	−40°C to +125°C		< 1		nA
Supply Current (per Channel)	I_{CC}	In Active Mode		95	210	μA
		−40°C to +125°C			230	
Common−Mode Rejection Ratio	CMRR	0 V ≤ V_{CM} ≤ 3.8 V, 4.6 V ≤ V_{CM} ≤ 5.0 V	50	70		dB
		−40°C to +125°C	50			
		−0.2 V ≤ V_{CM} ≤ 0 V, 5.0 V ≤ V_{CM} ≤ 5. 2V	50	70		
Power Supply Rejection Ratio	PSRR	1.8 V ≤ V^+ ≤ 5 V, V_{CM} = 0.5 V	50	70		dB
		−40°C to +125°C	50			
Input Common−Mode Voltage Range	VCM	For CMRR ≥ 50 dB and T_A = 25°C	V_{EE} − 0.2	−0.2 to 5.3	V_{CC} + 0.2	V
		For CMRR ≥ 50 dB and T_A = −40°C to +85°C	V_{EE}		V_{CC}	
		For CMRR ≥ 50 dB and T_A = −40°C to +125°C	V_{EE} + 0.3		V_{CC} − 0.3	
Large Signal Voltage Gain LMV931 (Single)	A_V	R_L = 600 Ω to 2.5 V, V_O = 0.2 V to 4.8 V	88	102		dB
		−40°C to +125°C	87			
		R_L = 2 kΩ to 2.5 V, V_O = 0.2 V to 4.8 V	94	113		
		−40°C to +125°C	93			
Large Signal Voltage Gain LMV932 (Dual)	A_V	R_L = 600 Ω to 2.5 V, V_O = 0.2 V to 4.8 V	81	90		
		−40°C to +125°C	78			
		R_L = 2 kΩ to 2.5 V, V_O = 0.2 V to 4.8 V	85	100		
		−40°C to +125°C	82			
Output Swing	V_{OH}	R_L = 600 Ω to 2.5 V, V_{IN} = ±100 mV	4.855	4.89		V
		−40°C to +125°C	4.835			
	V_{OL}	R_L = 600 Ω to 2.5 V, V_{IN} = ±100 mV		0.12	0.16	
		−40°C to +125°C			0.18	
	V_{OH}	R_L = 2 kΩ to 2.5 V, V_{IN} = ±100 mV	4.945	4.967		
		−40°C to +125°C	4.935			
	V_{OL}	R_L = 2 kΩ to 2.5 V, V_{IN} = ±100 mV		0.037	0.065	
		−40°C to +125°C			0.075	
Output Short−Circuit Current	I_O	Sourcing, Vo = 0 V, V_{IN} = +100 mV	55	65		mA
		−40°C to +125°C	45			
		Sinking, Vo = 5 V, V_{IN} = −100 mV	58	80		
		−40°C to +125°C	45			

8. Guaranteed by design and/or characterization.

5 V AC ELECTRICAL CHARACTERISTICS Unless otherwise specified, all limits are guaranteed for T_A = 25°C, V_S = 5 V, V_{CM} = V_S/2, Vo = V_S/2 and R_L > 1 MΩ. Typical specifications represent the most likely parametric norm.

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Slew Rate	SR	(Note 9)		0.48		V/uS
Gain Bandwidth Product	GBWP			1.5		MHz
Phase Margin	Θm			65		°
Gain Margin	Gm			8		dB
Input−Referred Voltage Noise	e_n	f = 50 kHz, V_{CM} = 2 V		50		nV/$\sqrt{Hz}$
Total Harmonic Distortion	THD	f = 1 kHz, A_V = +1, R_L = 600 Ω, V_O = 1 V_{PP}		0.022		%
Amplifier−to−Amplifier Isolation		(Note 10)		123		dB

9. Connected as voltage follower with input step from V_{EE} to V_{CC}. Number specified is the slower of the positive and negative slew rates.
10. Input referred, R_L = 100 kΩ connected to V_S/2. Each amp excited in turn with 1 kHz to produce V_O = 3 V_{PP}. (For Supply Voltages < 3 V, V_O = V_{CC}).

TYPICAL CHARACTERISTICS

(T_A = 25°C and V_S = 5 V unless otherwise specified)




Figure 2. Supply Current vs. Supply Voltage




Figure 3. Supply Current vs. Supply Voltage




Figure 4. Sourcing Current vs. Output Voltage (T_A = 25°C)




Figure 5. Sinking Current vs. Output Voltage (T_A = 25°C)




Figure 6. Output Voltage Swing vs. Supply Voltage




Figure 7. Output Voltage vs. Supply Voltage

TYPICAL CHARACTERISTICS

(T_A = 25°C and V_S = 5 V unless otherwise specified)




Figure 8. Open Loop Gain and Phase




Figure 9. Frequency Response vs. CL




Figure 10. Frequency Response vs. CL




Figure 11. Gain and Phase vs. Temp




Figure 12. Gain and Phase vs. Temp

TYPICAL CHARACTERISTICS

(T_A = 25°C and V_S = 5 V unless otherwise specified)




Figure 13. CMRR vs. Frequency




Figure 14. PSRR vs. Frequency




Figure 15. Input Voltage Noise vs. Frequency




Figure 16. THD vs. Frequency




Figure 17. Slew Rate vs. Supply Voltage

TYPICAL CHARACTERISTICS

(T_A = 25°C and V_S = 5 V unless otherwise specified)




Figure 18. Small Signal Transient Response




Figure 19. Small Signal Transient Response




Figure 20. Small Signal Transient Response




Figure 21. Large Signal Transient Response




Figure 22. Large Signal Transient Response




Figure 23. Large Signal Transient Response

TYPICAL CHARACTERISTICS

(T_A = 25°C and V_S = 5 V unless otherwise specified)




Figure 24. Short−Circuit vs. Temperature (Sinking)




Figure 25. Short−Circuit vs. Temperature (Sourcing)




Figure 26. Offset Voltage vs. Common Mode Range V_{DD}




Figure 27. Offset Voltage vs. Common Mode Range




Figure 28. Offset Voltage vs. Common Mode Range

APPLICATION INFORMATION




Figure 29. Voltage Reference





Figure 30. Wien Bridge Oscillator




$$V_{in}L = \frac{R1}{R1 + R2} (V_{OL} - V_{ref}) + V_{ref}$$

$$V_{in}H = \frac{R1}{R1 + R2} (V_{OH} - V_{ref}) + V_{ref}$$

$$H = \frac{R1}{R1 + R2} (V_{OH} - V_{OL})$$

Figure 31. Comparator with Hysteresis



Given: f_o = center frequency
$A(f_o)$ = gain at center frequency

Choose value f_o, C

Then : $R3 = \frac{Q}{\pi f_O C}$

$$R1 = \frac{R3}{2\,A(f_O)}$$

$$R2 = \frac{R1\,R3}{4Q^2\,R1 - R3}$$

For less than 10% error from operational amplifier, $((Q_O\,f_O)/BW) < 0.1$ where f_o and BW are expressed in Hz. If source impedance varies, filter may be preceded with voltage follower buffer to stabilize filter parameters.

Figure 32. Multiple Feedback Bandpass Filter

ORDERING INFORMATION

Order Number	Number of Channels	Number of Pins	Package Type	Shipping†
LMV931SQ3T2G	Single	5	SC70−5 (Pb−Free)	3000 / Tape & Reel
LMV931SN3T1G	Single	5	TSOP−5 (Pb−Free)	3000 / Tape & Reel
LMV932DMR2G	Dual	8	Micro8 (Pb−Free)	4000 / Tape & Reel
LMV932DR2G	Dual	8	SOIC−8 (Pb−Free)	2500 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS

ON Semiconductor®

SC−88A (SC−70−5/SOT−353)
CASE 419A−02
ISSUE L

SCALE 2:1


DATE 17 JAN 2013




NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A−01 OBSOLETE. NEW STANDARD 419A−02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.071	0.087	1.80	2.20
B	0.045	0.053	1.15	1.35
C	0.031	0.043	0.80	1.10
D	0.004	0.012	0.10	0.30
G	0.026 BSC		0.65 BSC	
H	---	0.004	---	0.10
J	0.004	0.010	0.10	0.25
K	0.004	0.012	0.10	0.30
N	0.008 REF		0.20 REF	
S	0.079	0.087	2.00	2.20

SOLDER FOOTPRINT



GENERIC MARKING DIAGRAM*



XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. BASE
2. EMITTER
3. BASE
4. COLLECTOR
5. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. EMITTER
3. BASE
4. COLLECTOR
5. CATHODE

STYLE 3:
PIN 1. ANODE 1
2. N/C
3. ANODE 2
4. CATHODE 2
5. CATHODE 1

STYLE 4:
PIN 1. SOURCE 1
2. DRAIN 1/2
3. SOURCE 1
4. GATE 1
5. GATE 2

STYLE 5:
PIN 1. CATHODE
2. COMMON ANODE
3. CATHODE 2
4. CATHODE 3
5. CATHODE 4

STYLE 6:
PIN 1. EMITTER 2
2. BASE 2
3. EMITTER 1
4. COLLECTOR
5. COLLECTOR 2/BASE 1

STYLE 7:
PIN 1. BASE
2. EMITTER
3. BASE
4. COLLECTOR
5. COLLECTOR

STYLE 8:
PIN 1. CATHODE
2. COLLECTOR
3. N/C
4. BASE
5. EMITTER

STYLE 9:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. ANODE
5. ANODE

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.


DOCUMENT NUMBER:	98ASB42984B	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	SC−88A (SC−70−5/SOT−353)	PAGE 1 OF 1

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS


ON Semiconductor®




SCALE 2:1

TSOP−5
CASE 483
ISSUE N


DATE 12 AUG 2020




TOP VIEW



DETAIL Z



SIDE VIEW




END VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE. DIMENSION A.
5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.

	MILLIMETERS	
DIM	MIN	MAX
A	2.85	3.15
B	1.35	1.65
C	0.90	1.10
D	0.25	0.50
G	0.95 BSC	
H	0.01	0.10
J	0.10	0.26
K	0.20	0.60
M	0 °	10 °
S	2.50	3.00


SOLDERING FOOTPRINT*




SCALE 10:1 (mm / inches)

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



Analog



Discrete/Logic

XXX = Specific Device Code
A = Assembly Location
Y = Year
W = Work Week
▪ = Pb−Free Package

XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

DOCUMENT NUMBER:	98ARB18753C	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	TSOP−5	PAGE 1 OF 1

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018


MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS



SCALE 1:1

SOIC−8 NB
CASE 751−07
ISSUE AK


DATE 16 FEB 2011



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751−01 THRU 751−06 ARE OBSOLETE. NEW STANDARD IS 751−07.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	4.80	5.00	0.189	0.197
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.053	0.069
D	0.33	0.51	0.013	0.020
G	1.27 BSC		0.050 BSC	
H	0.10	0.25	0.004	0.010
J	0.19	0.25	0.007	0.010
K	0.40	1.27	0.016	0.050
M	0 °	8 °	0 °	8 °
N	0.25	0.50	0.010	0.020
S	5.80	6.20	0.228	0.244


SOLDERING FOOTPRINT*



SCALE 6:1 (mm / inches)

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



IC | IC (Pb−Free) | Discrete | Discrete (Pb−Free)

XXXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

XXXXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42564B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**SOIC−8 NB**	**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

SOIC−8 NB
CASE 751−07
ISSUE AK

DATE 16 FEB 2011

STYLE 1:
PIN 1. EMITTER
2. COLLECTOR
3. COLLECTOR
4. EMITTER
5. EMITTER
6. BASE
7. BASE
8. EMITTER

STYLE 2:
PIN 1. COLLECTOR, DIE, #1
2. COLLECTOR, #1
3. COLLECTOR, #2
4. COLLECTOR, #2
5. BASE, #2
6. EMITTER, #2
7. BASE, #1
8. EMITTER, #1

STYLE 3:
PIN 1. DRAIN, DIE #1
2. DRAIN, #1
3. DRAIN, #2
4. DRAIN, #2
5. GATE, #2
6. SOURCE, #2
7. GATE, #1
8. SOURCE, #1

STYLE 4:
PIN 1. ANODE
2. ANODE
3. ANODE
4. ANODE
5. ANODE
6. ANODE
7. ANODE
8. COMMON CATHODE

STYLE 5:
PIN 1. DRAIN
2. DRAIN
3. DRAIN
4. DRAIN
5. GATE
6. GATE
7. SOURCE
8. SOURCE

STYLE 6:
PIN 1. SOURCE
2. DRAIN
3. DRAIN
4. SOURCE
5. SOURCE
6. GATE
7. GATE
8. SOURCE

STYLE 7:
PIN 1. INPUT
2. EXTERNAL BYPASS
3. THIRD STAGE SOURCE
4. GROUND
5. DRAIN
6. GATE 3
7. SECOND STAGE Vd
8. FIRST STAGE Vd

STYLE 8:
PIN 1. COLLECTOR, DIE #1
2. BASE, #1
3. BASE, #2
4. COLLECTOR, #2
5. COLLECTOR, #2
6. EMITTER, #2
7. EMITTER, #1
8. COLLECTOR, #1

STYLE 9:
PIN 1. EMITTER, COMMON
2. COLLECTOR, DIE #1
3. COLLECTOR, DIE #2
4. EMITTER, COMMON
5. EMITTER, COMMON
6. BASE, DIE #2
7. BASE, DIE #1
8. EMITTER, COMMON

STYLE 10:
PIN 1. GROUND
2. BIAS 1
3. OUTPUT
4. GROUND
5. GROUND
6. BIAS 2
7. INPUT
8. GROUND

STYLE 11:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. DRAIN 2
7. DRAIN 1
8. DRAIN 1

STYLE 12:
PIN 1. SOURCE
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 13:
PIN 1. N.C.
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 14:
PIN 1. N−SOURCE
2. N−GATE
3. P−SOURCE
4. P−GATE
5. P−DRAIN
6. P−DRAIN
7. N−DRAIN
8. N−DRAIN

STYLE 15:
PIN 1. ANODE 1
2. ANODE 1
3. ANODE 1
4. ANODE 1
5. CATHODE, COMMON
6. CATHODE, COMMON
7. CATHODE, COMMON
8. CATHODE, COMMON

STYLE 16:
PIN 1. EMITTER, DIE #1
2. BASE, DIE #1
3. EMITTER, DIE #2
4. BASE, DIE #2
5. COLLECTOR, DIE #2
6. COLLECTOR, DIE #2
7. COLLECTOR, DIE #1
8. COLLECTOR, DIE #1

STYLE 17:
PIN 1. VCC
2. V2OUT
3. V1OUT
4. TXE
5. RXE
6. VEE
7. GND
8. ACC

STYLE 18:
PIN 1. ANODE
2. ANODE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. CATHODE
8. CATHODE

STYLE 19:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. MIRROR 2
7. DRAIN 1
8. MIRROR 1

STYLE 20:
PIN 1. SOURCE (N)
2. GATE (N)
3. SOURCE (P)
4. GATE (P)
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 21:
PIN 1. CATHODE 1
2. CATHODE 2
3. CATHODE 3
4. CATHODE 4
5. CATHODE 5
6. COMMON ANODE
7. COMMON ANODE
8. CATHODE 6

STYLE 22:
PIN 1. I/O LINE 1
2. COMMON CATHODE/VCC
3. COMMON CATHODE/VCC
4. I/O LINE 3
5. COMMON ANODE/GND
6. I/O LINE 4
7. I/O LINE 5
8. COMMON ANODE/GND

STYLE 23:
PIN 1. LINE 1 IN
2. COMMON ANODE/GND
3. COMMON ANODE/GND
4. LINE 2 IN
5. LINE 2 OUT
6. COMMON ANODE/GND
7. COMMON ANODE/GND
8. LINE 1 OUT

STYLE 24:
PIN 1. BASE
2. EMITTER
3. COLLECTOR/ANODE
4. COLLECTOR/ANODE
5. CATHODE
6. CATHODE
7. COLLECTOR/ANODE
8. COLLECTOR/ANODE

STYLE 25:
PIN 1. VIN
2. N/C
3. REXT
4. GND
5. IOUT
6. IOUT
7. IOUT
8. IOUT

STYLE 26:
PIN 1. GND
2. dv/dt
3. ENABLE
4. ILIMIT
5. SOURCE
6. SOURCE
7. SOURCE
8. VCC

STYLE 27:
PIN 1. ILIMIT
2. OVLO
3. UVLO
4. INPUT+
5. SOURCE
6. SOURCE
7. SOURCE
8. DRAIN

STYLE 28:
PIN 1. SW_TO_GND
2. DASIC_OFF
3. DASIC_SW_DET
4. GND
5. V_MON
6. VBULK
7. VBULK
8. VIN

STYLE 29:
PIN 1. BASE, DIE #1
2. EMITTER, #1
3. BASE, #2
4. EMITTER, #2
5. COLLECTOR, #2
6. COLLECTOR, #2
7. COLLECTOR, #1
8. COLLECTOR, #1

STYLE 30:
PIN 1. DRAIN 1
2. DRAIN 1
3. GATE 2
4. SOURCE 2
5. SOURCE 1/DRAIN 2
6. SOURCE 1/DRAIN 2
7. SOURCE 1/DRAIN 2
8. GATE 1


DOCUMENT NUMBER:	**98ASB42564B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOIC−8 NB**		**PAGE 2 OF 2**

onsemi and ONSEMI. are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS


ON Semiconductor®




SCALE 2:1

Micro8
CASE 846A−02
ISSUE K


DATE 16 JUL 2020





NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.10 mm IN EXCESS OF MAXIMUM MATERIAL CONDITION.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSION OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 mm PER SIDE. DIMENSION E DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 mm PER SIDE. DIMENSIONS D AND E ARE DETERMINED AT DATUM F.
5. DATUMS A AND B ARE TO BE DETERMINED AT DATUM F.
6. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.




RECOMMENDED
MOUNTING FOOTPRINT

For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	---	---	1.10
A1	0.05	0.08	0.15
b	0.25	0.33	0.40
c	0.13	0.18	0.23
D	2.90	3.00	3.10
E	2.90	3.00	3.10
e	0.65 BSC		
H_E	4.75	4.90	5.05
L	0.40	0.55	0.70

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
W = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. SOURCE
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 2:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. DRAIN 2
7. DRAIN 1
8. DRAIN 1

STYLE 3:
PIN 1. N-SOURCE
2. N-GATE
3. P-SOURCE
4. P-GATE
5. P-DRAIN
6. P-DRAIN
7. N-DRAIN
8. N-DRAIN

DOCUMENT NUMBER:	**98ASB14087C**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**MICRO8**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊