NL17SG373

Low-Power D-Type Transparent Latch with 3-State Output

The NL17SG373 MiniGate™ is an advanced high−speed CMOS D−Type Transparent Latch with 3−State Output in ultra−small footprint.

The NL17SG373 input structures provide protection when voltages up to 5.5 V are applied, regardless of the supply voltage.

This device is fully specified for partial power−down applications using I_{OFF}. The I_{OFF} circuitry disables the output, preventing the damaging backflow current through the device when it is powered down.

Features

- Wide Operating V_{CC} Range: 0.9 V to 3.6 V
- High Speed: t_{PD} = 2.4 ns (Typ) @ V_{CC} = 3.0 V, C_L = 15 pF
- Low Power Dissipation: I_{CC} = 0.5 μA (Max) at T_A = 25°C
- 5.5 V Overvoltage Tolerant (OVT) Input Pins
- Ultra−Small Packages
- These Devices are Pb−Free and are RoHS Compliant




Figure 1. SC88 (Top View)





Figure 2. Logic Symbol


ON Semiconductor®

www.onsemi.com

MARKING DIAGRAMS



SC−88
DF SUFFIX
CASE 419B



AG = Device Code
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation and/or position may vary depending upon manufacturing location.

PIN ASSIGNMENT

Pin	Function
1	LE
2	GND
3	D
4	Q
5	V_{CC}
6	$\overline{OE}$

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 9 of this data sheet.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

FUNCTION TABLE

Input				Output	
$\overline{OE}$	LE	D	Internal Latch	Q	Operating Mode
L	H	L	L	L	Enable and Read Register
L	H	H	H	H	(Transparent Mode)
L	L	X	L	L	Latch and Read Register
L	L	X	H	H	
H	X	X	X	Z	Latch Register and Disable Output

MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CC}	DC Supply Voltage	−0.5 to +5.5	V
V_{IN}	DC Input Voltage	−0.5 to +5.5	V
V_{OUT}	DC Output Voltage	−0.5 to V_{CC} + 0.5	V
I_{IK}	DC Input Diode Current V_{IN} < GND	−50	mA
I_{OK}	DC Output Diode Current V_{OUT} < GND, V_{OUT} > V_{CC}	±50	mA
I_O	DC Output Source/Sink Current	±20	mA
I_{CC}	DC Supply Current Per Supply Pin	±50	mA
I_{GND}	DC Ground Current per Ground Pin	±50	mA
T_{STG}	Storage Temperature Range	−65 to +150	°C
T_L	Lead Temperature, 1 mm from Case for 10 Seconds	260	°C
T_J	Junction Temperature Under Bias	150	°C
MSL	Moisture Sensitivity	Level 1	
F_R	Flammability Rating Oxygen Index: 28 to 34	UL 94 V−0 @ 0.125 in	
V_{ESD}	ESD Withstand Voltage Human Body Mode (Note 2) Machine Model (Note 3)	> 3000 > 200	V
$I_{LATCHUP}$	Latchup Performance Above V_{CC} and Below GND at 125°C (Note 4)	±100	mA

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm−by−1 inch, 2 ounce copper trace no air flow.
2. Tested to EIA / JESD22−A114−A.
3. Tested to EIA / JESD22−A115−A.
4. Tested to EIA / JESD78.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
V_{CC}	Positive DC Supply Voltage	0.9	3.6	V
V_{IN}	Digital Input Voltage	0	3.6	V
V_{OUT}	Output Voltage Active Mode	0	V_{CC}	V
T_A	Operating Free−Air Temperature	−55	+125	°C
$\Delta t / \Delta V$	Input Transition Rise or Fail Rate V_{CC} = 3.3 V ± 0.3 V	0	10	nS/V

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions		V_{CC} (V)	T_A = 25°C			T_A = −55°C to +125°C		Unit
					Min	Typ	Max	Min	Max	
V_{IH}	High−Level Input Voltage			0.9	V_{CC}			V_{CC}		V
				1.1 to 1.3	0.7 x V_{CC}			0.7 x V_{CC}		
				1.4 to 1.6	0.65 x V_{CC}			0.65 x V_{CC}		
				1.65 to 1.95	0.65 x V_{CC}			0.65 x V_{CC}		
				2.3 to 2.7	1.7			1.7		
				3.0 to 3.6	2.0			2.0		
V_{IL}	Low−Level Input Voltage			0.9			GND		GND	V
				1.1 to 1.3			0.3 x V_{CC}		0.3 x V_{CC}	
				1.4 to 1.6			0.35 x V_{CC}		0.35 x V_{CC}	
				1.65 to 1.95			0.35 x V_{CC}		0.35 x V_{CC}	
				2.3 to 2.7			0.7		0.7	
				3.0 to 3.6			0.8		0.8	
V_{OH}	High−Level Output Voltage	V_{IN} = V_{IH} or V_{IL}	I_{OH} = −20 μA	0.9	0.75			0.75		V
			I_{OH} = −0.3 mA	1.1 to 1.3	0.75 x V_{CC}			0.75 x V_{CC}		
			I_{OH} = −1.7 mA	1.4 to 1.6	0.75 x V_{CC}			0.75 x V_{CC}		
			I_{OH} = −3.0 mA	1.65 to 1.95	V_{CC} − 0.45			V_{CC} − 0.45		
			I_{OH} = −4.0 mA	2.3 to 2.7	2.0			2.0		
			I_{OH} = −8.0 mA	3.0 to 3.6	2.48			2.48		
V_{OL}	Low−Level Output Voltage	V_{IN} = V_{IH} or V_{IL}	I_{OL} = 20 μA	0.9			0.1		0.1	V
			I_{OL} = 0.3 mA	1.1 to 1.3			0.25 x V_{CC}		0.25 x V_{CC}	
			I_{OL} = 1.7 mA	1.4 to 1.6			0.25 x V_{CC}		0.25 x V_{CC}	
			I_{OL} = 3.0 mA	1.65 to 1.95			0.45		0.45	
			I_{OL} = 4.0 mA	2.3 to 2.7			0.4		0.4	
			I_{OL} = 8.0 mA	3.0 to 3.6			0.4		0.4	
I_{IN}	Input Leakage Current	0 ≤ V_{IN} ≤ 3.6 V		0 to 3.6			±0.1		±0.5	μA
I_{CC}	Quiescent Supply Current	V_{IN} = V_{CC} or GND		3.6			0.5		10	μA
I_{OZ}	3−State Output Leakage Current	V_{IN} = V_{IH} or V_{IL}; V_{OUT} = 0 to 3.6 V		0.9 to 3.6			0.1		1	μA

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3.0$ ns)

Symbol	Parameter	Test Condition	V_{CC} (V)	T_A = 25 °C			T_A = −55°C to +125°C		Unit
				Min	Typ	Max	Min	Max	
t_{PLH}, t_{PHL}	Propagation Delay, D to Q	C_L = 10 pF, R_L = 1 MΩ	0.9	–	15.3	–	–	–	ns
			1.1 to 1.3	–	6.3	12.3	1.0	14.4	
			1.4 to 1.6	–	4.4	8.1	1.0	9.4	
			1.65 to 1.95	–	3.6	6.2	0.5	6.7	
			2.3 to 2.7	–	2.6	3.9	0.5	4.4	
			3.0 to 3.6	–	2.1	3.1	0.5	3.7	
		C_L = 15 pF, R_L = 1 MΩ	0.9	–	17.7	–	–	–	ns
			1.1 to 1.3	–	7.1	13.6	1.0	15.6	
			1.4 to 1.6	–	5.0	9.2	1.0	10.4	
			1.65 to 1.95	–	4.1	6.9	1.0	7.1	
			2.3 to 2.7	–	2.9	4.4	0.5	5.0	
			3.0 to 3.6	–	2.4	3.4	0.5	3.9	
		C_L = 30 pF, R_L = 1 MΩ	0.9	–	29	–	–	–	ns
			1.1 to 1.3	–	9.3	17.3	1.0	21.2	
			1.4 to 1.6	–	6.4	11.6	1.0	12.6	
			1.65 to 1.95	–	5.3	9.1	1.0	9.6	
			2.3 to 2.7	–	4	5.7	1.0	6.1	
			3.0 to 3.6	–	3.3	4.4	1.0	4.8	
t_{PLH}, t_{PHL}	Propagation Delay, LE to Q	C_L = 10 pF, R_L = 1 MΩ	0.9	–	15.3	–	–	–	ns
			1.1 to 1.3	–	6.3	12.3	1.0	14.4	
			1.4 to 1.6	–	4.4	8.1	1.0	9.4	
			1.65 to 1.95	–	3.6	6.2	0.5	6.7	
			2.3 to 2.7	–	2.6	3.9	0.5	4.4	
			3.0 to 3.6	–	2.1	3.1	0.5	3.7	
		C_L = 15 pF, R_L = 1 MΩ	0.9	–	17.7	–	–	–	ns
			1.1 to 1.3	–	7.1	13.6	1.0	15.6	
			1.4 to 1.6	–	5.0	9.2	1.0	10.4	
			1.65 to 1.95	–	4.1	6.9	1.0	7.1	
			2.3 to 2.7	–	2.9	4.4	0.5	5.0	
			3.0 to 3.6	–	2.4	3.4	0.5	3.9	
		C_L = 30 pF, R_L = 1 MΩ	0.9	–	29	–	–	–	ns
			1.1 to 1.3	–	9.3	17.3	1.0	21.2	
			1.4 to 1.6	–	6.4	11.6	1.0	12.6	
			1.65 to 1.95	–	5.3	9.1	1.0	9.6	
			2.3 to 2.7	–	4	5.7	1.0	6.1	
			3.0 to 3.6	–	3.3	4.4	1.0	4.8	

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3.0$ ns)

Symbol	Parameter	Test Condition	V_{CC} (V)	T_A = 25 °C			T_A = −55°C to +125°C		Unit
				Min	Typ	Max	Min	Max	
t_{PZH}, t_{PZL}	Output Enable Time, $\overline{OE}$ to Q	C_L = 10 pF, R_L = 5 kΩ	0.9	–	18.9	–	–	–	ns
			1.1 to 1.3	–	6.0	10.2	1	10.6	
			1.4 to 1.6	–	4.5	6.5	1	7.0	
			1.65 to 1.95	–	3.9	5.4	1	5.8	
			2.3 to 2.7	–	2.5	3.5	1	3.8	
			3.0 to 3.6	–	2.1	2.7	1	3	
		C_L = 15 pF, R_L = 5 kΩ	0.9	–	22	–	–	–	ns
			1.1 to 1.3	–	6.8	11.6	1	12.1	
			1.4 to 1.6	–	5.1	7.2	1	7.9	
			1.65 to 1.95	–	4.4	6.1	1	6.5	
			2.3 to 2.7	–	2.9	3.9	1	4.2	
			3.0 to 3.6	–	2.3	3	1	3.3	
		C_L = 30 pF, R_L = 5 kΩ	0.9	–	31.8	–	–	–	ns
			1.1 to 1.3	–	9.1	15.7	1	16.2	
			1.4 to 1.6	–	6.7	9.5	1	10.5	
			1.65 to 1.95	–	5.7	7.9	1	8.6	
			2.3 to 2.7	–	3.8	5	1	5.5	
			3.0 to 3.6	–	2.9	3.8	1	4.2	
t_{PHZ}, t_{PLZ}	Output Disable Time, $\overline{OE}$ to Q	C_L = 10 pF, R_L = 5 kΩ	0.9	–	11.3	–	–	–	ns
			1.1 to 1.3	–	5.3	8.3	1	8.4	
			1.4 to 1.6	–	4.1	5.8	1	6.1	
			1.65 to 1.95	–	4.2	5.7	1	5.9	
			2.3 to 2.7	–	3.0	4	1	4.2	
			3.0 to 3.6	–	3.4	4.7	1	5	
		C_L = 15 pF, R_L = 5 kΩ	0.9	–	11	–	–	–	ns
			1.1 to 1.3	–	5.8	8.2	1	11	
			1.4 to 1.6	–	3.9	5.9	1	8	
			1.65 to 1.95	–	4.5	6.6	1	7.4	
			2.3 to 2.7	–	3.2	4.3	1	5.1	
			3.0 to 3.6	–	4.8	6.2	1	6.7	
		C_L = 30 pF, R_L = 5 kΩ	0.9	–	17.7	–	–	–	ns
			1.1 to 1.3	–	9.9	15.7	1	16	
			1.4 to 1.6	–	7.7	10.8	1	11.6	
			1.65 to 1.95	–	6	12.9	1	12.9	
			2.3 to 2.7	–	5	9.1	1	9.5	
			3.0 to 3.6	–	4	12.5	1	13	

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3.0$ ns)


Symbol	Parameter	Test Condition	V_{CC} (V)	T_A = 25 °C			T_A = −55°C to +125°C		Unit
				Min	Typ	Max	Min	Max	
C_{IN}	Input Capacitance		0 to 3.6		1.5	–	–	–	pF
C_O	Output Capacitance	V_O = GND	0		3	–	–	–	pF
C_{PD}	Power dissipation Capacitance (Note 5)	f =10 MHz; V_I = GND to V_{CC}	0.9	–	1.6	–		–	pF
			1.1 to 1.3	–	1.7	–		–	
			1.4 to 1.6	–	1.8	–		–	
			1.65 to 1.95	–	1.9	–		–	
			2.3 to 2.7	–	2.2	–		–	
			3.0 to 3.6	–	2.7	–		–	

5. C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the dynamic operating current consumption without load. Average operating current can be obtained by the equation $I_{CC(OPR)} = C_{PD} \bullet V_{CC} \bullet f_{in} + I_{CC}$. C_{PD} is used to determine the no−load dynamic power consumption: $P_D = C_{PD} \bullet V_{CC}^2 \bullet f_{in} + I_{CC} \bullet V_{CC}$.

TIMING REQUIREMENTS (Input $t_r = t_f = 3.0$ ns; C_L = 5 pF, 10 pF, 15 pF and 20 pF)


Symbol	Parameter	Test Condition	V_{CC} (V)	T_A = 25 °C			T_A = −55°C to +125°C		Unit
				Min	Typ	Max	Min	Max	
t_W	Pulse Width, LE	High	0.9	–	4.0	–	–	–	ns
			1.1 to 1.3	–	0.7	–	2.1	–	
			1.4 to 1.6	–	0.5	–	1.3	–	
			1.65 to 1.95	–	0.4	–	1.0	–	
			2.3 to 2.7	–	0.3	–	0.8	–	
			3.0 to 3.6	–	0.2	–	0.8	–	
t_{SU}	Set−Up Time, D to LE	High or Low	0.9	–	2.1	–	–	–	ns
			1.1 to 1.3	–	0.5	–	2.7	–	
			1.4 to 1.6	–	0.3	–	1.5	–	
			1.65 to 1.95	–	0.3	–	1.2	–	
			2.3 to 2.7	–	0.2	–	0.9	–	
			3.0 to 3.6	–	0.2	–	0.7	–	
t_H	Hold Time D to LE	High or Low	0.9	–	−2.8	–	–	–	ns
			1.1 to 1.3	–	−0.7	–	−0.1	–	
			1.4 to 1.6	–	−0.4	–	−0.1	–	
			1.65 to 1.95	–	−0.4	–	0	–	
			2.3 to 2.7	–	−0.3	–	0.2	–	
			3.0 to 3.6	–	−0.4	–	0.3	–	

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION




Characteristics	Switch
t_{pLH}, t_{pHL}	Open
t_{pLZ}, t_{pZL}	V_{CC} × 2
t_{pHZ}, t_{pZH}	GND

Figure 3. Test Circuit




Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 4. t_{PLH}, t_{PHL} Waveforms (D to Q)



Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 5. t_{PLH}, t_{PHL}, t_W Waveforms (LE to Q)




Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 6. t_{SU}, t_H Waveforms (D to LE)

MEASUREMENT POINTS FOR FIGURES 4, 5 AND 6

Supply Voltage	Input			Output
V_{CC}	V_M	V_I	$t_r = t_f$	V_M
0.9 V to 3.6 V	0.5 x V_{CC}	V_{CC}	≤ 3.0 ns	0.5 x V_{CC}



Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 7. t_{PLZ}, t_{PHZ}, t_{PZH}, t_{PZL} Waveforms ($\overline{OE}$ to Q)

MEASUREMENT POINTS FOR FIGURE 7

Supply Voltage	Input			Output		
V_{CC}	V_M	V_I	$t_r = t_f$	V_M	V_X	V_Y
0.9 V	0.5 x V_{CC}	V_{CC}	≤ 3.0 ns	0.5 x V_{CC}	V_{OL} + 0.1 V	V_{OH} − 0.1 V
1.1 V to 1.3 V	0.5 x V_{CC}	V_{CC}	≤ 3.0 ns	0.5 x V_{CC}	V_{OL} + 0.1 V	V_{OH} − 0.1 V
1.4 V to 1.6 V	0.5 x V_{CC}	V_{CC}	≤ 3.0 ns	0.5 x V_{CC}	V_{OL} + 0.1 V	V_{OH} − 0.1 V
1.65 V to 1.95 V	0.5 x V_{CC}	V_{CC}	≤ 3.0 ns	0.5 x V_{CC}	V_{OL} + 0.15 V	V_{OH} − 0.15 V
2.3 V to 2.7 V	0.5 x V_{CC}	V_{CC}	≤ 3.0 ns	0.5 x V_{CC}	V_{OL} + 0.15 V	V_{OH} − 0.15 V
3.0 V to 3.6 V	0.5 x V_{CC}	V_{CC}	≤ 3.0 ns	0.5 x V_{CC}	V_{OL} + 0.3 V	V_{OH} − 0.3 V

NEW DESIGN

ORDERING INFORMATION

Device	Package	Shipping†
NL17SG373DFT2G	SC−88 / SOT−363 / SC−70−6 (Pb−Free)	3000 / Tape & Reel


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION




SC−88 2.00x1.25x0.90, 0.65P
CASE 419B−02
ISSUE Z


DATE 18 APR 2024




TOP VIEW



SIDE VIEW



END VIEW




DETAIL A
SCALE 2:1

NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5−2018.
2. ALL DIMENSION ARE IN MILLIMETERS.
3. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.20 PER END.
4. DIMENSIONS D AND E1 AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AND DATUM H.
5. DATUMS A AND B ARE DETERMINED AT DATUM H.
6. DIMENSIONS b AND c APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08 AND 0.15 FROM THE TIP.
7. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 TOTAL IN EXCESS OF DIMENSION b AT MAXIMUM MATERIAL CONDITION. THE DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT.


	MILLIMETERS		
DIM	MIN.	NOM.	MAX.
A	−−−	−−−	1.10
A1	0.00	−−−	0.10
A2	0.70	0.90	1.00
b	0.15	0.20	0.25
c	0.08	0.15	0.22
D	2.00 BSC		
E	2.10 BSC		
E1	1.25 BSC		
e	0.65 BSC		
L	0.26	0.36	0.46
L2	0.15 BSC		
aaa	0.15		
bbb	0.30		
ccc	0.10		
ddd	0.10		



RECOMMENDED MOUNTING FOOTPRINT*

* FOR ADDITIONAL INFORMATION ON OUR Pb−FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ONSEMI SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXX = Specific Device Code
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation and/or position may vary depending upon manufacturing location.

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42985B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**SC−88 2.00x1.25x0.90, 0.65P**		**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

SC−88 2.00x1.25x0.90, 0.65P
CASE 419B−02
ISSUE Z

DATE 18 APR 2024

STYLE 1:
PIN 1. EMITTER 2
2. BASE 2
3. COLLECTOR 1
4. EMITTER 1
5. BASE 1
6. COLLECTOR 2

STYLE 2:
CANCELLED

STYLE 3:
CANCELLED

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. COLLECTOR
4. EMITTER
5. BASE
6. ANODE

STYLE 5:
PIN 1. ANODE
2. ANODE
3. COLLECTOR
4. EMITTER
5. BASE
6. CATHODE

STYLE 6:
PIN 1. ANODE 2
2. N/C
3. CATHODE 1
4. ANODE 1
5. N/C
6. CATHODE 2

STYLE 7:
PIN 1. SOURCE 2
2. DRAIN 2
3. GATE 1
4. SOURCE 1
5. DRAIN 1
6. GATE 2

STYLE 8:
CANCELLED

STYLE 9:
PIN 1. EMITTER 2
2. EMITTER 1
3. COLLECTOR 1
4. BASE 1
5. BASE 2
6. COLLECTOR 2

STYLE 10:
PIN 1. SOURCE 2
2. SOURCE 1
3. GATE 1
4. DRAIN 1
5. DRAIN 2
6. GATE 2

STYLE 11:
PIN 1. CATHODE 2
2. CATHODE 2
3. ANODE 1
4. CATHODE 1
5. CATHODE 1
6. ANODE 2

STYLE 12:
PIN 1. ANODE 2
2. ANODE 2
3. CATHODE 1
4. ANODE 1
5. ANODE 1
6. CATHODE 2

STYLE 13:
PIN 1. ANODE
2. N/C
3. COLLECTOR
4. EMITTER
5. BASE
6. CATHODE

STYLE 14:
PIN 1. VREF
2. GND
3. GND
4. IOUT
5. VEN
6. VCC

STYLE 15:
PIN 1. ANODE 1
2. ANODE 2
3. ANODE 3
4. CATHODE 3
5. CATHODE 2
6. CATHODE 1

STYLE 16:
PIN 1. BASE 1
2. EMITTER 2
3. COLLECTOR 2
4. BASE 2
5. EMITTER 1
6. COLLECTOR 1

STYLE 17:
PIN 1. BASE 1
2. EMITTER 1
3. COLLECTOR 2
4. BASE 2
5. EMITTER 2
6. COLLECTOR 1

STYLE 18:
PIN 1. VIN1
2. VCC
3. VOUT2
4. VIN2
5. GND
6. VOUT1

STYLE 19:
PIN 1. I OUT
2. GND
3. GND
4. V CC
5. V EN
6. V REF

STYLE 20:
PIN 1. COLLECTOR
2. COLLECTOR
3. BASE
4. EMITTER
5. COLLECTOR
6. COLLECTOR

STYLE 21:
PIN 1. ANODE 1
2. N/C
3. ANODE 2
4. CATHODE 2
5. N/C
6. CATHODE 1

STYLE 22:
PIN 1. D1 (i)
2. GND
3. D2 (i)
4. D2 (c)
5. VBUS
6. D1 (c)

STYLE 23:
PIN 1. Vn
2. CH1
3. Vp
4. N/C
5. CH2
6. N/C

STYLE 24:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. CATHODE
5. CATHODE
6. CATHODE

STYLE 25:
PIN 1. BASE 1
2. CATHODE
3. COLLECTOR 2
4. BASE 2
5. EMITTER
6. COLLECTOR 1

STYLE 26:
PIN 1. SOURCE 1
2. GATE 1
3. DRAIN 2
4. SOURCE 2
5. GATE 2
6. DRAIN 1

STYLE 27:
PIN 1. BASE 2
2. BASE 1
3. COLLECTOR 1
4. EMITTER 1
5. EMITTER 2
6. COLLECTOR 2

STYLE 28:
PIN 1. DRAIN
2. DRAIN
3. GATE
4. SOURCE
5. DRAIN
6. DRAIN

STYLE 29:
PIN 1. ANODE
2. ANODE
3. COLLECTOR
4. EMITTER
5. BASE/ANODE
6. CATHODE

STYLE 30:
PIN 1. SOURCE 1
2. DRAIN 2
3. DRAIN 2
4. SOURCE 2
5. GATE 1
6. DRAIN 1

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

DOCUMENT NUMBER:	**98ASB42985B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SC−88 2.00x1.25x0.90, 0.65P**		**PAGE 2 OF 2**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales