

NPN Epitaxial Silicon Transistor

KSC1008



TO−92−3
CASE 135AN



TO−92−3 LF
CASE 135AR

KSC1008: 1. Emitter 2. Base 3. Collector
KSC1008C: 1. Emitter 2. Collector 3. Base

Features

- Low−Frequency Amplifier Medium Speed Switching
- High Collector−Base Voltage: V_{CBO} = 80 V
- Collector Current: I_C = 700 mA
- Suffix "−C" means Center Collector (1. Emitter 2. Collector 3. Base)
- Non Suffix "−C" means Side Collector (1. Emitter 2. Base 3. Collector)
- Complement to KSA708
- These are Pb−Free Devices

ABSOLUTE MAXIMUM RATINGS

(T_A = 25°C unless otherwise noted.)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector−Base Voltage	80	V
V_{CEO}	Collector−Emitter Voltage	60	V
V_{EBO}	Emitter−Base Voltage	8	V
I_C	Collector Current	700	mA
T_J	Junction Temperature	150	°C
T_{STG}	Storage Temperature	−55 to 150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


THERMAL CHARACTERISTICS

(T_A = 25°C unless otherwise noted.) (Note 1)

Symbol	Parameter	Value	Unit
P_D	Power Dissipation	800	mW
	Derate Above 25°C	6.4	mW/°C
$R_{\theta JA}$	Thermal Resistance, Junction−to−Ambient	156	°C/W

1. PCB size: FR−4, 76 mm × 114 mm × 1.57 mm (3.0 inch × 4.5 inch × 0.062 inch) with minimum land pattern size.

MARKING DIAGRAM



A = Assembly Code
C1008 = Device Code
X = O/Y/YC/G
YWW = Date Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2001

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
BV_{CBO}	Collector−Base Breakdown Voltage	I_C = 100 μA, I_E = 0	80	–	–	V
BV_{CEO}	Collector−Emitter Breakdown Voltage	I_C = 10 mA, I_B = 0	60	–	–	V
BV_{EBO}	Emitter−Base Breakdown Voltage	I_E = 10 μA, I_C = 0	8	–	–	V
I_{CBO}	Collector Cut−Off Current	V_{CB} = 60 V, I_E = 0	–	–	0.1	μA
I_{EBO}	Emitter Cut−Off Current	V_{EB} = 5 V, I_C = 0	–	–	0.1	μA
h_{FE}	DC Current Gain	V_{CE} = 2 V, I_C = 50 mA	40	–	400	
$V_{CE(sat)}$	Collector−Emitter Saturation Voltage	I_C = 500 mA, I_B = 50 mA	–	0.2	0.4	V
$V_{BE(sat)}$	Base−Emitter Saturation Voltage	I_C = 500 mA, I_B = 50 mA	–	0.86	1.10	V
f_T	Current Gain Bandwidth Product	V_{CE} = 10 V, I_C = 50 mA	30	50	–	MHz
C_{ob}	Output Capacitance	V_{CB} = 10 V, I_E = 0, f = 1 MHz	–	8	–	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

h_{FE} Classification

Classification	O	Y	G
hFE	70 ~ 140	120 ~ 240	200 ~ 400

ORDERING INFORMATION (Note 2)

Part Number	Top Mark	Package	Shipping
KSC1008OBU	C1008 O−	TO−92−3 (Pb−Free)	10000 / Bulk Bag
KSC1008YBU	C1008 Y−		10000 / Bulk Bag
KSC1008YTA	C1008 Y−	TO−92−3 LR (Pb−Free)	2000 / Fan−Fold
KSC1008CYTA	C1008 YC		2000 / Fan−Fold
KSC1008GTA	C1008 G−		2000 / Fan−Fold

2. Affix "−C−" means center collector pin. Affix "−O−, −Y−, −G−" means h_{FE} classification. Suffix "−BU" means bulk packing, straight lead form. Suffix "−TA" means tape and ammo packing, 0.200 in−line spacing lead form.

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. Static Characteristic




Figure 2. DC Current Gain




Figure 3. Base−Emitter Saturation Voltage and Collector−Emitter Saturation Voltage




Figure 4. Base−Emitter On Voltage





Figure 5. Collector Output Capacitance

TO−92 3 4.825x4.76
CASE 135AN
ISSUE O

DATE 31 JUL 2016



NOTES: UNLESS OTHERWISE SPECIFIED


A) DRAWING WITH REFERENCE TO JEDEC TO−92 RECOMMENDATIONS.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DRAWING CONFORMS TO ASME Y14.5M−2009.


DOCUMENT NUMBER:	**98AON13880G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**TO−92 3 4.825X4.76**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

TO−92 3 4.83x4.76 LEADFORMED
CASE 135AR
ISSUE O

DATE 30 SEP 2016





NOTES: UNLESS OTHERWISE SPECIFIED

A) DRAWING WITH REFERENCE TO JEDEC TO-92 RECOMMENDATIONS.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DRAWING CONFORMS TO ASME Y14.5M-1994

DOCUMENT NUMBER:	**98AON13879G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**TO−92 3 4.83X4.76 LEADFORMED**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales