

# MOSFET – P-Channel, 1.8 V Specified, POWERTRENCH®

## FDN306P

### General Description

This P-Channel 1.8 V specified MOSFET uses onsemi's advanced low voltage POWERTRENCH process. It has been optimized for battery power management applications.

### Features

- -2.6 A, -12 V  $R_{DS(on)} = 40 \text{ m}\Omega$  @  $V_{GS} = -4.5 \text{ V}$   
 $R_{DS(on)} = 50 \text{ m}\Omega$  @  $V_{GS} = -2.5 \text{ V}$   
 $R_{DS(on)} = 80 \text{ m}\Omega$  @  $V_{GS} = -1.8 \text{ V}$
- Fast Switching Speed
- High Performance Trench Technology for Extremely Low  $R_{DS(on)}$
- SUPERSOT™ -3 Provides Low  $R_{DS(on)}$  and 30% Higher Power Handling Capability than SOT-23 in the Same Footprint
- This is a Pb-Free and Halide Free Device

### Applications

- Battery Management
- Load Switch
- Battery Protection


### ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted.)

| Symbol         | Parameter                                           | Value       | Unit             |
|----------------|-----------------------------------------------------|-------------|------------------|
| $V_{DSS}$      | Drain-Source Voltage                                | -12         | V                |
| $V_{GSS}$      | Gate-Source Voltage                                 | $\pm 8$     | V                |
| $I_D$          | Drain Current<br>– Continuous (Note 1a)<br>– Pulsed | -2.6<br>-10 | A                |
| $P_D$          | Maximum Power Dissipation<br>(Note 1a)<br>(Note 1b) | 0.5<br>0.46 | W                |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range    | -55 to +150 | $^\circ\text{C}$ |


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

### THERMAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted.)


| Symbol          | Parameter                                         | Value | Unit               |
|-----------------|---------------------------------------------------|-------|--------------------|
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient (Note 1a) | 250   | $^\circ\text{C/W}$ |
| $R_{\theta JC}$ | Thermal Resistance, Junction-to-Case (Note 1)     | 75    | $^\circ\text{C/W}$ |



SOT-23  
CASE 527AG



### MARKING DIAGRAM



306 = Specific Device Code  
M = Month Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

### ORDERING INFORMATION

| Device  | Package                             | Shipping†             |
|---------|-------------------------------------|-----------------------|
| FDN306P | SOT-23<br>(Pb-Free/<br>Halide Free) | 3000 /<br>Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, [BRD8011/D](http://BRD8011/D).

# FDN306P

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted.)

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Unit |
|--------|-----------|-----------------|-----|-----|-----|------|
|--------|-----------|-----------------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|                                |                                           |                                                                    |     |    |      |                      |
|--------------------------------|-------------------------------------------|--------------------------------------------------------------------|-----|----|------|----------------------|
| $BV_{DSS}$                     | Drain–Source Breakdown Voltage            | $V_{GS} = 0\text{ V}, I_D = -250\text{ }\mu\text{A}$               | -12 | -  | -    | V                    |
| $\Delta BV_{DSS} / \Delta T_J$ | Breakdown Voltage Temperature Coefficient | $I_D = -250\text{ }\mu\text{A}$ , Referenced to $25^\circ\text{C}$ | -   | -3 | -    | mV/ $^\circ\text{C}$ |
| $I_{DSS}$                      | Zero Gate Voltage Drain Current           | $V_{DS} = -10\text{ V}, V_{GS} = 0\text{ V}$                       | -   | -  | -1   | $\mu\text{A}$        |
| $I_{GSSF}$                     | Gate–Body Leakage, Forward                | $V_{GS} = 8\text{ V}, V_{DS} = 0\text{ V}$                         | -   | -  | 100  | nA                   |
| $I_{GSSR}$                     | Gate–Body Leakage, Reverse                | $V_{GS} = -8\text{ V}, V_{DS} = 0\text{ V}$                        | -   | -  | -100 | nA                   |

### ON CHARACTERISTICS

|                                  |                                                |                                                                                                                                                                                                                           |      |                      |                      |                      |
|----------------------------------|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|----------------------|----------------------|----------------------|
| $V_{GS(th)}$                     | Gate Threshold Voltage                         | $V_{DS} = V_{GS}, I_D = -250\text{ }\mu\text{A}$                                                                                                                                                                          | -0.4 | -0.6                 | -1.5                 | V                    |
| $\Delta V_{GS(th)} / \Delta T_J$ | Gate Threshold Voltage Temperature Coefficient | $I_D = -250\text{ }\mu\text{A}$ , Referenced to $25^\circ\text{C}$                                                                                                                                                        | -    | 2.5                  | -                    | mV/ $^\circ\text{C}$ |
| $R_{DS(on)}$                     | Static Drain–Source On–Resistance              | $V_{GS} = -4.5\text{ V}, I_D = -2.6\text{ A}$<br>$V_{GS} = -2.5\text{ V}, I_D = -2.3\text{ A}$<br>$V_{GS} = -1.8\text{ V}, I_D = -1.8\text{ A}$<br>$V_{GS} = -4.5\text{ V}, I_D = -2.6\text{ A}, T_J = 125^\circ\text{C}$ | -    | 30<br>39<br>54<br>40 | 40<br>50<br>80<br>54 | m $\Omega$           |
| $I_{D(on)}$                      | On–State Drain Current                         | $V_{GS} = -4.5\text{ V}, V_{DS} = -5\text{ V}$                                                                                                                                                                            | -10  | -                    | -                    | A                    |
| $g_{FS}$                         | Forward Transconductance                       | $V_{DS} = -5\text{ V}, I_D = -2.6\text{ A}$                                                                                                                                                                               | -    | 10                   | -                    | S                    |

### DYNAMIC CHARACTERISTICS

|           |                              |                                                                 |   |      |   |    |
|-----------|------------------------------|-----------------------------------------------------------------|---|------|---|----|
| $C_{iss}$ | Input Capacitance            | $V_{DS} = -6\text{ V}, V_{GS} = 0\text{ V}, f = 1.0\text{ MHz}$ | - | 1138 | - | pF |
| $C_{oss}$ | Output Capacitance           |                                                                 | - | 454  | - | pF |
| $C_{rss}$ | Reverse Transfer Capacitance |                                                                 | - | 302  | - | pF |

### SWITCHING CHARACTERISTICS (Note 2)

|              |                     |                                                                                                   |   |    |    |    |
|--------------|---------------------|---------------------------------------------------------------------------------------------------|---|----|----|----|
| $t_{d(on)}$  | Turn–On Delay Time  | $V_{DD} = -6\text{ V}, I_D = -1\text{ A},$<br>$V_{GS} = -4.5\text{ V}, R_{GEN} = 6\text{ }\Omega$ | - | 11 | 20 | ns |
| $t_r$        | Turn–On Rise Time   |                                                                                                   | - | 10 | 20 | ns |
| $t_{d(off)}$ | Turn–Off Delay Time |                                                                                                   | - | 38 | 61 | ns |
| $t_f$        | Turn–Off Fall Time  |                                                                                                   | - | 35 | 56 | ns |
| $Q_g$        | Total Gate Charge   | $V_{DS} = -6\text{ V}, I_D = -2.6\text{ A}, V_{GS} = -4.5\text{ V}$                               | - | 12 | 17 | nC |
| $Q_{gs}$     | Gate–Source Charge  |                                                                                                   | - | 2  | -  | nC |
| $Q_{gd}$     | Gate–Drain Charge   |                                                                                                   | - | 3  | -  | nC |

### DRAIN–SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

|                 |                                                       |                                                        |   |      |       |   |
|-----------------|-------------------------------------------------------|--------------------------------------------------------|---|------|-------|---|
| I <sub>S</sub>  | Maximum Continuous Drain–Source Diode Forward Current |                                                        | – | –    | –0.42 | A |
| V <sub>SD</sub> | Drain–Source Diode Forward Voltage                    | V <sub>GS</sub> = 0 V, I <sub>S</sub> = –0.42 (Note 2) | – | –0.6 | –1.2  | V |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

#### NOTES:

- $R_{\theta JA}$  is the sum of the junction–to–case and case–to–ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.



a)  $250^\circ\text{C/W}$  when mounted on a  $0.02\text{ in}^2$  pad of 2 oz. copper.



b)  $270^\circ\text{C/W}$  when mounted on a minimum pad.

Scale 1:1 on letter size paper.

- Pulse Test: Pulse Width  $\leq 300\text{ }\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .

## TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage




Figure 3. On-Resistance Variation with Temperature




Figure 4. On-Resistance Variation with Gate-to-Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature

TYPICAL CHARACTERISTICS (Continued)




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance Characteristics




Figure 9. Maximum Safe Operating Area




Figure 10. Single Pulse Maximum Power Dissipation





Figure 11. Transient Thermal Response Curve

Thermal characterization performed using the conditions described in Note 1b.  
Transient thermal response will change depending on the circuit board design.




### SOT-23/SUPERSOT™ –23, 3 LEAD, 1.4x2.9

#### CASE 527AG

#### ISSUE A





DATE 09 DEC 2019



NOTES: UNLESS OTHERWISE SPECIFIED


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. ALL DIMENSIONS ARE IN MILLIMETERS.
3. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR EXTRUSIONS.

| DIM | MIN.     | NOM.  | MAX.  |
|-----|----------|-------|-------|
| A   | 0.85     | 0.95  | 1.12  |
| A1  | 0.00     | 0.05  | 0.10  |
| b   | 0.370    | 0.435 | 0.508 |
| c   | 0.085    | 0.150 | 0.180 |
| D   | 2.80     | 2.92  | 3.04  |
| E   | 2.31     | 2.51  | 2.71  |
| E1  | 1.20     | 1.40  | 1.52  |
| e   | 0.95 BSC |       |       |
| e1  | 1.90 BSC |       |       |
| L   | 0.33     | 0.38  | 0.43  |



\*FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

### GENERIC MARKING DIAGRAM\*



XXX = Specific Device Code  
M = Month Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

|                  |                                     |                                                                                                                                                                                  |
|------------------|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON34319E                         | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SOT-23/SUPERSOT-23, 3 LEAD, 1.4X2.9 | PAGE 1 OF 1                                                                                                                                                                      |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)