2.5 V / 3.3 V Dual Channel Programmable Clock/Data Delay with Differential LVPECL Outputs

Multi−Level Inputs w/ Internal Termination

NB6L295


The NB6L295 is a Dual Channel Programmable Delay Chip designed primarily for Clock or Data de−skewing and timing adjustment. The NB6L295 is versatile in that two individual variable delay channels, PD0 and PD1, can be configured in one of two operating modes, a Dual Delay or an Extended Delay.

In the Dual Delay Mode, each channel has a programmable delay section which is designed using a matrix of gates and a chain of multiplexers. There is a fixed minimum delay of 3.2 ns per channel.

The Extended Delay Mode amounts to the additive delay of PD0 plus PD1 and is accomplished with the Serial Data Interface MSEL bit set High. This will internally cascade the output of PD0 into the input of PD1. Therefore, the Extended Delay path starts at the IN0/$\overline{\text{IN0}}$ inputs, flows through PD0, cascades to the PD1 and outputs through Q1/$\overline{\text{Q1}}$. There is a fixed minimum delay of 6 ns for the Extended Delay Mode.


The required delay is accomplished by programming each delay channel via a 3−pin Serial Data Interface, described in the application section. The digitally selectable delay has an increment resolution of typically 11 ps with a net programmable delay range of either 0 ns to 6 ns per channel in Dual Delay Mode; or from 0 ns to 11.2 ns for the Extended Delay Mode.

The Multi−Level Inputs can be driven directly by differential LVPECL, LVDS or CML logic levels; or by single ended LVPECL, LVCMOS or LVTTL. A single enable pin is available to control both inputs. The SDI input pins are controlled by LVCMOS or LVTTL level signals. The NB6L295 LVPECL output contains temperature compensation circuitry. This device is offered in a 4 mm x 4 mm 24−pin QFN Pb−free package. The NB6L295 is a member of the ECLinPS MAX™ family of high performance products.



QFN−24
MN SUFFIX
CASE 485L

MARKING DIAGRAM*



A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package
(Note: Microdot may be in either location)

*For additional marking information, refer to Application Note AND8002/D.

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 12 of this data sheet.

Features

- Input Clock Frequency > 1.5 GHz with 550 mV V_{OUTPP}
- Input Data Rate > 2.5 Gb/s
- Programmable Delay Range: 0 ns to 6 ns per Delay Channel
- Programmable Delay Range: 0 ns to 11.2 ns for Extended Delay Mode
- Total Delay Range: 3.2 ns to 8.8 ns per Delay Channel
- Total Delay Range: 6 ns to 17 ns in Extended Delay Mode
- Monotonic Delay: 11 ps Increments in 511 Steps
- Linearity ±20 ps, Maximum
- 100 ps Typical Rise and Fall Times
- 3 ps Typical Clock Jitter, RMS
- 20 ps Pk−Pk Typical Data Dependent Jitter
- LVPECL, CML or LVDS Differential Input Compatible
- LVPECL, LVCMOS, LVTTL Single−Ended Input Compatible
- 3−Wire Serial Interface
- Input Enable/Disable
- Operating Range: V_{CC} = 2.375 V to 3.6 V
- LVPECL Output Level; 780 mV Peak−to−Peak, Typical
- Internal 50 Ω Input Termination Provided
- −40°C to 85°C Ambient Operating Temperature
- 24−Pin QFN, 4 mm x 4 mm
- These are Pb−Free Devices*

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

© Semiconductor Components Industries, LLC, 2012




Figure 1. Simplified Functional Block Diagram




Figure 2. Pinout: QFN−24 (Top View)

Table 1. PIN DESCRIPTION

Pin	Name	I/O	Description
1	VCC	Power Supply	Positive Supply Voltage for the Inputs and Core Logic
2	$\overline{EN}$	LVCMOS/LVTTL Input	Input Enable/ Disable for both PD0 and PD1. LOW for enable, HIGH for disable, Open Pin Default state LOW (37 kΩ pulldown resistor). High forces Q LOW and $\overline{Q}$ HIGH.
3	SLOAD	LVCMOS/LVTTL Input	Serial Load; This pin loads the configuration latches with the contents of the shift register. The latches will be transparent when this signal is HIGH; thus, the data must be stable on the HIGH−to−LOW transition of S_LOAD for proper operation. Open Pin Default state LOW (37 kΩ pulldown resistor).
4	SDIN	LVCMOS/LVTTL Input	Serial Data In; This pin acts as the data input to the serial configuration shift register. Open Pin Default state LOW (37 kΩ pulldown resistor).
5	SCLK	LVCMOS/LVTTL Input	Serial Clock In; This pin serves to clock the serial configuration shift register. Data from SDIN is sampled on the rising edge. Open Pin Default state LOW (37 kΩ pulldown resistor).
6	VCC	Power Supply	Positive Supply Voltage for the Inputs and Core Logic
7	VT1		Internal 50 Ω Termination Pin for IN1
8	IN1	LVPECL, CML, LVDS Input	Non−inverted differential input. Note 1.
9	$\overline{IN1}$	LVPECL, CML, LVDS Input	Inverted differential input. Note 1.
10	$\overline{VT1}$		Internal 50 Ω Termination Pin for $\overline{IN1}$
11	GND	Power Supply	Negative Power Supply
12	VCC1	Power Supply	Positive Supply Voltage for the Q1/$\overline{Q1}$ outputs, channel PD1
13	$\overline{Q1}$	LVPECL Output	Inverted Differential Output. Channel 1. Typically terminated with 50 Ω resistor to V_{CC1} − 2.0 V.
14	Q1	LVPECL Output	Non−inverted Differential Output. Channel 1. Typically terminated with 50 Ω resistor to V_{CC1} − 2.0 V.
15	VCC1	Power Supply	Positive Supply Voltage for the Q1/$\overline{Q1}$ outputs, channel PD1
16	VCC0	Power Supply	Positive Supply Voltage for the Q0/$\overline{Q0}$ outputs, channel PD0
17	$\overline{Q0}$	LVPECL Output	Inverted Differential Output. Channel 0. Typically terminated with 50 Ω resistor to V_{CC0} − 2.0 V.
18	Q0	LVPECL Output	Non−inverted Differential Output . Channel 0. Typically terminated with 50 Ω resistor to V_{CC0} − 2.0 V.
19	VCC0	Power Supply	Positive Supply Voltage for the Q0/$\overline{Q0}$ outputs, channel PD0
20	GND	Power Supply	Negative Power Supply
21	$\overline{VT0}$		Internal 50 Ω Termination Pin for $\overline{IN0}$
22	$\overline{IN0}$	LVPECL, CML, LVDS Input	Inverted differential input. Note 1.
23	IN0	LVPECL, CML, LVDS Input	Noninverted differential input. Note 1.
24	VT0		Internal 50 Ω Termination Pin for IN0
−	EP	Ground	The Exposed Pad (EP) on the QFN−24 package bottom is thermally connected to the die for improved heat transfer out of package. The exposed pad must be attached to a heat−sinking conduit. The pad is electrically connected to GND and must be connected to GND on the PC board.

1. In the differential configuration when the input termination pin (VTx/$\overline{VTx}$) are connected to a common termination voltage or left open, and if no signal is applied on INx/$\overline{INx}$ input then the device will be susceptible to self−oscillation.
2. All VCC, VCC0 and VCC1 Pins must be externally connected to the same power supply for proper operation. Both VCC0s are connected to each other and both VCC1s are connected to each other: VCC0 and VCC1 are separate.

Table 2. ATTRIBUTES

Characteristics		Value
Input Default State Resistors		37 kΩ
ESD Protection	Human Body Model Machine Model	> 2 kV > 100V
Moisture Sensitivity (Note 3)	QFN−24	Level 1
Flammability Rating	Oxygen Index: 28 to 34	UL 94 V−0 @ 0.125 in
Transistor Count		3094
Meets or exceeds JEDEC Spec EIA/JESD78 IC Latchup Test		

3. For additional information, see Application Note AND8003/D.

Table 3. MAXIMUM RATINGS

Symbol	Parameter	Condition 1	Condition 2	Rating	Unit
V_{CC}, V_{CC0}, V_{CC1}	Positive Power Supply	GND = 0 V		4.0	V
V_{IO}	Positive Input/Output Voltage	GND = 0 V	$-0.5 \le V_{IO} \le V_{CC} + 0.5$	4.5	V
V_{INPP}	Differential Input Voltage $\lvert INx - \overline{INx}\rvert$			V_{CC} − GND	V
I_{IN}	Input Current Through R_T (50 Ω Resistor)			±50	mA
I_{OUT}	Output Current (LVPECL Output)	Continuous Surge		50 100	mA mA
T_A	Operating Temperature Range			−40 to +85	°C
T_{stg}	Storage Temperature Range			−65 to +150	°C
θ_{JA}	Thermal Resistance (Junction−to−Ambient) (Note 4)	0 lfpm 500 lfpm	QFN−24 QFN−24	37 32	°C/W °C/W
θ_{JC}	Thermal Resistance (Junction−to−Case)	(Note 4)	QFN−24	11	°C/W
T_{sol}	Wave Solder Pb−Free			265	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

4. JEDEC standard multilayer board − 2S2P (2 signal, 2 power) with 8 filled thermal vias under exposed pad.

Table 4. DC CHARACTERISTICS, MULTI−LEVEL INPUTS V_{CC} = V_{CC0} = V_{CC1} = 2.375 V to 3.6 V, GND = 0 V, T_A = −40°C to +85°C

Symbol	Characteristic	Min	Typ	Max	Unit
POWER SUPPLY CURRENT					
I_{CC}	Power Supply Current (Inputs, V_{Tx} and Outputs Open) (Sum of I_{CC}, I_{CC0}, and I_{CC1})	110	140	170	mA
LVPECL OUTPUTS (Notes 5 and 6, Figure 21)					
V_{OH}	Output HIGH Voltage V_{CC} = V_{CC0} = V_{CC1} = 3.3 V V_{CC} = V_{CC0} = V_{CC1} = 2.5 V	V_{CC} − 1075 2225 1425	V_{CC} − 950 2350 1550	V_{CC} − 825 2475 1675	mV
V_{OL}	Output LOW Voltage V_{CC} = V_{CC0} = V_{CC1} = 3.3 V	V_{CC} − 1825 1475	V_{CC} − 1725 1575	V_{CC} − 1625 1675	mV
	V_{CC} = V_{CC0} = V_{CC1} = 2.5 V	V_{CC} − 1825 675	V_{CC} − 1725 775	V_{CC} − 1600 900	
DIFFERENTIAL INPUT DRIVEN SINGLE−ENDED (see Figures 10 and 11) (Note 7)					
V_{th}	Input Threshold Reference Voltage Range	1050		V_{CC} − 150	mV
V_{IH}	Single−Ended Input HIGH Voltage	V_{th} + 150		V_{CC}	mV
V_{IL}	Single−Ended Input LOW Voltage	GND		V_{th} − 150	mV
V_{ISE}	Single−Ended Input Voltage Amplitude (V_{IH} − V_{IL})	300		V_{CC} − GND	mV
DIFFERENTIAL INPUTS DRIVEN DIFFERENTIALLY (see Figures 12 and 13) (Note 8)					
V_{IHD}	Differential Input HIGH Voltage	1200		V_{CC}	mV
V_{ILD}	Differential Input LOW Voltage	GND		V_{CC} − 150	mV
V_{ID}	Differential Input Voltage Swing (INx, $\overline{INx}$) (V_{IHD} − V_{ILD})	150		V_{CC} − GND	mV
V_{CMR}	Input Common Mode Range (Differential Configuration) (Note 9)	950		V_{CC} − 75	mV
I_{IH}	Input HIGH Current INx/$\overline{INx}$, (VTn/$\overline{VTn}$ Open)	−150		150	μA
I_{IL}	Input LOW Current IN/$\overline{INX}$, (VTn/$\overline{VTn}$ Open)	−150		150	μA
SINGLE−ENDED LVCMOS/LVTTL CONTROL INPUTS					
V_{IH}	Single−Ended Input HIGH Voltage	2000		V_{CC}	mV
V_{IL}	Single−Ended Input LOW Voltage	GND		800	mV
I_{IH}	Input HIGH Current	−150		150	μA
I_{IL}	Input LOW Current	−150		150	μA
TERMINATION RESISTORS					
R_{TIN}	Internal Input Termination Resistor	40	50	60	Ω

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm.

5. LVPECL outputs loaded with 50 Ω to V_{CC} − 2.0 V for proper operation.
6. Input and output parameters vary 1:1 with V_{CC}.
7. V_{th}, V_{IH}, $V_{IL,}$, and V_{ISE} parameters must be complied with simultaneously. V_{th} is applied to the complementary input when operating in single−ended mode.
8. V_{IHD}, $V_{ILD,}$ V_{ID} and V_{CMR} parameters must be complied with simultaneously.
9. V_{CMR}(min) varies 1:1 with voltage on GND Pin, V_{CMR}(max) varies 1:1 with V_{CC}. The V_{CMR} range is referenced to the most positive side of the differential input signal.

Table 5. AC CHARACTERISTICS $V_{CC} = V_{CC0} = V_{CC1}$ = 2.375 V to 3.6 V, GND = 0 V, T_A = −40°C to +85°C (Note 10)

Symbol	Characteristic	Min	Typ	Max	Unit
f_{SCLK}	Serial Clock Input Frequency, 50% Duty Cycle			20	MHz
V_{OUTPP}	Output Voltage Amplitude (@ $V_{INPPmin}$) $f_{in} \le 1.5$ GHz (Note 15) (See Figure 22)	530	780		mV
f_{DATA}	Maximum Data Rate (Note 14)	2.5			Gb/s
t_{Range}	Programmable Delay Range (@ 50 MHz) Dual Mode IN0/$\overline{IN0}$ to Q0/$\overline{Q0}$ or IN1/$\overline{IN1}$ to Q1/$\overline{Q1}$ Extended Mode IN0/$\overline{IN0}$ to Q1/$\overline{Q1}$	 0 0	 5.7 11.2	 6.9 13.7	ns
t_{SKEW}	Duty Cycle Skew (Note 11) Within Device Skew − Dual Mode D[8:0] = 0 D[8:0] = 1	0	2 60 60	5 100 175	ps
L_{in}	Linearity (Note 12)		±15	±20	ps
t_s	Setup Time (@ 20 MHz) SDIN to SCLK SLOAD to SCLK $\overline{EN}$ to SDIN	0.5 1.5 0.5	0.3 1.0		ns
t_h	Hold Time SDIN to SCLK SLOAD to SCLK $\overline{EN}$ to SLOAD	1.0 1.0 0.5	0.6		ns
t_{pwmin}	Minimum Pulse Width SLOAD	1			ns
t_{JITTER}	Random Clock Jitter RMS; SETMIN to SETMAX (Note 13) $f_{in} \le 1.5$ GHz Dual Mode IN0/$\overline{IN0}$ to Q0/$\overline{Q0}$ or IN1/$\overline{IN1}$ to Q1/$\overline{Q1}$ Extended Mode IN0/$\overline{IN0}$ to Q1/$\overline{Q1}$ Deterministic Jitter; SETMIN to SETMAX (Note 14) $f_{DATA} \le 2.5$ Gbps Dual Mode IN0/$\overline{IN0}$ to Q0/$\overline{Q0}$ or IN1/$\overline{IN1}$ to Q1/$\overline{Q1}$		 3 6 20	 10 20 30	ps
V_{INPP}	Input Voltage Swing/Sensitivity (Differential Configuration) (Note 15)	150		V_{CC} − GND	mV
t_r, t_f	Output Rise/Fall Times (@ 50 MHz), (20% − 80%) Qx, $\overline{Qx}$	85	120	170	ps

Symbol	Characteristic	−40°C			+25°C			+85°C			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
t_{PLH}, t_{PHL}	Propagation Delay (@ 50 MHz) Dual Mode IN0/$\overline{IN0}$ to Q0/$\overline{Q0}$ or IN1/$\overline{IN1}$ to Q1/$\overline{Q1}$ D[8:0] = 0 D[8:0] = 1 Extended Mode IIN0/$\overline{IN0}$ to Q1/$\overline{Q1}$ D[8:0] = 0 D[8:0] = 1	 2.7 7.2 5.0 14.2	 2.9 8.0 5.5 15.2	 3.2 8.8 6.0 17.1	 2.8 7.5 5.2 14.8	 3.1 8.4 5.8 16.5	 3.4 9.3 6.3 18.2	 2.9 7.9 5.5 15.6	 3.2 9.2 6.2 16.4	 3.6 9.9 6.8 19.6	ns
Δt	Step Delay (Selected D Bit HIGH All Others LOW) D0 HIGH D1 HIGH D2 HIGH D3 HIGH D4 HIGH D5 HIGH D6 HIGH D7 HIGH D8 HIGH		 9.6 19.4 40 81 167 338 678 1358 2715			 8.7 19 42 85 175 355 714 1432 2861			 11 24.4 52 99 196 389 774 1544 3074		ps

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm.

10. Measured by forcing $V_{INPPmin}$ and $V_{INPPmax}$ from a 50% duty cycle clock source, V_{CMR} (min and max). All loading with an external R_L = 50 Ω to V_{CC}. See Figure 20. Input edge rates 40 ps (20% − 80%).
11. Duty cycle skew is measured between differential outputs using the deviations of the sum of T_{pw}− and T_{pw}+ @ 0.5 GHz.
12. Deviation from a linear delay (actual Min to Max) in the Dual Mode 511 programmable steps.
13. Additive random CLOCK jitter with 50% duty cycle input clock signal.
14. NRZ data at PRBS23 and K28.5.
15. Input and output voltage swing is a single−ended measurement operating in differential mode.

Serial Data Interface Programming

The NB6L295 is programmed by loading the 11−Bit SHIFT REGISTER using the SCLK, SDATA and SLOAD inputs. The 11 SDATA bits are 1 PSEL bit, 1 MSEL bit and 9 delay value data bitsD[8:0]. A separate 11−bit load cycle is required to program the delay data value of each channel, PD0 and PD1. For example, at powerup two load cycles will be needed to initially set PD0 and PD1; Dual Mode Operation as shown in Figures 3 and 4 and Extended Mode Operation as shown in Figures 5 and 6.

DUAL MODE OPERATIONS

PD0 Programmable Delay									Control Bits		
0/1	0/1	0/1	0/1	0/1	0/1	0/1	0/1	0/1	0	0	Value
D8	D7	D6	D5	D4	D3	D2	D1	D0	MSEL	PSEL	Bit Name
(MSB)										(LSB)	

Figure 3. PDO Shift Register

PD1 Programmable Delay									Control Bits		
0/1	0/1	0/1	0/1	0/1	0/1	0/1	0/1	0/1	0	1	Value
D8	D7	D6	D5	D4	D3	D2	D1	D0	MSEL	PSEL	Bit Name
(MSB)										(LSB)	

Figure 4. PD1 Shift Register

EXTENDED MODE OPERATIONS

PD0 Programmable Delay									Control Bits		
0/1	0/1	0/1	0/1	0/1	0/1	0/1	0/1	0/1	1	0	Value
D8	D7	D6	D5	D4	D3	D2	D1	D0	MSEL	PSEL	Bit Name
(MSB)										(LSB)	

Figure 5. PDO Shift Register

PD1 Programmable Delay									Control Bits		
0/1	0/1	0/1	0/1	0/1	0/1	0/1	0/1	0/1	1	1	Value
D8	D7	D6	D5	D4	D3	D2	D1	D0	MSEL	PSEL	Bit Name
(MSB)										(LSB)	

Figure 6. PD1 Shift Register

Refer to Table 6, Channel and Mode Select BIT Functions. In a load cycle, the 11−Bit Shift Register least significant bit (clocked in first) is **PSEL** and will determine which channel delay buffer, either PDO (LOW) or PD1 (HIGH), will latch the delay data value D[8:0]. The **MSEL BIT** determines the Delay Mode. When set LOW, the Dual Delay Mode is selected and the device uses both channels independently. A pulse edge entering IN0/$\overline{\text{IN0}}$ is delayed according to the values in PD0 and exits from Q0/$\overline{\text{Q0}}$. An input signal pulse edge entering IN1/$\overline{\text{IN1}}$ is delayed according to the values in PD1 and exits from Q1/$\overline{\text{Q1}}$. When MSEL is set HIGH, the Extended Delay Mode is selected and an input signal pulse edge enters IN0 and $\overline{\text{IN0}}$ and flows through PD0 and is extended through PD1 to exit at Q1 and $\overline{\text{Q1}}$. The most significant 9−bits, D[8:0] are delay value data for both channels. See Figure 7.

Table 6. CHANNEL AND MODE SELECT BIT FUNCTIONS

BIT Name	Function
PSEL	0 Loads Data to PD0
	1 Loads Data to PD1
MSEL	0 Selects Dual Programmable Delay Paths, 3.1 ns to 8.8 ns Delay Range for Each Path
	1 Selects Extended Delay Path from IN0/$\overline{\text{IN0}}$ to Q1/$\overline{\text{Q1}}$, 6.0 ns to 17.2 ns Delay Range; Disables Q0/$\overline{\text{Q0}}$ Outputs, Q0−LOW, $\overline{\text{Q0}}$−HIGH.
D[8:0]	Select one of 512 Delay Values




Figure 7. Serial Data Interface, Shift Register, Data Latch, Programmable Delay Channels

Serial Data Interface Loading

Loading the device through the 3 input Serial Data Interface (SDI) is accomplished by sending data into the SDIN pin by using the SCLK input pin and latching the data with the SLOAD input pin. The 11−bit SHIFT REGISTER shifts once per rising edge of the **SCLK** input. The serial input **SDIN** must meet setup and hold timing as specified in the AC Characteristics section of this document for each bit and clock pulse. The **SLOAD** line loads the value of the shift register on a LOW−to−HIGH edge transition (transparent state) into a data Latch register and latches the data with a subsequent HIGH−to−LOW edge transition. Further changes in SDIN or SCLK are not recognized by the latched register. The internal multiplexer states are set by the PSEL and MSEL bits in the SHIFT register. Figure 6 shows the timing diagram of a typical load sequence.

Input $\overline{EN}$ should be LOW (enabled) prior to SDI programming, then pulled HIGH (disabled) during programming. After programming, the $\overline{EN}$ should be returned LOW (enabled) for functional delay operation.

The disabling of $\overline{EN}$ (HIGH) forces Qx LOW and $\overline{Qx}$ HIGH and is included during programming to prevent (or mask out) any potential runt pulses or extended pulses which might occur in the internal delay gates programming switching, but it is not required for programming.




Figure 8. SDI Timing Diagram

Table 7 shows theoretical values of delay capabilities in both the Dual Delay Mode and in the Extended Delay Modes of operation.

Table 7. EXAMPLES OF THEORETICAL DELAY VALUES FOR PD0 AND PD1 IN DUAL MODE
INPUTS: IN0/$\overline{IN0}$, IN1/$\overline{IN1}$, OUTPUTS: Q0/$\overline{Q0}$, Q1, $\overline{Q1}$

Dual Mode						
PD1 D[8:0]	(Decimal)	PD0 D[8:0]	(Decimal)	MSEL	PD0 Delay* (ps)	PD1 Delay* (ps)
000000000	(0)	000000000	(0)	0	0	0
000000000	(0)	000000001	(1)	0	11	0
000000000	(0)	000000010	(2)	0	22	0
000000000	(0)	000000011	(3)	0	33	0
000000000	(0)	000000100	(4)	0	44	0
000000000	(0)	000000101	(5)	0	55	0
000000000	(0)	000000110	(6)	0	66	0
000000000	(0)	000000111	(7)	0	77	0
000000000	(0)	000001000	(8)	0	88	0
		• • •			• • •	• • •
000000000	(0)	000010000	(16)	0	176	0
000000000	(0)	000100000	(32)	0	352	0
000000000	(0)	001000000	(64)	0	704	0
000000000	(0)	111111101	(509)	0	5599	0
000000000	(0)	111111110	(510)	0	5610	0
000000000	(0)	111111111	(511)	0	5621	0

*Fixed minimum delay not included

Table 8. EXAMPLES OF THEORETICAL DELAY VALUES FOR PD0 AND PD1 IN EXTENDED MODE
INPUTS: IN0/$\overline{IN0}$, IN1/$\overline{IN1}$, OUTPUTS: Q0/$\overline{Q0}$, Q1, $\overline{Q1}$

Extended Delay Mode							
PD1 D[8:0]	(Decimal)	PD0 D[8:0]	(Decimal)	MSEL	PD0* (ps)	PD1* (ps)	Total Delay* (ps)
000000000	(0)	000000000	(0)	1	0	0	0
000000000	(0)	000000001	(1)	1	0	11	11
000000000	(0)	000000010	(2)	1	0	22	22
000000000	(0)	000000011	(3)	1	0	33	33
		• • •			• • •	• • •	• • •
000000000	(0)	111111101	(509)	1	0	5599	5599
000000000	(0)	111111110	(510)	1	0	5610	5610
000000000	(0)	111111111	(511)	1	0	5621	5621
000000001	(1)	111111111	(511)	1	11	5621	5632
000000010	(2)	111111111	(511)	1	22	5621	5643
		• • •			• • •	• • •	• • •
111111100	(508)	111111111	(511)	1	5588	5621	11209
111111101	(509)	111111111	(511)	1	5599	5621	11220
111111110	(510)	111111111	(511)	1	5610	5621	11231
111111111	(511)	111111111	(511)	1	5621	5621	11242

*Fixed minimum delay not included




Figure 9. Input Structure




Figure 10. Differential Input Driven Single−Ended




Figure 11. V_{th} Diagram




Figure 12. Differential Inputs Driven Differentially




Figure 13. Differential Inputs Driven Differentially




Figure 14. V_{CMR} Diagram




Figure 15. AC Reference Measurement




Figure 16. LVPECL Interface




Figure 17. LVDS Interface




Figure 18. CML Interface, Standard 50 Ω Load




Figure 19. Capacitor−Coupled Differential Interface (V_{Tx}/$\overline{V_{Tx}}$ Connected to V_{REFAC}; V_{REFAC} Bypassed to Ground with 0.1 μF Capacitor)




Figure 20. Capacitor−Coupled Single−Ended Interface (V_{Tx}/$\overline{V_{Tx}}$ Connected to External V_{REFAC}; V_{REFAC} Bypassed to Ground with 0.1 μF Capacitor)




Figure 21. Typical Termination for Output Driver and Device Evaluation (See Application Note AND8020/D − Termination of ECL Logic Devices.)




Figure 22. Output Voltage Amplitude (V_{OUTPP}) vs. Output Frequency at Ambient Temperature (Typical)

ORDERING INFORMATION


Device	Package	Shipping†
NB6L295MNG	QFN−24 (Pb−free)	92 Units / Rail
NB6L295MNTXG	QFN−24 (Pb−free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


ECLinPS MAX is trademark of Semiconductor Components Industries, LLC (SCILLC).


QFN24, 4x4, 0.5P
CASE 485L
ISSUE B

DATE 05 JUN 2012




SCALE 2:1







DETAIL A
ALTERNATE CONSTRUCTIONS



DETAIL B
ALTERNATE TERMINAL CONSTRUCTIONS






NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS	
DIM	MIN	MAX
A	0.80	1.00
A1	0.00	0.05
A3	0.20 REF	
b	0.20	0.30
D	4.00 BSC	
D2	2.70	2.90
E	4.00 BSC	
E2	2.70	2.90
e	0.50 BSC	
L	0.30	0.50
L1	0.05	0.15

RECOMMENDED SOLDERING FOOTPRINT



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON11783D**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**QFN24, 4X4, 0.5P**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales