MOSFET – Complementary, POWERTRENCH®

N-Channel: 20 V, 3.8 A, 66 mΩ
P-Channel: -20 V, -2.6 A, 142 mΩ

FDME1034CZT

General Description

This device is designed specifically as a single package solution for a DC–DC 'Switching' MOSFET in cellular handset and other ultra–portable applications. It features an independent N–Channel & P–Channel MOSFET with low on–state resistance for minimum conduction losses. The gate charge of each MOSFET is also minimized to allow high frequency switching directly from the controlling device.

The MicroFET™ 1.6x1.6 Thin package offers exceptional thermal performance for it's physical size and is well suited to switching and linear mode applications.

Features

Q1: N–Channel

- Max $R_{DS(on)}$ = 66 mΩ at V_{GS} = 4.5 V, I_D = 3.4 A
- Max $R_{DS(on)}$ = 86 mΩ at V_{GS} = 2.5 V, I_D = 2.9 A
- Max $R_{DS(on)}$ = 113 mΩ at V_{GS} = 1.8 V, I_D = 2.5 A
- Max $R_{DS(on)}$ = 160 mΩ at V_{GS} = 1.5 V, I_D = 2.1 A


Q2: P–Channel


- Max $R_{DS(on)}$ = 142 mΩ at V_{GS} = −4.5 V, I_D = −2.3 A
- Max $R_{DS(on)}$ = 213 mΩ at V_{GS} = −2.5 V, I_D = −1.8 A
- Max $R_{DS(on)}$ = 331 mΩ at V_{GS} = −1.8 V, I_D = −1.5 A
- Max $R_{DS(on)}$ = 530 mΩ at V_{GS} = −1.5 V, I_D = −1.2 A
- Low Profile: 0.55 mm Maximum in the New Package MicroFET 1.6x1.6 Thin
- Free from Halogenated Compounds and Antimony Oxides
- HBM ESD Protection Level > 1600 V (Note 3)
- This Device is Pb–Free and is RoHS Compliant

Applications

- DC–DC Conversion
- Level Shifted Load Switch

ELECTRICAL CONNECTION






Bottom Top

Note: Center pad of P7 & P8 is a virtual pin number. Actual P7 & P8 is connected to edge pad of P6 & P3 respectively.

UDFN6 1.6x1.6, 0.5P
CASE 517DW

MARKING DIAGRAM



&Z	= Assembly Plant Code
&2	= 2–Digit Date Code (YW)
&K	= 2–Digit Lot Traceability Code
5T	= Specific Device Code

ORDERING INFORMATION

Device	Package	Shipping†
FDME1034CZT	UDFN6 (Pb–Free)	5,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2019

MOSFET MAXIMUM RATINGS (T_A = 25°C, Unless otherwise noted)

Symbol	Parameter				Q1	Q2	Units
V_{DS}	Drain to Source Voltage				20	−20	V
V_{GS}	Gate to Source Voltage				±8	±8	V
I_D	Drain Current	−Continuous	T_A = 25°C	(Note 1a)	3.8	−2.6	A
		−Pulsed			6	−6	
P_D	Power Dissipation for Single Operation		T_A = 25°C	(Note 1a)	1.4		W
	Power Dissipation for Single Operation		T_A = 25°C	(Note 1b)	0.6		
T_J, T_{STG}	Operating and Storage Junction Temperature Range				−55 to +150		°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Symbol	Parameter		Value	Units
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Single Operation)	(Note 1a)	90	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Single Operation)	(Note 1b)	195	

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Type	Min.	Typ.	Max.	Units
OFF CHARACTERISTICS							
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = 250 μA, V_{GS} = 0 V I_D = −250 μA, V_{GS} = 0 V	Q1 Q2	20 −20	– –	– –	V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25°C I_D = −250 μA, referenced to 25°C	Q1 Q2	– –	16 −12	– –	mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 16 V, V_{GS} = 0 V V_{DS} = −16 V, V_{GS} = 0 V	Q1 Q2	– –	– –	1 −1	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = ±8 V, V_{DS} = 0 V	All	–	–	±10	μA
ON CHARACTERISTICS							
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA V_{GS} = V_{DS}, I_D = −250 μA	Q1 Q2	0.4 −0.4	0.7 −0.6	1.0 −1.0	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25°C I_D = −250 μA, referenced to 25°C	Q1 Q2	– –	−3 2	– –	mV/°C
$R_{DS(on)}$	Drain to Source On Resistance	V_{GS} = 4.5 V, I_D = 3.4 A V_{GS} = 2.5 V, I_D = 2.9 A V_{GS} = 1.8 V, I_D = 2.5 A V_{GS} = 1.5 V, I_D = 2.1 A V_{GS} = 4.5 V, I_D = 3.4 A, T_J = 125°C	Q1	– – – – –	55 68 85 106 76	66 86 113 160 112	mΩ
		V_{GS} = −4.5 V, I_D = −2.3 A V_{GS} = −2.5 V, I_D = −1.8 A V_{GS} = −1.8 V, I_D = −1.5 A V_{GS} = −1.5 V, I_D = −1.2 A V_{GS} = −4.5 V, I_D = −2.3 A , T_J = 125°C	Q2	– – – – –	95 120 150 190 128	142 213 331 530 190	
g_{FS}	Forward Transconductance	V_{DS} = 4.5 V, I_D = 3.4 A V_{DS} = −4.5 V, I_D = −2.3 A	Q1 Q2	– –	9 7	– –	S


ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (continued)

Symbol	Parameter	Test Conditions	Type	Min.	Typ.	Max.	Units
DYNAMIC CHARACTERISTICS							
C_{iss}	Input Capacitance	Q1: V_{DS} = 10 V, V_{GS} = 0 V, f = 1 MHz	Q1 Q2	– –	225 305	300 405	pF
C_{oss}	Output Capacitance	Q2: V_{DS} = −10 V, V_{GS} = 0 V, f = 1 MHz	Q1 Q2	– –	40 55	55 75	pF
C_{rss}	Reverse Transfer Capacitance		Q1 Q2	– –	25 50	40 75	pF
SWITCHING CHARACTERISTICS							
$t_{d(on)}$	Turn−On Delay Time	Q1: V_{DD} = 10 V, I_D = 1 A, V_{GS} = 4.5V, R_{GEN} = 6 Ω	Q1 Q2	– –	4.5 4.7	10 10	ns
t_r	Rise Time	Q2: V_{DD} = −10 V, I_D = −1 A, V_{GS} = −4.5 V, R_{GEN} = 6 Ω	Q1 Q2	– –	2.0 4.8	10 10	
$t_{d(off)}$	Turn−Off Delay Time		Q1 Q2	– –	15 33	27 53	
t_f	Fall Time		Q1 Q2	– –	1.7 16	10 29	
Q_g	Total Gate Charge	Q1: V_{DD} = 10 V, I_D = 3.4 A, V_{GS} = 4.5 V	Q1 Q2	– –	3 5.5	4.2 7.7	nC
Q_{gs}	Gate to Source Gate Charge	Q2: V_{DD} = −10 V, I_D = −2.3 A, V_{GS} = −4.5 V	Q1 Q2	– –	0.4 0.6	– –	
Q_{gd}	Gate to Drain “Miller” Charge		Q1 Q2	– –	0.6 1.4	– –	
DRAIN−SOURCE DIODE CHARACTERISTICS T_J = 25°C unless otherwise noted.							
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 0.9 A (Note 2) V_{GS} = 0 V, I_S = −0.9 A (Note 2)	Q1 Q2	– –	0.7 −0.8	1.2 −1.2	V
t_{rr}	Reverse Recovery Time	Q1: I_F = 3.4 A, Δi/Δt = 100 A/μs	Q1 Q2	– –	8.5 16	17 29	ns
Q_{rr}	Reverse Recovery Charge	Q2: I_F = −2.3 A, Δi/Δt = 100 A/μs	Q1 Q2	– –	1.4 4.4	10 10	nC


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

NOTES:

1. $R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR−4 material. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user’s board design.



a. 90 °C/W when mounted on a 1 in^2 pad of 2 oz copper



b. 195 °C/W when mounted on a minimum pad of 2 oz copper

2. Pulse Test: Pulse Width < 300 μs, Duty cycle < 2.0 %.
3. The diode connected between the gate and source serves only as protection ESD. No gate overvoltage rating is implied.

TYPICAL CHARACTERISTICS (Q1 N−CHANNEL) T_J = 25°C UNLESS OTHERWISE NOTED.




Figure 1. On-Region Characteristics




Figure 2. Normalized On−Resistance vs. Drain Current and Gate Voltage




Figure 3. Normalized On Resistance vs. Junction Temperature




Figure 4. On−Resistance vs. Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs. Source Current

TYPICAL CHARACTERISTICS (Q1 N−CHANNEL) T_J = 25°C UNLESS OTHERWISE NOTED.




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs. Drain to Source Voltage




Figure 9. Forward Bias Safe Operating Area




Figure 10. Gate Leakage Current vs. Gate to Source Voltage




Figure 11. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS (Q1 N−CHANNEL) T_J = 25°C UNLESS OTHERWISE NOTED.




Figure 12. Junction−to−Ambient Transient Thermal Response Curve

TYPICAL CHARACTERISTICS (Q2 P−CHANNEL) T_J = 25°C UNLESS OTHERWISE NOTED.




Figure 13. On-Region Characteristics




Figure 14. Normalized On−Resistance vs. Drain Current and Gate Voltage




Figure 15. Normalized On−Resistance vs. Junction Temperature




Figure 16. On Resistance vs. Gate to Source Voltage




Figure 17. Transfer Characteristics




Figure 18. Source to Drain Diode Forward Voltage vs. Source Current

TYPICAL CHARACTERISTICS (Q2 N−CHANNEL) T_J = 25°C UNLESS OTHERWISE NOTED.




Figure 19. Gate Charge Characteristics




Figure 20. Capacitance vs. Drain to Source Voltage




Figure 21. Forward Bias Safe Operating Area




Figure 22. Gate Leakage Current vs. Gate to Source Voltage




Figure 23. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS (Q2 P−CHANNEL) T_J = 25°C UNLESS OTHERWISE NOTED.






Figure 24. Junction −to−Ambient Transient Thermal Response Curve

POWERTRENCH is a registered trademark and MicroFET is a trademark of Semiconductor Components Industries, LLC dba “**onsemi**” or its affiliates and/or subsidiaries in the United States and/or other countries.


UDFN6 1.6x1.6, 0.5P
CASE 517DW
ISSUE O


DATE 31 OCT 2016





RECOMMENDED
LAND PATTERN





NOTES:

A. PACKAGE DOES NOT CONFORM TO ANY JEDEC STANDARD.
B. DIMENSIONS ARE IN MILLIMETERS.
C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 2009.
D. LAND PATTERN RECOMMENDATION IS EXISTING INDUSTRY LAND PATTERN.

DOCUMENT NUMBER:	**98AON13701G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**UDFN6 1.6x1.6, 0.5P**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales