NIF9N05CL, NIF9N05ACL

Protected Power MOSFET

2.6 A, 52 V, N−Channel, Logic Level, Clamped MOSFET w/ ESD Protection in a SOT−223 Package

ON Semiconductor®

http://onsemi.com

V_{DSS} (Clamped)	$R_{DS(ON)}$ TYP	I_D MAX
52 V	107 mΩ	2.6 A

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi REPRESENTATIVE FOR INFORMATION

Benefits


- High Energy Capability for Inductive Loads
- Low Switching Noise Generation

Features

- Diode Clamp Between Gate and Source
- ESD Protection − HBM 5000 V
- Active Over−Voltage Gate to Drain Clamp
- Scalable to Lower or Higher $R_{DS(on)}$
- Internal Series Gate Resistance
- Pb−Free Packages are Available

Applications

- Automotive and Industrial Markets:
  Solenoid Drivers, Lamp Drivers, Small Motor Drivers




MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain−to−Source Voltage Internally Clamped	V_{DSS}	52−59	V
Gate−to−Source Voltage − Continuous	V_{GS}	±15	V
Drain Current − Continuous @ T_A = 25°C − Single Pulse (t_p = 10 μs) (Note 1)	I_D I_{DM}	 2.6 10	A
Total Power Dissipation @ T_A = 25°C (Note 1)	P_D	1.69	W
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to 150	°C
Single Pulse Drain−to−Source Avalanche Energy (V_{DD} = 50 V, $I_{D(pk)}$ = 1.17 A, V_{GS} = 10 V, L = 160 mH, R_G = 25 Ω)	E_{AS}	110	mJ
Thermal Resistance, Junction−to−Ambient (Note 1) Junction−to−Ambient (Note 2)	 $R_{\theta JA}$ $R_{\theta JA}$	 74 169	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8″ from Case for 10 Seconds	T_L	260	°C


Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. When surface mounted to a FR4 board using 1″ pad size, (Cu area 1.127 in^2).
2. When surface mounted to a FR4 board using minimum recommended pad size, (Cu area 0.412 in^2).



SOT−223
CASE 318E
STYLE 3

MARKING DIAGRAM



(Top View)

A = Assembly Location
Y = Year
W = Work Week
xxxxx = F9N05 or 9N05A
▪ = Pb−Free Package
(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

© Semiconductor Components Industries, LLC, 2011

MOSFET ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Drain−to−Source Breakdown Voltage (Note 3) (V_{GS} = 0 V, I_D = 1.0 mA, T_J = 25°C) (V_{GS} = 0 V, I_D = 1.0 mA, T_J = −40°C to 125°C) Temperature Coefficient (Negative)	$V_{(BR)DSS}$	 52 50.8	 55 54 −9.3	 59 59.5	 V V mV/°C
Zero Gate Voltage Drain Current (V_{DS} = 40 V, V_{GS} = 0 V) (V_{DS} = 40 V, V_{GS} = 0 V, T_J = 125°C)	I_{DSS}			 10 25	μA
Gate−Body Leakage Current (V_{GS} = ±8 V, V_{DS} = 0 V) (V_{GS} = ±14 V, V_{DS} = 0 V)	I_{GSS}		 ±22	 ±10	μA
ON CHARACTERISTICS (Note 3)					
Gate Threshold Voltage (Note 3) (V_{DS} = V_{GS}, I_D = 100 μA) Threshold Temperature Coefficient (Negative)	$V_{GS(th)}$	1.3	1.75 −4.1	2.5	V mV/°C
Static Drain−to−Source On−Resistance (Note 3) (V_{GS} = 3.5 V, I_D = 0.6 A) (V_{GS} = 4.0 V, I_D = 1.5 A) (V_{GS} = 10 V, I_D = 2.6 A)	$R_{DS(on)}$		 190 165 107	 380 200 125	mΩ
Forward Transconductance (Note 3) (V_{DS} = 15 V, I_D = 2.6 A)	g_{FS}		3.8		Mhos
DYNAMIC CHARACTERISTICS					
Input Capacitance	C_{iss}		155	250	pF
Output Capacitance	C_{oss}		60	100	
Transfer Capacitance	C_{rss}		25	40	
Input Capacitance	C_{iss}		170		pF
Output Capacitance	C_{oss}		70		
Transfer Capacitance	C_{rss}		30		

V_{DS} = 35 V, V_{GS} = 0 V, f = 10 kHz

V_{DS} = 25 V, V_{GS} = 0 V, f = 10 kHz

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
4. Switching characteristics are independent of operating junction temperatures.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

MOSFET ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS (Note 4)						
Turn−On Delay Time	V_{GS} = 4.5 V, V_{DD} = 40 V, I_D = 2.6 A, R_D = 15.4 Ω	$t_{d(on)}$		275	465	ns
Rise Time		t_r		1418	2400	
Turn−Off Delay Time		$t_{d(off)}$		780	1320	
Fall Time		t_f		1120	1900	
Turn−On Delay Time	V_{GS} = 4.5 V, V_{DD} = 40 V, I_D = 1.0 A, R_D = 40 Ω	$t_{d(on)}$		242		ns
Rise Time		t_r		1165		
Turn−Off Delay Time		$t_{d(off)}$		906		
Fall Time		t_f		1273		
Turn−On Delay Time	V_{GS} = 10 V, V_{DD} = 15 V, I_D = 2.6 A, R_D = 5.8 Ω	$t_{d(on)}$		107		ns
Rise Time		t_r		290		
Turn−Off Delay Time		$t_{d(off)}$		1540		
Fall Time		t_f		1000		
Gate Charge	V_{GS} = 4.5 V, V_{DS} = 40 V, I_D = 2.6 A (Note 3)	Q_T		4.5	7.0	nC
		Q_1		0.9		
		Q_2		2.6		
Gate Charge	V_{GS} = 4.5 V, V_{DS} = 15 V, I_D = 1.5 A (Note 3)	Q_T		3.9		nC
		Q_1		1.0		
		Q_2		1.7		
SOURCE−DRAIN DIODE CHARACTERISTICS						
Forward On−Voltage	I_S = 2.6 A, V_{GS} = 0 V (Note 3) I_S = 2.6 A, V_{GS} = 0 V, T_J = 125°C	V_{SD}		0.81 0.66	1.5	V
Reverse Recovery Time	I_S = 1.5 A, V_{GS} = 0 V, dI_s/dt = 100 A/μs (Note 3)	t_{rr}		730		ns
		t_a		200		
		t_b		530		
Reverse Recovery Stored Charge		Q_{RR}		6.3		μC
ESD CHARACTERISTICS						
Electro−Static Discharge Capability	Human Body Model (HBM)	ESD	5000			V
	Machine Model (MM)		500			

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
4. Switching characteristics are independent of operating junction temperatures.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi REPRESENTATIVE FOR INFORMATION

TYPICAL PERFORMANCE CURVES




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance vs. Gate−to−Source Voltage




Figure 4. On−Resistance vs. Drain Current and Gate Voltage




Figure 5. On−Resistance Variation with Temperature




Figure 6. Drain−to−Source Leakage Current vs. Voltage

DISCONTINUED
DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL PERFORMANCE CURVES




Figure 7. Capacitance Variation




Figure 8. Gate−to−Source Voltage vs. Total Gate Charge




Figure 9. Resistance Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION


ORDERING INFORMATION

Device	Package	Shipping†
NIF9N05CLT1	SOT−223	1000 / Tape & Reel
NIF9N05CLT1G	SOT−223 (Pb−Free)	
NIF9N05ACLT1G		
NIF9N05CLT3	SOT−223	4000 / Tape & Reel
NIF9N05CLT3G	SOT−223 (Pb−Free)	
NIF9N05ACLT3G		

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

PACKAGE DIMENSIONS

SOT−223 (TO−261)
CASE 318E−04
ISSUE N




NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCH.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	1.50	1.63	1.75	0.060	0.064	0.068
A1	0.02	0.06	0.10	0.001	0.002	0.004
b	0.60	0.75	0.89	0.024	0.030	0.035
b1	2.90	3.06	3.20	0.115	0.121	0.126
c	0.24	0.29	0.35	0.009	0.012	0.014
D	6.30	6.50	6.70	0.249	0.256	0.263
E	3.30	3.50	3.70	0.130	0.138	0.145
e	2.20	2.30	2.40	0.087	0.091	0.094
e1	0.85	0.94	1.05	0.033	0.037	0.041
L	0.20	---	---	0.008	---	---
L1	1.50	1.75	2.00	0.060	0.069	0.078
H_E	6.70	7.00	7.30	0.264	0.276	0.287
θ	0°	–	10°	0°	–	10°

STYLE 3:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

SOLDERING FOOTPRINT



DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales