Constant Voltage / Constant Current Secondary-Side Controller

NCS1002A



SOIC-8
D SUFFIX
CASE 751

Description

The NCS1002A is a performance upgrade from the NCS1002 focused on reducing power consumption in applications that require more efficient operation. It is a highly integrated solution for Switching Mode Power Supply (SMPS) applications requiring a dual control loop to perform Constant Voltage (CV) and Constant Current (CC) regulation. The NCS1002A integrates a 2.5 V voltage reference and two precision op amps. The voltage reference, along with Op Amp 1, is the core of the voltage control-loop. Op Amp 2 is an independent, uncommitted amplifier specifically designed for the current control. Key external components needed to complete the two control loops are: (a) A resistor divider that senses the output of the power supply (battery charger) and fixes the voltage regulation set point at the specified value. (b) A sense resistor that feeds the current sensing circuit with a voltage proportional to the DC output current. This resistor determines the current regulation set point and must be adequately rated in terms of power dissipation. The NCS1002A comes in a small 8-pin SOIC package and is ideal for space-shrunk applications such as battery chargers.

Features

- Low Input Offset Voltage: 0.5 mV, Typ
- Input Common-Mode Range includes Ground
- Low Quiescent Current: 75 μA per Op Amp at V_{CC} = 5 V
- Large Output Voltage Swing
- Wide Power Supply Range: 3 V to 36 V
- High ESD Protection: 2 kV
- This is a Pb-Free Device

Typical Applications

- Battery Chargers
- Switch Mode Power Supplies

MARKING DIAGRAM



A	= Assembly Location
L	= Wafer Lot
Y	= Year
W	= Work Week
▪	= Pb-Free Package

(Note: Microdot may be in either location)

PIN CONNECTIONS



(Top View)



ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 8 of this data sheet.

© Semiconductor Components Industries, LLC, 2014

MAXIMUM RATINGS

Symbol	Parameter	Rating	Unit
V_{CC}	Supply Voltage (V_{CC} to GND) (Operating Range V_{CC} = 3 V to 36 V)	36	V
V_{id}	Differential Input Voltage	36	V
V_i	Input Voltage	−0.3 to +36	V
V_{ESD}	ESD Protection Voltage at Pin Human Body Model	2000	V
T_J	Maximum Junction Temperature	150	°C
T_A	Specification Temperature Range (T_{min} to T_{max})	−40 to +105	°C
T_{oper}	Operating Free-Air Temperature Range	−55 to +125	°C
T_{stg}	Storage Temperature Range	−65 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Symbol	Parameter	Rating	Unit
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient	175	°C/W

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS

Symbol	Characteristics	Conditions	Min	Typ	Max	Unit
I_{CC}	Total Supply Current, excluding current in the Voltage Reference V_{CC} = 5 V, no load; −40 ≤ T_A ≤ +105 °C		–	0.15	0.25	mA
I_{CC}	Total Supply Current, excluding Current in the Voltage Reference V_{CC} = 30 V, no load; −40 ≤ T_A ≤ +105 °C		–	0.2	0.3	mA

OP AMP 1 (OP AMP WITH NONINVERTING INPUT CONNECTED TO THE INTERNAL V_{ref})
(V_{CC} = 5 V, T_A = 25 °C unless otherwise noted)

V_{IO}	Input Offset Voltage	T_A = 25 °C	–	–	2.0	mV
		−40 ≤ T_A ≤ +105 °C	–	–	3.0	mV
DV_{IO}	Input Offset Voltage Drift (−40 ≤ T_A ≤ +105 °C)		–	7.0	–	μV/°C
I_{IB}	Input Bias Current (Inverting Input Only)		–	20	150	nA
AVD	Large Signal Voltage Gain (V_{CC} = 15 V, R_L = 2 kΩ, V_{ICM} = 0 V)		–	100	–	V/mV
PSRR	Power Supply Rejection (V_{CC} = 5.0 V to 30 V, V_{OUT} = 2 V)		80	100	–	dB
I_{SOURCE}	Output Source Current (V_{CC} = 15 V, V_{OUT} = 2.0 V, V_{id} = 1 V)		20	40	–	mA
I_O	Short Circuit to GND (V_{CC} = 15 V)		–	40	60	mA
I_{SINK}	Output Current Sink (V_{id} = −1 V)	V_{CC} = +15 V, V_{OUT} = 0.2 V (Note 1)	1	10	–	mA
		V_{CC} = +15 V, V_{OUT} = 2 V	10	20	–	mA
V_{OH}	Output Voltage Swing, High (V_{CC} = 30 V)	R_L = 2 kΩ, T_A = 25 °C	26	27	–	V
		−40 ≤ T_A ≤ +105 °C	26	–	–	
		R_L = 10 kΩ, T_A = 25 °C	27	28	–	
		−40 ≤ T_A ≤ +105 °C	27	–	–	
V_{OL}	Output Voltage Swing, Low	R_L = 10 kΩ, T_A = 25 °C	–	5.0	50	mV
SR	Slew Rate (AV = +1, V_i = 0.5 V to 2 V, V_{CC} = 15 V, R_L = 2 kΩ, C_L = 100 pF)		0.2	0.4	–	V/μs
GBP	Gain Bandwidth Product (V_{CC} = 30 V, AV = +1, (Note 1) R_L = 2 kΩ, C_L = 100 pF, f = 100 kHz, V_{IN} = 10 mV_{PP})		0.5	0.9	–	MHz
THD	Total Harmonic Distortion (f = 1 kHz, AV = 10, R_L = 2 kΩ, V_{CC} = 30 V, V_{OUT} = 2 V_{PP})		–	0.08	–	%

OP AMP 2 (INDEPENDENT OP AMP) (V_{CC} = 5.0 V, T_A = 25 °C unless otherwise noted)

V_{IO}	Input Offset Voltage	T_A = 25 °C	–	0.5	2.0	mV
		−40 ≤ T_A ≤ +105 °C	–	–	3.0	
DV_{IO}	Input Offset Voltage Drift (−40 ≤ T_A ≤ +105 °C)		–	7.0	–	μV/°C
I_{IO}	Input Offset Current	T_A = 25°C	–	2.0	75	nA
		−40 ≤ T_A ≤ +105 °C	–	–	150	
I_B	Input Bias Current	T_A = 25 °C	–	20	150	nA
		−40 ≤ T_A ≤ +105 °C	–	–	200	
AVD	Large Signal Voltage Gain (V_{CC} = 15 V, R_L = 2 kΩ, V_{OUT} = 1.4 V to 11.4 V)	T_A = 25 °C	50	100	–	V/mV
		−40 ≤ T_A ≤ +105 °C	25	–	–	
PSRR	Power Supply Rejection (V_{CC} = 5 V to 30 V)		80	100	–	dB

1. Guaranteed by design and/or characterization.

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (continued)

Symbol	Characteristics	Conditions	Min	Typ	Max	Unit
OP AMP 2 (INDEPENDENT OP AMP) (continued) (V_{CC} = 5.0 V, T_A = 25 °C unless otherwise noted)						
V_{ICM}	Input Common Mode Voltage Range (Note 2) (V_{CC} = +30 V)	T_A = 25 °C	0	–	V_{CC} - 1.5	V
		−40 ≤ T_A ≤ +105 °C	0	–	V_{CC} - 2.0	
CMRR	Common Mode Rejection Ratio (Note 4)	0 to V_{CC} - 1.7 V, T_A = 25 °C	70	85	–	dB
		0 to V_{CC} - 2.2 V −40 ≤ T_A ≤ +105 °C	60	–	–	
I_{SOURCE}	Output Current Source (V_{CC} = 15 V, V_{OUT} = 2 V, V_{ID} = +1 V)		20	40	–	mA
I_O	Short-Circuit to GND (V_{CC} = 15 V)		–	40	60	mA
I_{SINK}	Output Current Sink (V_{ID} = −1 V)	V_{CC} = +15 V, V_{OUT} = 0.2 V	1	10	–	mA
		V_{CC} = +15 V, V_{OUT} = 2 V	10	20	–	mA
V_{OH}	Output Voltage Swing, High (V_{CC} = 30 V)	R_L = 2 kΩ, T_A = 25 °C	26	27	–	V
		−40 ≤ T_A ≤ +105 °C	26	–	–	
		R_L = 10 kΩ, T_A = 25 °C	27	28	–	
		−40 ≤ T_A ≤ +105 °C	27	–	–	
V_{OL}	Output Voltage Swing, Low	R_L = 10 kΩ, T_A = 25 °C	–	5.0	50	mV
SR	Slew Rate (AV = +1, V_i = 0.5 V to 3 V, V_{CC} = 15 V, R_L = 2 kΩ, C_L = 100 pF)		0.2	0.4	–	V/μs
GBP	Gain Bandwidth Product (V_{CC} = 30 V, AV = +1, R_L = 2 kΩ, C_L = 100 pF, f = 100 kHz, V_{IN} = 10 mV_{PP}) (Note 4)		0.5	0.9	–	MHz
THD	Total Harmonic Distortion (f = 1 kHz, AV = 10, R_L = 2 kΩ, V_{CC} = 30 V, V_{OUT} = 2 V_{PP})		–	0.08	–	%
e_{noise}	Equivalent Input Noise Voltage (f = 1 kHz, R_S = 100 Ω, V_{CC} = 30 V)		–	50	–	nV/√Hz
VOLTAGE REFERENCE (V_{CC} = 5.0 V, T_A = 25 °C unless otherwise noted)						
I_K	Cathode Current		0.05		100	mA
V_{ref}	Reference Voltage (I_K = 1 mA)	T_A = 25 °C	2.49	2.5	2.51	V
		−40 ≤ T_A ≤ +105 °C	2.48	2.5	2.52	
ΔV_{ref}	Reference Deviation over Temperature (V_{KA} = V_{ref}, I_K = 10 mA, −40 ≤ T_A ≤ +105 °C) (Note 4)		–	7.0	30	mV
I_{min}	Minimum Cathode Current for Regulation (2.4875 V_f ≤ V_{KA} ≤ 2.5125 V_f)		–	10	50	μA
I ZKA I	Dynamic Impedance (Note 3) (V_{KA} = V_{ref}, I_K = 1 mA to 100 mA, f < 1 kHz)		–	0.2	0.5	Ω

2. The input common-mode voltage of either input signal should not be allowed to go negative by more than 0.3 V. The upper end of the common-mode range is V_{CC} - 1.5 V. Both inputs can go to V_{CC} + 0.3 V without damage.
3. The Dynamic Impedance is defined as I ZKA I = $\Delta V_{KA} / \Delta I_K$.
4. Guaranteed by design and/or characterization.

Share Feedback
Your Opinion Matters



Figure 1. Input Offset Voltage vs. Temperature



Figure 2. IB vs. Temperature



Figure 3. Vref as a Function of IK



Figure 4. Vref Over Temperature



Figure 5. Ref Dynamic Impedance vs. Temperature

Share Feedback
Your Opinion Matters



Figure 6. NCS1002A PSRR vs. Supply Voltage



Figure 7. NCS1002A CMRR vs. Supply Voltage



Figure 8. Distortion vs. Frequency



Figure 9. Output Voltage Swing vs. Output Current
V_{id} = 1 V, V_{CM} = 0 V, V_{CC} = 3 V to 36 V



Figure 10. Region of Reference Stability vs. Capacitive Load (Pin 3)

Share Feedback
Your Opinion Matters



Figure 1. AC Adapter Application

Share Feedback
Your Opinion Matters

ORDERING INFORMATION

Device	Package	Shipping†
NCS1002ADR2G	SOIC-8 (Pb-Free)	2,500 / Tape & Reel

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Share Feedback
Your Opinion Matters

REVISION HISTORY

Revision	Description of Changes	Date
7	Rebranded the Data Sheet to **onsemi** format.	01/13/2026

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.

Share Feedback
Your Opinion Matters



SCALE 1:1

SOIC−8 NB
CASE 751−07
ISSUE AK

DATE 16 FEB 2011



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751−01 THRU 751−06 ARE OBSOLETE. NEW STANDARD IS 751−07.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	4.80	5.00	0.189	0.197
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.053	0.069
D	0.33	0.51	0.013	0.020
G	1.27 BSC		0.050 BSC	
H	0.10	0.25	0.004	0.010
J	0.19	0.25	0.007	0.010
K	0.40	1.27	0.016	0.050
M	0°	8°	0°	8°
N	0.25	0.50	0.010	0.020
S	5.80	6.20	0.228	0.244

SOLDERING FOOTPRINT*



SCALE 6:1 (mm / inches)

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

XXXXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42564B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOIC−8 NB**		**PAGE 1 OF 2**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

SOIC−8 NB
CASE 751−07
ISSUE AK

DATE 16 FEB 2011

STYLE 1:
PIN 1. EMITTER
2. COLLECTOR
3. COLLECTOR
4. EMITTER
5. EMITTER
6. BASE
7. BASE
8. EMITTER

STYLE 2:
PIN 1. COLLECTOR, DIE, #1
2. COLLECTOR, #1
3. COLLECTOR, #2
4. COLLECTOR, #2
5. BASE, #2
6. EMITTER, #2
7. BASE, #1
8. EMITTER, #1

STYLE 3:
PIN 1. DRAIN, DIE #1
2. DRAIN, #1
3. DRAIN, #2
4. DRAIN, #2
5. GATE, #2
6. SOURCE, #2
7. GATE, #1
8. SOURCE, #1

STYLE 4:
PIN 1. ANODE
2. ANODE
3. ANODE
4. ANODE
5. ANODE
6. ANODE
7. ANODE
8. COMMON CATHODE

STYLE 5:
PIN 1. DRAIN
2. DRAIN
3. DRAIN
4. DRAIN
5. GATE
6. GATE
7. SOURCE
8. SOURCE

STYLE 6:
PIN 1. SOURCE
2. DRAIN
3. DRAIN
4. SOURCE
5. SOURCE
6. GATE
7. GATE
8. SOURCE

STYLE 7:
PIN 1. INPUT
2. EXTERNAL BYPASS
3. THIRD STAGE SOURCE
4. GROUND
5. DRAIN
6. GATE 3
7. SECOND STAGE Vd
8. FIRST STAGE Vd

STYLE 8:
PIN 1. COLLECTOR, DIE #1
2. BASE, #1
3. BASE, #2
4. COLLECTOR, #2
5. COLLECTOR, #2
6. EMITTER, #2
7. EMITTER, #1
8. COLLECTOR, #1

STYLE 9:
PIN 1. EMITTER, COMMON
2. COLLECTOR, DIE #1
3. COLLECTOR, DIE #2
4. EMITTER, COMMON
5. EMITTER, COMMON
6. BASE, DIE #2
7. BASE, DIE #1
8. EMITTER, COMMON

STYLE 10:
PIN 1. GROUND
2. BIAS 1
3. OUTPUT
4. GROUND
5. GROUND
6. BIAS 2
7. INPUT
8. GROUND

STYLE 11:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. DRAIN 2
7. DRAIN 1
8. DRAIN 1

STYLE 12:
PIN 1. SOURCE
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 13:
PIN 1. N.C.
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 14:
PIN 1. N−SOURCE
2. N−GATE
3. P−SOURCE
4. P−GATE
5. P−DRAIN
6. P−DRAIN
7. N−DRAIN
8. N−DRAIN

STYLE 15:
PIN 1. ANODE 1
2. ANODE 1
3. ANODE 1
4. ANODE 1
5. CATHODE, COMMON
6. CATHODE, COMMON
7. CATHODE, COMMON
8. CATHODE, COMMON

STYLE 16:
PIN 1. EMITTER, DIE #1
2. BASE, DIE #1
3. EMITTER, DIE #2
4. BASE, DIE #2
5. COLLECTOR, DIE #2
6. COLLECTOR, DIE #2
7. COLLECTOR, DIE #1
8. COLLECTOR, DIE #1

STYLE 17:
PIN 1. VCC
2. V2OUT
3. V1OUT
4. TXE
5. RXE
6. VEE
7. GND
8. ACC

STYLE 18:
PIN 1. ANODE
2. ANODE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. CATHODE
8. CATHODE

STYLE 19:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. MIRROR 2
7. DRAIN 1
8. MIRROR 1

STYLE 20:
PIN 1. SOURCE (N)
2. GATE (N)
3. SOURCE (P)
4. GATE (P)
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 21:
PIN 1. CATHODE 1
2. CATHODE 2
3. CATHODE 3
4. CATHODE 4
5. CATHODE 5
6. COMMON ANODE
7. COMMON ANODE
8. CATHODE 6

STYLE 22:
PIN 1. I/O LINE 1
2. COMMON CATHODE/VCC
3. COMMON CATHODE/VCC
4. I/O LINE 3
5. COMMON ANODE/GND
6. I/O LINE 4
7. I/O LINE 5
8. COMMON ANODE/GND

STYLE 23:
PIN 1. LINE 1 IN
2. COMMON ANODE/GND
3. COMMON ANODE/GND
4. LINE 2 IN
5. LINE 2 OUT
6. COMMON ANODE/GND
7. COMMON ANODE/GND
8. LINE 1 OUT

STYLE 24:
PIN 1. BASE
2. EMITTER
3. COLLECTOR/ANODE
4. COLLECTOR/ANODE
5. CATHODE
6. CATHODE
7. COLLECTOR/ANODE
8. COLLECTOR/ANODE

STYLE 25:
PIN 1. VIN
2. N/C
3. REXT
4. GND
5. IOUT
6. IOUT
7. IOUT
8. IOUT

STYLE 26:
PIN 1. GND
2. dv/dt
3. ENABLE
4. ILIMIT
5. SOURCE
6. SOURCE
7. SOURCE
8. VCC

STYLE 27:
PIN 1. ILIMIT
2. OVLO
3. UVLO
4. INPUT+
5. SOURCE
6. SOURCE
7. SOURCE
8. DRAIN

STYLE 28:
PIN 1. SW_TO_GND
2. DASIC_OFF
3. DASIC_SW_DET
4. GND
5. V_MON
6. VBULK
7. VBULK
8. VIN

STYLE 29:
PIN 1. BASE, DIE #1
2. EMITTER, #1
3. BASE, #2
4. EMITTER, #2
5. COLLECTOR, #2
6. COLLECTOR, #2
7. COLLECTOR, #1
8. COLLECTOR, #1

STYLE 30:
PIN 1. DRAIN 1
2. DRAIN 1
3. GATE 2
4. SOURCE 2
5. SOURCE 1/DRAIN 2
6. SOURCE 1/DRAIN 2
7. SOURCE 1/DRAIN 2
8. GATE 1

DOCUMENT NUMBER:	**98ASB42564B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOIC−8 NB**		**PAGE 2 OF 2**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales