Silicon Power Transistors


NJW21193G (PNP)
NJW21194G (NPN)

16 AMPERES
COMPLEMENTARY SILICON
POWER TRANSISTORS
250 VOLTS, 200 WATTS


The NJW21193G and NJW21194G utilize Perforated Emitter technology and are specifically designed for high power audio output, disk head positioners and linear applications.

Features

- Total Harmonic Distortion Characterized
- High DC Current Gain
- Excellent Gain Linearity
- High SOA
- These Devices are Pb-Free and are RoHS Compliant



TO-3P
CASE 340AB
STYLES 1,2,3



MAXIMUM RATINGS


Symbol	Rating	Value	Unit
V_{CEO}	Collector-Emitter Voltage	250	Vdc
V_{CBO}	Collector-Base Voltage	400	Vdc
V_{EBO}	Emitter-Base Voltage	5.0	Vdc
V_{CEX}	Collector-Emitter Voltage – 1.5 V	400	Vdc
I_C	Collector Current – Continuous	16	Adc
I_{CM}	Collector Current – Peak (Note 1)	30	Adc
I_B	Base Current – Continuous	5.0	Adc
P_D	Total Power Dissipation @ T_C = 25 °C Derate Above 25 °C	200 1.6	W W/°C
T_J, T_{stg}	Operating and Storage Junction Temperature Range	– 65 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
1. Pulse Test: Pulse Width = 5 μs, Duty Cycle ≤ 10%.

THERMAL CHARACTERISTICS

Symbol	Characteristic	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	0.625	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction–to–Ambient	40	°C/W

MARKING DIAGRAM



NJW2119= Specific Device Code
x = 3 or 4
G = Pb-Free Package
A = Assembly Location
Y = Year
WW = Work Week

ORDERING INFORMATION

Device	Package	Shipping
NJW21193G	TO-3P (Pb-Free)	30 Units/Rail
NJW21194G	TO-3P (Pb-Free)	30 Units/Rail

© Semiconductor Components Industries, LLC, 2013

ELECTRICAL CHARACTERISTICS (T_C = 25 °C unless otherwise noted)

Symbol	Characteristic	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
$V_{CEO(sus)}$	Collector-Emitter Sustaining Voltage (I_C = 100 mAdc, I_B = 0)	250	–	–	Vdc
I_{CEO}	Collector Cutoff Current (V_{CE} = 200 Vdc, I_B = 0)	–	–	100	μAdc
I_{EBO}	Emitter Cutoff Current (V_{CE} = 5 Vdc, I_C = 0)	–	–	100	μAdc
I_{CEX}	Collector Cutoff Current (V_{CE} = 250 Vdc, $V_{BE(off)}$ = 1.5 Vdc)	–	–	100	μAdc
SECOND BREAKDOWN					
$I_{S/b}$	Second Breakdown Collector Current with Base Forward Biased				Adc
	(V_{CE} = 50 Vdc, t = 1 s (non-repetitive)	4.0	–	–	
	(V_{CE} = 80 Vdc, t = 1 s (non-repetitive)	2.25	–	–	
ON CHARACTERISTICS					
h_{FE}	DC Current Gain				
	(I_C = 8 Adc, V_{CE} = 5 Vdc)	20	–	80	
	(I_C = 16 Adc, I_B = 5 Adc)	8	–	–	
$V_{BE(on)}$	Base-Emitter On Voltage (I_C = 8 Adc, V_{CE} = 5 Vdc)	–	–	2.2	Vdc
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage				Vdc
	(I_C = 8 Adc, I_B = 0.8 Adc)	–	–	1.4	
	(I_C = 16 Adc, I_B = 3.2 Adc)	–	–	4	
DYNAMIC CHARACTERISTICS					
T_{HD}	Total Harmonic Distortion at the Output				%
	V_{RMS} = 28.3 V, f = 1 kHz, P_{LOAD} = 100 W_{RMS} h_{FE} unmatched	–	0.8	–	
	(Matched pair h_{FE} = 50 @ 5 A/5 V) h_{FE} matched	–	0.08	–	
f_T	Current Gain Bandwidth Product (I_C = 1 Adc, V_{CE} = 10 Vdc, f_{test} = 1 MHz)	4	–	–	MHz
C_{ob}	Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f_{test} = 1 MHz)	–	–	500	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS

PNP NJW21193G




Figure 1. Typical Current Gain Bandwidth Product

NPN NJW21194G




Figure 2. Typical Current Gain Bandwidth Product

PNP NJW21193G




Figure 3. DC Current Gain, V_{CE} = 20 V

NPN NJW21194G




Figure 4. DC Current Gain, V_{CE} = 20 V

PNP NJW21193G




Figure 5. DC Current Gain, V_{CE} = 5 V

NPN NJW21194G




Figure 6. DC Current Gain, V_{CE} = 5 V

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS

PNP NJW21193G




Figure 7. Typical Output Characteristics

NPN NJW21194G




Figure 8. Typical Output Characteristics

PNP NJW21193G




Figure 9. Typical Saturation Voltages

NPN NJW21194G




Figure 10. Typical Saturation Voltages

PNP NJW21193G




Figure 11. Typical Base-Emitter Voltage

NPN NJW21194G




Figure 12. Typical Base-Emitter Voltage

Share Feedback
Your Opinion Matters

PNP NJW21193G




Figure 13. Active Region Safe Operating Area

NPN NJW21194G




Figure 14. Active Region Safe Operating Area

There are two limitations on the power handling ability of a transistor; average junction temperature and secondary breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 13 is based on $T_{J(pk)}$ = 150 °C; T_C is variable depending on conditions. At high case temperatures, thermal limitations will reduce the power than can be handled to values less than the limitations imposed by second breakdown.

Share Feedback
Your Opinion Matters




Figure 15. NJW21193G Typical Capacitance




Figure 16. NJW21194G Typical Capacitance




Figure 17. Typical Total Harmonic Distortion




Figure 18. Total Harmonic Distortion Test Circuit

Share Feedback
Your Opinion Matters

REVISION HISTORY


Revision	Description of Changes	Date
2	Rebranded the Data Sheet to **onsemi** format.	7/7/2025

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.


Share Feedback
Your Opinion Matters

TO−3P−3LD
CASE 340AB
ISSUE A

DATE 30 OCT 2007



SCALE 1:1



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30mm FROM THE TERMINAL TIP.
4. DIMENSION A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.


	MILLIMETERS		
DIM	MIN	NOM	MAX
A	19.70	19.90	20.10
B	15.40	15.60	15.80
C	4.60	4.80	5.00
D	0.80	1.00	1.20
E	1.45	1.50	1.65
F	1.80	2.00	2.20
G	5.45 BSC		
H	1.20	1.40	1.60
J	0.55	0.60	0.75
K	19.80	20.00	20.20
L	18.50	18.70	18.90
P	3.30	3.50	3.70
Q	3.10	3.20	3.50
U	5.00 REF		
W	2.80	3.00	3.20

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. CATHODE

STYLE 3:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

GENERIC MARKING DIAGRAM*



xxxxx = Specific Device Code
G = Pb−Free Package
A = Assembly Location
Y = Year
WW = Work Week

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G”, may or not be present.

DOCUMENT NUMBER:	**98AON25095D**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−3P−3LD**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales