Analog Multiplexers / Demultiplexers

MC14067B

The MC14067 multiplexer/demultiplexer is a digitally controlled analog switch featuring low ON resistance and very low leakage current. This device can be used in either digital or analog applications.

The MC14067 is a 16-channel multiplexer/demultiplexer with an inhibit and four binary control inputs A, B, C, and D. These control inputs select 1-of-16 channels by turning ON the appropriate analog switch (see MC14067 truth table.)

Features

- Low OFF Leakage Current
- Matched Channel Resistance
- Low Quiescent Power Consumption
- Low Crosstalk Between Channels
- Wide Operating Voltage Range: 3 to 18 V
- Low Noise
- Pin for Pin Replacement for CD4067B
- These Devices are Pb-Free and are RoHS Compliant
- NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable

MAXIMUM RATINGS (Voltages Referenced to V_{SS})

Symbol	Parameter	Value	Unit
V_{DD}	DC Supply Voltage Range	– 0.5 to + 18.0	V
V_{in}, V_{out}	Input or Output Voltage Range (DC or Transient)	– 0.5 to V_{DD} + 0.5	V
I_{in}	Input Current (DC or Transient), per Control Pin	±10	mA
I_{sw}	Switch Through Current	±25	mA
P_D	Power Dissipation, per Package (Note 1)	500	mW
T_A	Ambient Temperature Range	– 55 to + 125	°C
T_{stg}	Storage Temperature Range	– 65 to + 150	°C
T_L	Lead Temperature (8–Second Soldering)	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Temperature Derating:
   Plastic “P and D/DW” Packages: − 7.0 mW/°C From 65 °C To 125 °C

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation, V_{in} and V_{out} should be constrained to the range $V_{SS} \le (V_{in}$ or $V_{out}) \le V_{DD}$.

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either V_{SS} or V_{DD}). Unused outputs must be left open.



SOIC-24
DW SUFFIX
CASE 751E

MARKING DIAGRAM



A = Assembly Location
WL = Wafer Lot
YY = Year
WW = Work Week
G = Pb-Free Package

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.


NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 5.

© Semiconductor Components Industries, LLC, 2011


TRUTH TABLE

Control Inputs					Selected Channel
A	B	C	D	Inh	
X	X	X	X	1	None
0	0	0	0	0	X0
1	0	0	0	0	X1
0	1	0	0	0	X2
1	1	0	0	0	X3
0	0	1	0	0	X4
1	0	1	0	0	X5
0	1	1	0	0	X6
1	1	1	0	0	X7
0	0	0	1	0	X8
1	0	0	1	0	X9
0	1	0	1	0	X10
1	1	0	1	0	X11
0	0	1	1	0	X12
1	0	1	1	0	X13
0	1	1	1	0	X14
1	1	1	1	0	X15


PIN ASSIGNMENT



16-Channel Analog Multiplexer/Demultiplexer



FUNCTIONAL DIAGRAM



Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	V_{DD}	Test Conditions	− 55 °C Min	− 55 °C Max	25 °C Min	25 °C Typ (2)	25 °C Max	125 °C Min	125 °C Max	Unit
SUPPLY REQUIREMENTS (Voltages Referenced to V_{SS})											
Power Supply Voltage Range	V_{DD}	−		3.0	18	3.0	−	18	3.0	18	V
Quiescent Current Per Package	I_{DD}	5.0 10 15	Control Inputs: V_{in} = V_{SS} or V_{DD}, Switch I/O: $V_{SS} \le V_{I/O} \le V_{DD}$, and $\Delta V_{switch} \le 500$ mV (3)	− − −	5.0 10 20	− − −	0.005 0.010 0.015	5.0 10 20	− − −	150 300 600	μA
Total Supply Current (Dynamic Plus Quiescent, Per Package	$I_{D(AV)}$	5.0 10 15	T_A = 25 °C only (The channel component, $(V_{in} - V_{out})/R_{on}$, is not included.)	Typical			(0.07 μA/kHz) f + I_{DD} (0.20 μA/kHz) f + I_{DD} (0.36 μA/kHz) f + I_{DD}				μA
CONTROL INPUTS — INHIBIT, A, B, C, D (Voltages Referenced to V_{SS})											
Low-Level Input Voltage	V_{IL}	5.0 10 15	R_{on} = per spec, I_{off} = per spec	− − −	1.5 3.0 4.0	− − −	2.25 4.50 6.75	1.5 3.0 4.0	− − −	1.5 3.0 4.0	V
High-Level Input Voltage	V_{IH}	5.0 10 15	R_{on} = per spec, I_{off} = per spec	3.5 7.0 11	− − −	3.5 7.0 11	2.75 5.50 8.25	− − −	3.5 7.0 11	− − −	V
Input Leakage Current	I_{in}	15	V_{in} = 0 or V_{DD}	−	± 0.1	−	±0.00001	± 0.1	−	1.0	μA
Input Capacitance	C_{in}	—		−	−	−	5.0	7.5	−	−	pF
SWITCHES IN/OUT AND COMMONS OUT/IN — X, Y (Voltages Referenced to V_{SS})											
Recommended Peak-to-Peak Voltage Into or Out of the Switch	$V_{I/O}$	−	Channel On or Off	0	V_{DD}	0	−	V_{DD}	0	V_{DD}	V_{p-p}
Recommended Static or Dynamic Voltage Across the Switch (3) (Figure 1)	ΔV_{switch}	−	Channel On	0	600	0	−	600	0	300	mV
Output Offset Voltage	V_{OO}	−	V_{in} = 0 V, No Load	−	−	−	10	−	−	−	μV
ON Resistance	R_{on}	5.0 10 15	$\Delta V_{switch} \le 500$ mV (3), $V_{in} = V_{IL}$ or V_{IH} (Control), and V_{in} 0 to V_{DD} (Switch)	− − −	800 400 220	− − −	250 120 80	1050 500 280	− − −	1300 550 320	Ω
ΔON Resistance Between Any Two Channels in the Same Package	ΔR_{on}	5.0 10 15		− − −	70 50 45	− − −	25 10 10	70 50 45	− − −	135 95 65	Ω
Off−Channel Leakage Current (Figure 2)	I_{off}	15	$V_{in} = V_{IL}$ or V_{IH} (Control) Channel to Channel or Any One Channel	−	± 100	−	± 0.05	±100	−	±1000	nA
Capacitance, Switch I/O	$C_{I/O}$	−	Inhibit = V_{DD}	−	—	—	10	−	−	−	pF
Capacitance, Common O/I	$C_{O/I}$	−	Inhibit = V_{DD} (MC14067B) (MC14097B)	 − −	 − −	 − −	 100 60	 − −	 − −	 − −	pF
Capacitance, Feedthrough (Channel Off)	$C_{I/O}$	− −	Pins Not Adjacent Pins Adjacent	−	−	−	0.47	−	−	−	pF

2. Data labeled “Typ” is not to be used for design purposes, but is intended as an indication of the IC’s potential performance.
3. For voltage drops across the switch (ΔV_{switch}) > 600 mV (> 300 mV at high temperature), excessive V_{DD} current may be drawn; i.e. the current out of the switch may contain both V_{DD} and switch input components. The reliability of the device will be unaffected unless the Maximum Ratings are exceeded. (See first page of this data sheet.)

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (C_L = 50 pF, T_A = 25 °C)

Characteristic	Symbol	$V_{DD} - V_{SS}$ Vdc	Typ (4)	Max	Unit
Propagation Delay Times Channel Input-to-Channel Output (R_L = 200 kΩ) MC14067B	t_{PLH}, t_{PHL} (Figure 3)	 5.0 10 15	 35 15 12	 90 40 30	ns
Propagation Delay Times Channel Input-to-Channel Output (R_L = 1.0 kΩ) MC14067B	t_{PLH}, t_{PHL} (Figure 3)	 5.0 10 15		 50 30 20	ns
Control Input-to-Channel Output Channel Turn-On Time (R_L = 10 kΩ) MC14067B	 t_{PZH}, t_{PZL}	 5.0 10 15	 240 115 75	 600 290 190	ns
Channel Turn-Off Time (R_L = 300 kΩ) MC14067B	(Figure 4) t_{PHZ}, t_{PLZ}	 5.0 10 15	 250 120 75	 625 300 190	ns
Channel Turn-Off Time (R_L = 10 kΩ) MC14067B	(Figure 4)	 5.0 10 15		 625 450 350	ns
Any Pair of Address Inputs to Output MC14067B	t_{PLH}, t_{PHL}	 5.0 10 15	 280 115 85	 700 290 215	ns
Second Harmonic Distortion (R_L = 10 kΩ, f = 1 kHz, V_{in} = 5 V_{p-p})	–	10	0.3	–	%
ON Channel Bandwidth [R_L = 50 Ω, V_{in} = 1/2 ($V_{DD} - V_{SS}$) $_{p-p}$(sine-wave)] 20 Log10 (V_{out}/V_{in}) = − 3 dB MC14067B	BW (Figure 5)	 10	 15	 –	MHz
Off Channel Feedthrough Attenuation [R_L = 50 Ω, V_{in} = 1/2 ($V_{DD}-V_{SS}$) $_{p-p}$(sine-wave)] f_{in} = 20 MHz – MC14067B	– (Figure 5)	10	– 40	–	dB
Channel Separation [R_L = 1 kΩ, V_{in} = 1/2 ($V_{DD}-V_{SS}$) $_{p-p}$ (sine-wave)] f_{in} = 20 MHz	– (Figure 6)	10	– 40	–	dB
Crosstalk, Control Inputs-to-Common O/I (R1 = 1 kΩ, R_L = 10 kΩ, Control t_r = t_f = 20 ns, Inhibit = V_{SS})	– (Figure 7)	10	30	–	mV

4. Data labelled “Typ” is not to be used for design purposes but is intended as an indication of the IC’s potential performance.

Share Feedback
Your Opinion Matters

ORDERING INFORMATION

Device	Package	Shipping†
MC14067BDWG	SOIC-24 (Pb-Free)	30 Units / Rail
MC14067BDWR2G	SOIC-24 (Pb-Free)	1000 Units / Tape & Reel
NLV14067BDWR2G*		

DISCONTINUED (Note 5)

NLV14067BDWG*	SOIC-24 (Pb-Free)	30 Units / Rail

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

* NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable.

5. **DISCONTINUED:** This device is not recommended for new design. Please contact your **onsemi** representative for information. The most current information on this device may be available on www.onsemi.com.




Figure 1. ΔV Across Switch




Figure 2. Off Channel Leakage




Figure 3. Propagation Delay Test Circuit and Waveforms V_{in} to V_{out}




Figure 4. Turn-On and Delay Turn-Off Test Circuit and Waveforms

Share Feedback
Your Opinion Matters

A, B, and C inputs used to turn ON or OFF the switch under test.




Figure 5. Bandwidth and Off-Channel Feedthrough Attenuation




Figure 6. Channel Separation (Adjacent Channels Used for Setup)




Figure 7. Crosstalk, Control to Common O/I




Figure 8. Channel Resistance (R_{ON}) Test Circuit




Figure 9. Propagation Delay, Any Pair of Address Inputs to Output

Share Feedback
Your Opinion Matters

TYPICAL RESISTANCE CHARACTERISTICS




Figure 10. V_{DD} = 7.5 V, V_{SS} = − 7.5 V




Figure 11. V_{DD} = 5.0 V, V_{SS} = − 5.0 V




Figure 12. V_{DD} = 2.5 V, V_{SS} = − 2.5 V




Figure 13. Comparison at 25 °C, V_{DD} = −V_{SS}

Share Feedback
Your Opinion Matters

APPLICATIONS INFORMATION

Figure A illustrates use of the Analog Multiplexer / Demultiplexer. The 0-to-5 V Digital Control signal is used to directly control a 5 V_{p-p} analog signal.

The digital control logic levels are determined by V_{DD} and V_{SS}. The V_{DD} voltage is the logic high voltage; the V_{SS} voltage is logic low. For the example. V_{DD} = + 5 V = logic high at the control inputs; V_{SS} = GND = 0 V = logic low.

The maximum analog signal level is determined by V_{DD} and V_{SS}. The analog voltage must swing neither higher than V_{DD} nor lower than V_{SS}. The example shows a 5 V_{p-p} signal which allows no margin at either peak. If voltage transients above V_{DD} and/or below V_{SS} are anticipated on the analog channels, external diodes (D_x) are recommended as shown in Figure B. These diodes should be small signal types able to absorb the maximum anticipated current surges during clipping.

The absolute maximum potential difference between V_{DD} and V_{SS} is 18.0 volts. Most parameters are specified up to 15 V which is the recommended maximum difference between V_{DD} and V_{SS}.




Figure A. Application Example




Figure B. External Germanium or Schottky Clipping Diodes

Share Feedback
Your Opinion Matters

REVISION HISTORY

Revision	Description of Changes	Date
9	Rebranded the Data Sheet to **onsemi** format. NLV14067BDWG OPN Marked as Discontinued.	8/26/2025

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.

Share Feedback
Your Opinion Matters

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales