
NPN Epitaxial Silicon Transistor

BD135, 137, 139



TO-126-3LD
CASE 340AS


Features

- Complement to BD136, BD138 and BD140 Respectively
- These are Pb-Free Devices

Applications

- Medium Power Linear and Switching

MARKING DIAGRAM



&3 = 3-Digit Date Code
XXXXX = Specific Device Code

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C unless otherwise noted)

Symbol	Parameter		Ratings	Units
V_{CBO}	Collector-Base Voltage	BD135	45	V
		BD137	60	
		BD139	80	
V_{CEO}	Collector-Emitter Voltage	BD135	45	V
		BD137	60	
		BD139	80	
V_{EBO}	Emitter-Base Voltage		5	V
I_C	Collector Current (DC)		1.5	A
I_{CP}	Collector Current (Pulse)		3.0	A
I_B	Base Current		0.5	A
P_C	Device Dissipation	T_C = 25 °C	12.5	W
		T_A = 25 °C	1.25	W
T_J	Junction Temperature		150	°C
T_{STG}	Storage Temperature		−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Symbol	Parameter	Max	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	10	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	100	°C/W

ORDERING INFORMATION

See detailed ordering, marking and shipping information on page 4 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 4.

© Semiconductor Components Industries, LLC, 2007

ELECTRICAL CHARACTERISTICS (T_C = 25 °C unless otherwise noted)

Symbol	Parameter		Test Condition	Min	Typ	Max	Unit
V_{CEO}(sus)	Collector-Emitter Sustaining Voltage	BD135	I_C = 30 mA, I_B = 0	45			V
		BD137		60			
		BD139		80			
I_{CBO}	Collector Cut-off Current		V_{CB} = 30 V, I_E = 0	–		0.1	μA
I_{EBO}	Emitter Cut-off Current		V_{EB} = 5 V, I_C = 0	–		10	μA
h_{FE1}	DC Current Gain		V_{CE} = 2 V, I_C = 5 mA	25			
h_{FE2}			V_{CE} = 2 V, I_C = 0.5 A	25			
h_{FE3}			V_{CE} = 2 V, I_C = 150 mA	40		250	
V_{CE}(sat)	Collector-Emitter Saturation Voltage		I_C = 500 mA, I_B = 50 mA			0.5	V
V_{BE}(on)	Base-Emitter On Voltage		V_{CE} = 2 V, I_C = 0.5 A			1	V

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. DC Current Gain




Figure 2. Collector-Emitter Saturation Voltage




Figure 3. Base-Emitter Voltage




Figure 4. Safe Operating Area




Figure 5. Power Derating

Share Feedback
Your Opinion Matters

ORDERING INFORMATION

Part Number	Marking	Package	Packing Method
BD13516STU	BD135-16	TO-126-3LD (Pb-Free)	Rail
BD13716STU	BD137-16		
BD13916STU	BD139-16		

DISCONTINUED (Note 1)

BD13516S	BD135-16	TO-126-3LD (Pb-Free)	Rail
BD1356STU	BD135-6		
BD13510STU	BD135-10		
BD13710STU	BD137-10		
BD13716S	BD137-16		Bulk
BD13910S	BD139-10		
BD13916S	BD139-16		
BD1396STU	BD139-6		Rail
BD13910STU	BD139-10		

1. **DISCONTINUED:** These devices are not available. Please contact your **onsemi** representative for information. The most current information on these devices may be available on www.onsemi.com.

Share Feedback
Your Opinion Matters

REVISION HISTORY


Revision	Description of Changes	Date
3	Document converted to **onsemi** format. Added Thermal Characteristics, removed h_{FE} Classification. BD13516S, BD1356STU, BD13510STU, BD13710STU, BD13716S, BD13910S, BD13916S, BD1396STU, BD13910STU OPNs marked as Discontinued.	4/28/2026

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.

Share Feedback
Your Opinion Matters


TO−126−3LD
CASE 340AS
ISSUE O

DATE 30 SEP 2016



TOP VIEW

SIDE VIEW



FRONT VIEW

PRODUCTION CODE	TERMINAL LENGTH "D"	TERMINAL LENGTH "E"
TSSTU	3.45 - 4.05	6.45 - 7.45
TSTU	2.36 - 2.96	5.36 - 6.36
NONE (STD LENGTH)	12.76 - 13.36	15.76 - 16.76

NOTES:

A. NO INDUSTRY STANDARD APPLIES TO THIS PACKAGE
B. ALL DIMENSIONS ARE IN MILLIMETERS
C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR PROTRUSIONS

△D FOR TERMINAL LENGTH "D", REFER TO TABLE

△E FOR TERMINAL LENGTH "E", REFER TO TABLE

DOCUMENT NUMBER:	**98AON13817G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**TO−126−3LD**		**PAGE 1 OF 1**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales