

PNP Silicon Epitaxial Transistor

PZT2907A



SOT−223
CASE 318E
STYLE 1


This PNP Silicon Epitaxial transistor is designed for use in linear and switching applications. The device is housed in the SOT-223 package which is designed for medium power surface mount applications.



Features

- NPN Complement is PZT2222AT1
- The SOT-223 Package can be Soldered Using Wave or Reflow
- SOT-223 Package Ensures Level Mounting, Resulting in Improved Thermal Conduction, and Allows Visual Inspection of Soldered Joints. The Formed Leads Absorb Thermal Stress during Soldering Eliminating the Possibility of Damage to the Die
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant*

MARKING DIAGRAM



P2F = Specific Device Code
A = Assembly Location
Y = Year
W = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector − Emitter Voltage	V_{CEO}	−60	Vdc
Collector − Base Voltage	V_{CBO}	−60	Vdc
Emitter − Base Voltage	V_{EBO}	−5.0	Vdc
Collector Current − Continuous	I_C	−600	mAdc

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation (Note 1) T_A = 25°C	P_D	1.5 12	W mW/°C
Thermal Resistance Junction−to−Ambient (Note 1)	$R_{\theta JA}$	83.3	°C/W
Lead Temperature for Soldering, 0.0625″ from case Time in Solder Bath	T_L	 260 10	 °C Sec
Operating and Storage Temperature Range	T_J, T_{stg}	−65 to +150	°C

1. FR−4 with 1 oz and 713 mm^2 of copper area.

ORDERING INFORMATION

Device	Package	Shipping†
PZT2907AT1G	SOT−223 (Pb−Free)	1,000 / Tape & Reel
SPZT2907AT1G	SOT−223 (Pb−Free)	1,000 / Tape & Reel
PZT2907AT3G	SOT−223 (Pb−Free)	4,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

© Semiconductor Components Industries, LLC, 2013

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector−Base Breakdown Voltage (I_C = −10 μAdc, I_E = 0)		$V_{(BR)CBO}$	−60	–	–	Vdc
Collector−Emitter Breakdown Voltage (I_C = 10 mAdc, I_B = 0)		$V_{(BR)CEO}$	−60	–	–	Vdc
Emitter−Base Breakdown Voltage (I_E = −10 μAdc, I_C = 0)		$V_{(BR)EBO}$	−5.0	–	–	Vdc
Collector−Base Cutoff Current (V_{CB} = −50 Vdc, I_E = 0)		I_{CBO}	–	–	−10	nAdc
Collector−Emitter Cutoff Current (V_{CE} = −30 Vdc, V_{BE} = 0.5 Vdc)		I_{CEX}	–	–	−50	nAdc
Base−Emitter Cutoff Current (V_{CE} = −30 Vdc, V_{BE} = −0.5 Vdc)		I_{BEX}	–	–	−50	nAdc
ON CHARACTERISTICS (Note 2)						
DC Current Gain (I_C = −0.1 mAdc, V_{CE} = −10 Vdc) (I_C = −1.0 mAdc, V_{CE} = −10 Vdc) (I_C = −10 mAdc, V_{CE} = −10 Vdc) (I_C = −150 mAdc, V_{CE} = −10 Vdc) (I_C = −500 mAdc, V_{CE} = −10 Vdc)		h_{FE}	 75 100 100 100 50	 – – – – –	 – – – 300 –	–
Collector-Emitter Saturation Voltages (I_C = −150 mAdc, I_B = −15 mAdc) (I_C = − 500 mAdc, I_B = −50 mAdc)		$V_{CE(sat)}$	 – –	 – –	 −0.4 −1.6	Vdc
Base-Emitter Saturation Voltages (I_C = −150 mAdc, I_B = −15 mAdc) (I_C = −500 mAdc, I_B = −50 mAdc)		$V_{BE(sat)}$	 – –	 – –	 −1.3 −2.6	Vdc
DYNAMIC CHARACTERISTICS						
Current-Gain − Bandwidth Product (I_C = −50 mAdc, V_{CE} = −20 Vdc, f = 100 MHz)		f_T	200	–	–	MHz
Output Capacitance (V_{CB} = −10 Vdc, I_E = 0, f = 1.0 MHz)		C_c	–	–	8.0	pF
Input Capacitance (V_{EB} = −2.0 Vdc, I_C = 0, f = 1.0 MHz)		C_e	–	–	30	pF
SWITCHING TIMES						
Turn-On Time	(V_{CC} = −30 Vdc, I_C = −150 mAdc, I_{B1} = −15 mAdc)	t_{on}	–	–	45	ns
Delay Time		t_d	–	–	10	
Rise Time		t_r	–	–	40	
Turn-Off Time	(V_{CC} = −6.0 Vdc, I_C = −150 mAdc, I_{B1} = I_{B2} = −15 mAdc)	t_{off}	–	–	100	ns
Storage Time		t_s	–	–	80	
Fall Time		t_f	–	–	30	

2. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

Share Feedback
Your Opinion Matters




Figure 1. Delay and Rise Time Test Circuit




Figure 2. Storage and Fall Time Test Circuit

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 3. DC Current Gain




Figure 4. Current Gain Bandwidth Product




Figure 5. "ON" Voltage




Figure 6. Capacitances

Share Feedback
Your Opinion Matters

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales