

Inverting Octal 3-STATE Buffer, Octal 3-STATE Buffer


MM74HC540, MM74HC541




SOIC−20 WB
CASE 751D−05



SOIC−20, 300 mils
CASE 751BJ



TSSOP−20 WB
CASE 948E



TSSOP−20, 4.4x6.5
CASE 948AQ

General Description

The MM74HC540 and MM74HC541 3−STATE buffers utilize advanced silicon−gate CMOS technology. They possess high drive current outputs which enable high speed operation even when driving large bus capacitances. These circuits achieve speeds comparable to low power Schottky devices, while retaining the advantage of CMOS circuitry, i.e., high noise immunity, and low power consumption. Both devices have a fanout of 15 LS−TTL equivalent inputs.

The MM74HC540 is an inverting buffer and the MM74HC541 is a non−inverting buffer. The 3−STATE control gate operates as a two−input NOR such that if either $\overline{G1}$ or $\overline{G2}$ are HIGH, all eight outputs are in the high−impedance state.


In order to enhance PC board layout, the MM74HC540 and MM74HC541 offers a pinout having inputs and outputs on opposite sides of the package. All inputs are protected from damage due to static discharge by diodes to V_{CC} and ground.

Features


- Typical Propagation Delay: 12 ns
- 3−STATE Outputs for Connection to System Buses
- Wide Power Supply Range: 2−6 V
- Low Quiescent Current: 160 μA Maximum (74HC Series)
- Output Current: 6 mA
- These are Pb−Free Devices

MARKING DIAGRAMS

SOIC−20



TSSOP−20




XXXXXX	= Specific Device Code
A	= Assembly Location
WL, L	= Wafer Lot Number
Y	= Year
WW, YW	= Work Week

ORDERING INFORMATION


See detailed ordering and shipping information on page 5 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 5.

© Semiconductor Components Industries, LLC, 1983



MM74HC540 (Top View)



MM74HC541 (Top View)

Figure 1. Connection Diagrams
(Pin Assignments for SOIC and TSSOP)

ABSOLUTE MAXIMUM RATINGS (Note 1)

Symbol	Rating	Value	Unit
V_{CC}	Supply Voltage	−0.5 to +6.5	V
V_{IN}	DC Input Voltage	−0.5 to V_{CC} +0.5	V
V_{OUT}	DC Output Voltage	−0.5 to V_{CC} +0.5	V
I_{CD}	Clamp Diode Current	±20	mA
I_{OUT}	DC Output Current, per pin	±35	mA
I_{CC}	DC V_{CC} or GND Current, per pin	±70	mA
T_{STG}	Storage Temperature Range	−65 to +150	°C
P_D	Power Dissipation SOIC TSSOP	1302 833	mW
T_L	Lead Temperature (Soldering 10 seconds)	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
1. Unless otherwise specified all voltages are referenced to ground.

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter		Min	Max	Unit
V_{CC}	Supply Voltage		2	6	V
V_{IN}, V_{OUT}	DC Input or Output Voltage		0	V_{CC}	V
T_A	Operating Temperature Range		−55	+125	°C
t_r, t_f	Input Rise or Fall Times	V_{CC} = 2.0 V	–	1000	ns
		V_{CC} = 4.5 V	–	500	ns
		V_{CC} = 6.0 V	–	400	ns

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

Share Feedback
Your Opinion Matters

DC ELECTRICAL CHARACTERISTICS (Note 2)

Symbol	Parameter	Conditions	V_{CC}	T_A = 25°C	T_A = −40 to 85°C	T_A = −55 to 125°C	Unit
				Typ	Guaranteed Limits		
V_{IH}	Minimum HIGH Level Input Voltage		2.0 V 4.5 V 6.0 V		1.5 3.15 4.2	1.5 3.15 4.2	1.5 3.15 4.2	V V V
V_{IL}	Maximum LOW Level Input Voltage		2.0 V 4.5 V 6.0 V		0.5 1.35 1.8	0.5 1.35 1.8	0.5 1.35 1.8	V V V
V_{OH}	Minimum HIGH Level Output Voltage	V_{IN} = V_{IH} or V_{IL} $\|I_{OUT}\| \le 20\ \mu A$	2.0 V 4.5 V 6.0 V	2.0 4.5 6.0	1.9 4.4 5.9	1.9 4.4 5.9	1.9 4.4 5.9	V V V
		V_{IN} = V_{IH} or V_{IL} $\|I_{OUT}\| \le 6.0$ mA $\|I_{OUT}\| \le 7.8$ mA	 4.5 V 6.0 V	 4.2 5.7	 3.98 5.48	 3.84 5.34	 3.7 5.2	V V
V_{OL}	Maximum LOW Level Output Voltage	V_{IN} = V_{IH} or V_{IL} $\|I_{OUT}\| \le 20\ \mu A$	2.0 V 4.5 V 6.0 V	0 0 0	0.1 0.1 0.1	0.1 0.1 0.1	0.1 0.1 0.1	V V V
		V_{IN} = V_{IH} or V_{IL} $\|I_{OUT}\| \le 6.0$ mA $\|I_{OUT}\| \le 7.8$ mA	 4.5 V 6.0 V	 0.2 0.2	 0.26 0.26	 0.33 0.33	 0.4 0.4	V V
I_{IN}	Maximum Input Current	V_{IN} = V_{CC} or GND	6.0 V		±0.1	±1.0	±1.0	μA
I_{OZ}	Maximum 3−STATE Output Leakage Current	V_{IN} = V_{IH} or V_{IL}, $\overline{G}$ = V_{IH} V_{OUT} = V_{CC} or GND	6.0 V		±0.5	±5	±10	μA
I_{CC}	Maximum Quiescent Supply Current	V_{IN} = V_{CC} or GND I_{OUT} = 0 μA	6.0 V		8.0	80	160	μA

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. For a power supply of 5 V ±10% the worst case output voltages (V_{OH}, and V_{OL}) occur for HC at 4.5 V. Thus the 4.5 V values should be used when designing with this supply. Worst case V_{IH} and V_{IL} occur at V_{CC} = 5.5 V and 4.5 V respectively. (The V_{IH} value at 5.5 V is 3.85 V.) The worst case leakage current (I_{IN}, I_{CC}, and I_{OZ}) occur for CMOS at the higher voltage and so the 6.0 V values should be used.

AC ELECTRICAL CHARACTERISTICS

(V_{CC} = 5 V, T_A = 25°C, t_r = t_f = 6 ns)

Symbol	Parameter	Conditions	Typ	Guaranteed Limit	Unit
t_{PHL}, t_{PLH}	Maximum Propagation Delay (540)	C_L = 45 pF	12	18	ns
t_{PHL}, t_{PLH}	Maximum Propagation Delay (541)	C_L = 45 pF	14	20	ns
t_{PZH}, t_{PZL}	Maximum Output Enable Time	R_L = 1 kΩ C_L = 45 pF	17	28	ns
t_{PHZ}, t_{PLZ}	Maximum Output Disable Time	R_L = 1 kΩ C_L = 5 pF	15	25	ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

AC ELECTRICAL CHARACTERISTICS

(V_{CC} = 2.0 V to 6.0. V, C_L = 50 pF, $t_r = t_f$ = 6 ns, unless otherwise specified)

Symbol	Parameter	Conditions	V_{CC}	T_A = 25°C	T_A = −40 to 85°C	T_A = −55 to 125°C	Unit
				Typ	Guaranteed Limits		
t_{PHL}, t_{PLH}	Maximum Propagation Delay (540)	C_L = 50 pF C_L = 150 pF	2.0 V 2.0 V	55 83	100 150	126 190	149 224	ns ns
		C_L = 50 pF C_L = 150 pF	4.5 V 4.5 V	12 22	20 30	25 38	30 45	ns ns
		C_L = 50 pF C_L = 150 pF	6.0 V 6.0 V	11 18	17 26	21 32	25 38	ns ns
t_{PHL}, t_{PLH}	Maximum Propagation Delay (541)	C_L = 50 pF C_L = 150 pF	2.0 V 2.0 V	58 83	115 165	145 208	171 246	ns ns
		C_L = 50 pF C_L = 150 pF	4.5 V 4.5 V	14 17	23 33	29 42	34 49	ns ns
		C_L = 50 pF C_L = 150 pF	6.0 V 6.0 V	11 14	20 28	25 35	29 42	ns ns
t_{PZH}, t_{PZL}	Maximum Output Enable Time	R_L = 1 kΩ C_L = 50 pF C_L = 150 pF	 2.0 V 4.5 V	 75 100	 150 200	 189 252	 224 298	 ns ns
		C_L = 50 pF C_L = 150 pF	4.5 V 4.5 V	15 30	30 40	38 50	45 60	ns ns
		C_L = 50 pF C_L = 150 pF	6.0 V 6.0 V	13 17	26 34	32 43	38 51	ns ns
t_{PHZ}, t_{PLZ}	Maximum Output Disable Time	R_L = 1 kΩ C_L = 50 pF	2.0 V 4.5 V 6.0 V	75 15 13	150 30 26	189 38 32	224 45 38	ns ns ns
t_{THL}, t_{TLH}	Maximum Output Rise and Fall Time	C_L = 50 pF	2.0 V 4.5 V 6.0 V	25 7 6	60 12 10	75 15 13	90 18 15	ns ns ns
C_{PD}	Power Dissipation Capacitance (Note 3)	$\overline{G}$ = V_{IH} $\overline{G}$ = V_{IL}		10 50				pF
C_{IN}	Maximum Input Capacitance			5	10	10	10	pF
C_{OUT}	Maximum Output Capacitance			15	20	20	20	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. C_{PD} determines the no load dynamic power consumption, $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$, and the no load dynamic current consumption, $I_S = C_{PD} V_{CC} f + I_{CC}$.

Share Feedback
Your Opinion Matters

ORDERING INFORMATION

Device	Marking	Package	Shipping†
MM74HC540WM	HC540A	SOIC−20 WB (Pb−Free and Halide Free)	38 Units / Tube
MM74HC540WMX	HC540A		1000 / Tape & Reel
MM74HC540MTCX	HC 540A	TSSOP−20 WB (Pb−Free)	2500 / Tape & Reel
MM74HC541WM	HC541A	SOIC−20 WB (Pb−Free and Halide Free)	38 Units / Tube
MM74HC541WMX	HC541A	SOIC−20, 300 mils (Pb−Free and Halide Free)	1000 / Tape & Reel
MM74HC541MTC	HC 541A	TSSOP−20 WB (Pb−Free)	75 Units / Tube
MM74HC541MTCX	HC 541A	TSSOP20, 4.4 × 6.5 (Pb−Free)	2500 / Tape & Reel

DISCONTINUED (Note 4)

MM74HC540MTC	HC 540A	TSSOP−20 WB (Pb−Free)	75 Units / Tube


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

4. **DISCONTINUED:** This device is not recommended for new design. Please contact your **onsemi** representative for information. The most current information on this device may be available on www.onsemi.com.

Share Feedback
Your Opinion Matters


SOIC−20, 300 mils
CASE 751BJ
ISSUE O

DATE 19 DEC 2008




TOP VIEW

SYMBOL	MIN	NOM	MAX
A	2.36	2.49	2.64
A1	0.10		0.30
A2	2.05		2.55
b	0.31	0.41	0.51
c	0.20	0.27	0.33
D	12.60	12.80	13.00
E	10.01	10.30	10.64
E1	7.40	7.50	7.60
e		1.27 BSC	
h	0.25		0.75
L	0.40	0.81	1.27
θ	0°		8°
θ1	5°		15°



SIDE VIEW



END VIEW


Notes:
(1) All dimensions are in millimeters. Angles in degrees.
(2) Complies with JEDEC MS-013.

DOCUMENT NUMBER:	98AON34287E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	SOIC−20, 300 MILS	PAGE 1 OF 1


onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

SOIC−20 WB
CASE 751D−05
ISSUE H

DATE 22 APR 2015




SCALE 1:1



NOTES:
1. DIMENSIONS ARE IN MILLIMETERS.
2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.
5. DIMENSION B DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.13 TOTAL IN EXCESS OF B DIMENSION AT MAXIMUM MATERIAL CONDITION.

	MILLIMETERS	
DIM	MIN	MAX
A	2.35	2.65
A1	0.10	0.25
b	0.35	0.49
c	0.23	0.32
D	12.65	12.95
E	7.40	7.60
e	1.27 BSC	
H	10.05	10.55
h	0.25	0.75
L	0.50	0.90
θ	0°	7°


RECOMMENDED SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
A = Assembly Location
WL = Wafer Lot
YY = Year
WW = Work Week
G = Pb−Free Package


*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98ASB42343B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**SOIC−20 WB**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.


TSSOP20, 4.4x6.5
CASE 948AQ
ISSUE A

DATE 19 MAR 2009




TOP VIEW

SYMBOL	MIN	NOM	MAX
A			1.20
A1	0.05		0.15
A2	0.80		1.05
b	0.19		0.30
c	0.09		0.20
D	6.40	6.50	6.60
E	6.30	6.40	6.50
E1	4.30	4.40	4.50
e		0.65 BSC	
L	0.45	0.60	0.75
L1		1.00 REF	
θ	0°		8°



SIDE VIEW



END VIEW

Notes:
(1) All dimensions are in millimeters. Angles in degrees.
(2) Complies with JEDEC MO-153.

DOCUMENT NUMBER:	98AON34453E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TSSOP20, 4.4X6.5	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2009

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales