High-Current Complementary Silicon Power Transistors

2N5684 (PNP), 2N5686 (NPN)

50 AMPERE COMPLEMENTARY SILICON POWER TRANSISTORS 60–80 VOLTS, 300 WATTS

These packages are designed for use in high−power amplifier and switching circuit applications.

Features

- High Current Capability − I_C Continuous = 50 Amperes
- DC Current Gain − h_{FE} = 15−60 @ I_C = 25 Adc
- Low Collector−Emitter Saturation Voltage − $V_{CE(sat)}$ = 1.0 Vdc (Max) @ I_C = 25 Adc
- Pb−Free Packages are Available*

MAXIMUM RATINGS (Note 1)

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	80	Vdc
Collector−Base Voltage	V_{CB}	80	Vdc
Emitter−Base Voltage	V_{EB}	5.0	Vdc
Collector Current − Continuous	I_C	50	Adc
Base Current	I_B	15	Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	300 1.715	mW mW/°C
Operating and Storage Temperature Range	T_J, T_{stg}	−65 to +200	°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	θ_{JC}	0.584	°C/W

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Indicates JEDEC Registered Data.





Figure 1. Power Derating

Safe Area Curves are indicated by Figure 5. All limits are applicable and must be observed.

MARKING DIAGRAM





TO−204 (TO−3)
CASE 197A
STYLE 1

2N568x	=	Device Code x = 4 or 6
G	=	Pb−Free Package
A	=	Location Code
YY	=	Year
WW	=	Work Week
MEX	=	Country of Orgin

ORDERING INFORMATION

Device	Package	Shipping
2N5684G	TO−3 (Pb−Free)	100 Units/Tray
2N5686	TO−3	100 Units/Tray
2N5686G	TO−3 (Pb−Free)	100 Units/Tray

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


© Semiconductor Components Industries, LLC, 2007

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted) (Note 2)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Sustaining Voltage (Note 3)	(I_C = 0.2 Adc, I_B = 0)	$V_{CEO(sus)}$	80	–	Vdc
Collector Cutoff Current	(V_{CE} = 40 Vdc, I_B = 0)	I_{CEO}	–	1.0	mAdc
Collector Cutoff Current	(V_{CE} = 80 Vdc, $V_{EB(off)}$ = 1.5 Vdc) (V_{CE} = 80 Vdc, $V_{EB(off)}$ = 1.5 Vdc, T_C = 150°C)	I_{CEX}	– –	2.0 10	mAdc
Collector Cutoff Current	(V_{CB} = 80 Vdc, I_E = 0)	I_{CBO}	–	2.0	mAdc
Emitter Cutoff Current	(V_{BE} = 5.0 Vdc, I_C = 0)	I_{EBO}	–	5.0	mAdc
ON CHARACTERISTICS					
DC Current Gain (Note 3)	(I_C = 25 Adc, V_{CE} = 2.0 Vdc) (I_C = 50 Adc, V_{CE} = 5.0 Vdc)	h_{FE}	15 5.0	60 –	–
Collector−Emitter Saturation Voltage (Note 3)	(I_C = 25 Adc, I_B = 2.5 Adc) (I_C = 50 Adc, I_B = 10 Adc)	$V_{CE(sat)}$	– –	1.0 5.0	Vdc
Base−Emitter Saturation Voltage (Note 2)	(I_C = 25 Adc, I_B = 2.5 Adc)	$V_{BE(sat)}$	–	2.0	Vdc
Base−Emitter On Voltage (Note 2)	(I_C = 25 Adc, V_{CE} = 2.0 Vdc)	$V_{BE(on)}$	–	2.0	Vdc
DYNAMIC CHARACTERISTICS					
Current−Gain − Bandwidth Product	(I_C = 5.0 Adc, V_{CE} = 10 Vdc, f = 1.0 MHz)	f_T	2.0	–	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 0.1 MHz)	2N5684 2N5686	C_{ob}	– –	2000 1200	pF
Small−Signal Current Gain	(I_C = 10 Adc, V_{CE} = 5.0 Vdc, f = 1.0 kHz)	h_{fe}	15	–	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Indicates JEDEC Registered Data.
3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.



FOR CURVES OF FIGURES 3 & 6, R_B & R_L ARE VARIED.
INPUT LEVELS ARE APPROXIMATELY AS SHOWN.
FOR NPN CIRCUITS, REVERSE ALL POLARITIES.

Figure 2. Switching Time Test Circuit




Figure 3. Turn−On Time

Share Feedback
Your Opinion Matters




Figure 4. Thermal Response




Figure 5. Active−Region Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 5 is based on $T_{J(pk)}$ = 200°C; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} \leq 200°C$. $T_{J(pk)}$ may be calculated from the data in Figure 4. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.




Figure 6. Turn−Off Time





Figure 7. Capacitance

Share Feedback
Your Opinion Matters

PNP
2N5684



NPN
2N5686





Figure 8. DC Current Gain







Figure 9. Collector Saturation Region







Figure 10. “On” Voltages


Share Feedback
Your Opinion Matters




SCALE 1:1

TO−204 (TO−3)
CASE 197A−05
ISSUE K

DATE 21 FEB 2000





NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	1.530 REF		38.86 REF	
B	0.990	1.050	25.15	26.67
C	0.250	0.335	6.35	8.51
D	0.057	0.063	1.45	1.60
E	0.060	0.070	1.53	1.77
G	0.430 BSC		10.92 BSC	
H	0.215 BSC		5.46 BSC	
K	0.440	0.480	11.18	12.19
L	0.665 BSC		16.89 BSC	
N	0.760	0.830	19.31	21.08
Q	0.151	0.165	3.84	4.19
U	1.187 BSC		30.15 BSC	
V	0.131	0.188	3.33	4.77


STYLE 1:
PIN 1. BASE
2. EMITTER
CASE: COLLECTOR

STYLE 2:
PIN 1. EMITTER
2. BASE
CASE: COLLECTOR

STYLE 3:
PIN 1. GATE
2. SOURCE
CASE: DRAIN

STYLE 4:
PIN 1. ANODE = 1
2. ANODE = 2
CASE: CATHODES

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
A = Assembly Locationa
YY = Year
WW = Work Week

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98ASB42129B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−204 (TO−3)**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales