Complementary Plastic Silicon Power Transistors


MJE170G, MJE171G, MJE172G (PNP), MJE180G, MJE181G, MJE182G (NPN)


3 AMPERES
POWER TRANSISTORS
COMPLEMENTARY SILICON
40 – 60 – 80 VOLTS
12.5 WATTS

The MJE170/180 series is designed for low power audio amplifier and low current, high speed switching applications.

Features

- High DC Current Gain
- High Current−Gain − Bandwidth Product
- Annular Construction for Low Leakages
- Epoxy Meets UL 94 V−0 @ 0.125 in
- These Devices are Pb−Free and are RoHS Compliant*






TO−225
CASE 77−09
STYLE 1

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Base Voltage MJE170G, MJE180G MJE171G, MJE181G MJE172G, MJE182G	V_{CB}	 60 80 100	Vdc
Collector−Emitter Voltage MJE170G, MJE180G MJE171G, MJE181G MJE172G, MJE182G	V_{CEO}	 40 60 80	Vdc
Emitter−Base Voltage	V_{EB}	7.0	Vdc
Collector Current − Continuous	I_C	3.0	Adc
Collector Current − Peak	I_{CM}	6.0	Adc
Base Current	I_B	1.0	Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	 12.5 0.012	 W W/°C
Total Power Dissipation @ T_A = 25°C Derate above 25°C	P_D	 1.5 0.1	 W W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +150	°C
ESD − Human Body Model	HBM	3B	V
ESD − Machine Model	MM	C	V

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

MARKING DIAGRAM



Y = Year
WW = Work Week
JE1xx = Specific Device Code
x = 70, 71, 72, 80, 81, or 82
G = Pb−Free Package

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

© Semiconductor Components Industries, LLC, 2013

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	10	°C/W
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	83.4	°C/W

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector−Emitter Sustaining Voltage (I_C = 10 mAdc, I_B = 0) MJE170G, MJE180G MJE171G, MJE181G MJE172G, MJE182G	$V_{CEO(sus)}$	 40 60 80	 − − −	Vdc
Collector Cutoff Current (V_{CB} = 60 Vdc, I_E = 0) MJE170G, MJE180G (V_{CB} = 80 Vdc, I_E = 0) MJE171G, MJE181G (V_{CB} = 100 Vdc, I_E = 0) MJE172G, MJE182G (V_{CB} = 60 Vdc, I_E = 0, T_C = 150°C) MJE170G, MJE180G (V_{CB} = 80 Vdc, I_E = 0, T_C = 150°C) MJE171G, MJE181G (V_{CB} = 100 Vdc, I_E = 0, T_C = 150°C) MJE172G, MJE182G	I_{CBO}	 − − − − −	 0.1 0.1 0.1 0.1 0.1	 μAdc mAdc
Emitter Cutoff Current (V_{BE} = 7.0 Vdc, I_C = 0)	I_{EBO}	 −	 0.1	μAdc
ON CHARACTERISTICS				
DC Current Gain (I_C = 100 mAdc, V_{CE} = 1.0 Vdc) (I_C = 500 mAdc, V_{CE} = 1.0 Vdc) (I_C = 1.5 Adc, V_{CE} = 1.0 Vdc)	h_{FE}	 50 30 12	 250 − −	−
Collector−Emitter Saturation Voltage (I_C = 500 mAdc, I_B = 50 mAdc) (I_C = 1.5 Adc, I_B = 150 mAdc) (I_C = 3.0 Adc, I_B = 600 mAdc)	$V_{CE(sat)}$	 − − −	 0.3 0.9 1.7	Vdc
Base−Emitter Saturation Voltage (I_C = 1.5 Adc, I_B = 150 mAdc) (I_C = 3.0 Adc, I_B = 600 mAdc)	$V_{BE(sat)}$	 − −	 1.5 2.0	Vdc
Base−Emitter On Voltage (I_C = 500 mAdc, V_{CE} = 1.0 Vdc)	$V_{BE(on)}$	 −	 1.2	Vdc
DYNAMIC CHARACTERISTICS				
Current−Gain − Bandwidth Product (Note 1) (I_C = 100 mAdc, V_{CE} = 10 Vdc, f_{test} = 10 MHz)	f_T	50	−	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 0.1 MHz) MJE171G/MJE172G MJE181G/MJE182G	C_{ob}	 − −	 60 40	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. $f_T = |h_{fe}| \bullet f_{test}$.

Share Feedback
Your Opinion Matters




Figure 1. Power Derating




Figure 2. Switching Time Test Circuit




Figure 3. Turn−On Time




Figure 4. Thermal Response

Share Feedback
Your Opinion Matters

ACTIVE−REGION SAFE OPERATING AREA




Figure 5. MJE171, MJE172




Figure 6. MJE181, MJE182

There are two limitations on the power handling ability of a transistor − average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figures 5 and 6 is based on $T_{J(pk)}$ = 150°C; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} < 150°C$. $T_{J(pk)}$ may be calculated from the data in Figure 4. At high case temperature, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.




Figure 7. Turn−Off Time





Figure 8. Capacitance

Share Feedback
Your Opinion Matters

ORDERING INFORMATION

Device	Package	Shipping
MJE170G	TO−225 (Pb−Free)	500 Units / Box
MJE171G	TO−225 (Pb−Free)	500 Units / Box
MJE172G	TO−225 (Pb−Free)	500 Units / Box
MJE180G	TO−225 (Pb−Free)	500 Units / Box
MJE181G	TO−225 (Pb−Free)	500 Units / Box
MJE182G	TO−225 (Pb−Free)	500 Units / Box

Share Feedback
Your Opinion Matters




FRONT VIEW **BACK VIEW**


TO−225
CASE 77−09
ISSUE AD

DATE 25 MAR 2015

SCALE 1:1



FRONT VIEW




SIDE VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. NUMBER AND SHAPE OF LUGS OPTIONAL.

	MILLIMETERS	
DIM	MIN	MAX
A	2.40	3.00
A1	1.00	1.50
b	0.60	0.90
b2	0.51	0.88
c	0.39	0.63
D	10.60	11.10
E	7.40	7.80
e	2.04	2.54
L	14.50	16.63
L1	1.27	2.54
P	2.90	3.30
Q	3.80	4.20

GENERIC MARKING DIAGRAM*



Y = Year
WW = Work Week
XXXXX = Device Code
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. EMITTER
2., 4. COLLECTOR
3. BASE

STYLE 2:
PIN 1. CATHODE
2., 4. ANODE
3. GATE

STYLE 3:
PIN 1. BASE
2., 4. COLLECTOR
3. EMITTER

STYLE 4:
PIN 1. ANODE 1
2., 4. ANODE 2
3. GATE

STYLE 5:
PIN 1. MT 1
2., 4. MT 2
3. GATE

STYLE 6:
PIN 1. CATHODE
2., 4. GATE
3. ANODE

STYLE 7:
PIN 1. MT 1
2., 4. GATE
3. MT 2

STYLE 8:
PIN 1. SOURCE
2., 4. GATE
3. DRAIN

STYLE 9:
PIN 1. GATE
2., 4. DRAIN
3. SOURCE

STYLE 10:
PIN 1. SOURCE
2., 4. DRAIN
3. GATE

DOCUMENT NUMBER:	**98ASB42049B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−225**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales