Plastic Medium Power Silicon PNP Transistor

BD436G, BD438G, BD440G, BD442G

This series of plastic, medium−power silicon PNP transistors can be used for for amplifier and switching applications. Complementary types are BD437 and BD441.

Features

- These Devices are Pb−Free and are RoHS Compliant*

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage BD436G BD438G BD440G BD442G	V_{CEO}	 32 45 60 80	Vdc
Collector−Base Voltage BD436G BD438G BD440G BD442G	V_{CBO}	 32 45 60 80	Vdc
Emitter−Base Voltage	V_{EBO}	5.0	Vdc
Collector Current	I_C	4.0	Adc
Base Current	I_B	1.0	Adc
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	 36 288	 W W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−55 to +150	°C


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	3.5	°C/W

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


4.0 AMP POWER TRANSISTORS PNP SILICON





TO−225
CASE 77−09
STYLE 1

MARKING DIAGRAM



Y = Year
WW = Work Week
BD4xx = Device Code
xx = 36, 36T, 38, 38T, 40, 42
G = Pb−Free Package

ORDERING INFORMATION

Device	Package	Shipping
BD442G	TO−225 (Pb−Free)	500 Units/Box

DISCONTINUED (Note 1)

BD436G	TO−225 (Pb−Free)	500 Units/Box
BD436TG		50 Units/Rail
BD438G		500 Units/Box
BD438TG		50 Units/Rail
BD440G		500 Units/Box

1. **DISCONTINUED:** These devices are not recommended for new design. Please contact your **onsemi** representative for information. The most current information on these devices may be available on www.onsemi.com.

© Semiconductor Components Industries, LLC, 2013

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
Collector−Emitter Breakdown Voltage (I_C = 100 mA, I_B = 0)	$V_{(BR)CEO}$				Vdc
BD436G		32	–	–	
BD438G		45	–	–	
BD440G		60	–	–	
BD442G		80	–	–	
Collector−Base Breakdown Voltage (I_C = 100 μA, I_B = 0)	$V_{(BR)CBO}$				Vdc
BD436G		32	–	–	
BD438G		45	–	–	
BD440G		60	–	–	
BD442G		80	–	–	
Emitter−Base Breakdown Voltage (I_E = 100 μA, I_C = 0)	$V_{(BR)EBO}$	5.0	–	–	Vdc
Collector Cutoff Current	I_{CBO}				mAdc
(V_{CB} = 32 V, I_E = 0) BD436G		–	–	0.1	
(V_{CB} = 45 V, I_E = 0) BD438G		–	–	0.1	
(V_{CB} = 60 V, I_E = 0) BD440G		–	–	0.1	
(V_{CB} = 80 V, I_E = 0) BD442G		–	–	0.1	
Emitter Cutoff Current (V_{EB} = 5.0 V)	I_{EBO}	–	–	1.0	mAdc
DC Current Gain (I_C = 10 mA, V_{CE} = 5.0 V)	h_{FE}				–
BD436G		40	–	–	
BD438G		30	–	–	
BD440G		20	–	–	
BD442G		15	–	–	
DC Current Gain (I_C = 500 mA, V_{CE} = 1.0 V)	h_{FE}				–
BD436G		85	–	475	
BD438G		85	–	475	
BD440G		40	–	475	
BD442G		40	–	475	
DC Current Gain (I_C = 2.0 A, V_{CE} = 1.0 V)	h_{FE}				–
BD436G		50	–	–	
BD438G		40	–	–	
BD440G		25	–	–	
BD442G		15	–	–	
Collector Saturation Voltage	$V_{CE(sat)}$				Vdc
(I_C = 2.0 A, I_B = 0.2 A) BD436G		–	–	0.5	
(I_C = 3.0 A, I_B = 0.3 A) BD438G		–	–	0.7	
BD440G		–	–	0.8	
BD442G		–	–	0.8	
Base−Emitter On Voltage (I_C = 2.0 A, V_{CE} = 1.0 V)	$V_{BE(ON)}$				Vdc
BD436G/BD438G		–	–	1.1	
BD440G/BD442G		–	–	1.5	
Current−Gain − Bandwidth Product (V_{CE} = 1.0 V, I_C = 250 mA, f = 1.0 MHz)	f_T	3.0	–	–	MHz

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters




Figure 1. Collector Saturation Region




Figure 2. Current Gain




Figure 3. “On” Voltage





Figure 4. Active Region Safe Operating Area

Share Feedback
Your Opinion Matters




FRONT VIEW **BACK VIEW**


TO−225
CASE 77−09
ISSUE AD

DATE 25 MAR 2015

SCALE 1:1



FRONT VIEW




SIDE VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. NUMBER AND SHAPE OF LUGS OPTIONAL.

	MILLIMETERS	
DIM	MIN	MAX
A	2.40	3.00
A1	1.00	1.50
b	0.60	0.90
b2	0.51	0.88
c	0.39	0.63
D	10.60	11.10
E	7.40	7.80
e	2.04	2.54
L	14.50	16.63
L1	1.27	2.54
P	2.90	3.30
Q	3.80	4.20

GENERIC MARKING DIAGRAM*



Y = Year
WW = Work Week
XXXXX = Device Code
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. EMITTER
2., 4. COLLECTOR
3. BASE

STYLE 2:
PIN 1. CATHODE
2., 4. ANODE
3. GATE

STYLE 3:
PIN 1. BASE
2., 4. COLLECTOR
3. EMITTER

STYLE 4:
PIN 1. ANODE 1
2., 4. ANODE 2
3. GATE

STYLE 5:
PIN 1. MT 1
2., 4. MT 2
3. GATE

STYLE 6:
PIN 1. CATHODE
2., 4. GATE
3. ANODE

STYLE 7:
PIN 1. MT 1
2., 4. GATE
3. MT 2

STYLE 8:
PIN 1. SOURCE
2., 4. GATE
3. DRAIN

STYLE 9:
PIN 1. GATE
2., 4. DRAIN
3. SOURCE

STYLE 10:
PIN 1. SOURCE
2., 4. DRAIN
3. GATE

DOCUMENT NUMBER:	**98ASB42049B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−225**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales