Complementary Silicon Power Plastic Transistors

MJE243G (NPN), MJE253G (PNP)

These devices are designed for low power audio amplifier and low−current, high−speed switching applications.

Features

- High Collector−Emitter Sustaining Voltage
- High DC Current Gain
- Low Collector−Emitter Saturation Voltage
- High Current Gain Bandwidth Product
- Annular Construction for Low Leakages
- These Devices are Pb−Free and are RoHS Compliant*

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	100	Vdc
Collector−Base Voltage	V_{CB}	100	Vdc
Emitter−Base Voltage	V_{EB}	7.0	Vdc
Collector Current − Continuous	I_C	4.0	Adc
Collector Current − Peak	I_{CM}	8.0	Adc
Base Current	I_B	1.0	Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	15 120	W mW/°C
Total Power Dissipation @ T_A = 25°C Derate above 25°C	P_D	1.5 12	W mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +150	°C


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	8.34	°C/W
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	83.4	°C/W

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


4.0 AMPERES POWER TRANSISTORS COMPLEMENTARY SILICON 100 VOLTS, 15 WATTS





TO−225
CASE 77−09
STYLE 1

MARKING DIAGRAM



Y = Year
WW = Work Week
JE2x3 = Device Code
x = 4 or 5
G = Pb−Free Package

ORDERING INFORMATION

Device	Package	Shipping
MJE243G	TO−225 (Pb−Free)	500 Units/Box
MJE253G	TO−225 (Pb−Free)	500 Units/Box

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2014

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector−Emitter Sustaining Voltage (I_C = 10 mAdc, I_B = 0)	$V_{CEO(sus)}$	100	–	V
Collector Cutoff Current (V_{CB} = 100 Vdc, I_E = 0) (V_{CE} = 100 Vdc, I_E = 0, T_C = 125°C)	I_{CBO}	– –	0.1 0.1	μA mA
Emitter Cutoff Current (V_{BE} = 7.0 Vdc, I_C = 0)	I_{EBO}	–	0.1	μAdc
ON CHARACTERISTICS				
DC Current Gain (I_C = 200 mAdc, V_{CE} = 1.0 Vdc) (I_C = 1.0 Adc, V_{CE} = 1.0 Vdc)	h_{FE}	40 15	180 –	–
Collector−Emitter Saturation Voltage (I_C = 500 mAdc, I_B = 50 mAdc) (I_C = 1.0 Adc, I_B = 100 mAdc)	$V_{CE(sat)}$	– –	0.3 0.6	V
Base−Emitter Saturation Voltage (I_C = 2.0 Adc, I_B = 200 mAdc)	$V_{BE(sat)}$	–	1.8	V
Base−Emitter On Voltage (I_C = 500 mAdc, V_{CE} = 1.0 Vdc)	$V_{BE(on)}$	–	1.5	V
DYNAMIC CHARACTERISTICS				
Current−Gain − Bandwidth Product (I_C = 100 mAdc, V_{CE} = 10 Vdc, f_{test} = 10 MHz)	f_T	40	–	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 0.1 MHz)	C_{ob}	–	50	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters




Figure 1. Power Derating




Figure 2. Switching Time Test Circuit




Figure 3. Turn−On Time




Figure 4. Thermal Response

Share Feedback
Your Opinion Matters




Figure 5. Active Region Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 5 is based on $T_{J(pk)}$ = 150°C; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} \leq 150°C$. $T_{J(pk)}$ may be calculated from the data in Figure 4. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.




Figure 6. Turn−Off Time





Figure 7. Capacitance

Share Feedback
Your Opinion Matters

NPN
MJE243



PNP
MJE253





Figure 8. DC Current Gain







Figure 9. “On” Voltages







Figure 10. Temperature Coefficients

Share Feedback
Your Opinion Matters




FRONT VIEW **BACK VIEW**


TO−225
CASE 77−09
ISSUE AD

DATE 25 MAR 2015

SCALE 1:1



FRONT VIEW




SIDE VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. NUMBER AND SHAPE OF LUGS OPTIONAL.

	MILLIMETERS	
DIM	MIN	MAX
A	2.40	3.00
A1	1.00	1.50
b	0.60	0.90
b2	0.51	0.88
c	0.39	0.63
D	10.60	11.10
E	7.40	7.80
e	2.04	2.54
L	14.50	16.63
L1	1.27	2.54
P	2.90	3.30
Q	3.80	4.20

GENERIC MARKING DIAGRAM*



Y = Year
WW = Work Week
XXXXX = Device Code
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. EMITTER
2., 4. COLLECTOR
3. BASE

STYLE 2:
PIN 1. CATHODE
2., 4. ANODE
3. GATE

STYLE 3:
PIN 1. BASE
2., 4. COLLECTOR
3. EMITTER

STYLE 4:
PIN 1. ANODE 1
2., 4. ANODE 2
3. GATE

STYLE 5:
PIN 1. MT 1
2., 4. MT 2
3. GATE

STYLE 6:
PIN 1. CATHODE
2., 4. GATE
3. ANODE

STYLE 7:
PIN 1. MT 1
2., 4. GATE
3. MT 2

STYLE 8:
PIN 1. SOURCE
2., 4. GATE
3. DRAIN

STYLE 9:
PIN 1. GATE
2., 4. DRAIN
3. SOURCE

STYLE 10:
PIN 1. SOURCE
2., 4. DRAIN
3. GATE

DOCUMENT NUMBER:	**98ASB42049B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−225**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales