DSK10B,DSK10C, DSK10E



1.0A Power Rectifier

http://onsemi.com

Features

· Designed for 5mm-pitch automatic insertion

• Small plastic molded structure (3mm body)

Peak reverse voltage: 100 to 400VAverage output current: 1.0A

Specifications

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	DSK10B	DSK10C	DSK10E	Unit
Peak Reverse Voltage	VRM		100	200	400	V
Average Recitifiedd Current	Io		1.0			А
Surge Forward Current	IFSM	50Hz sine wave, 1cycle	45			А
Junction Temperature	Tj		150			°C
Storage Temperature	Tstg		-40 to +150			°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	Offic
Forward Voltage	VF	I _F =1.0A			1.1	V
Reverse Current	IR	V _R :At each V _{RM}			10	μΑ

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Package Dimensions

unit:mm(typ.)





1 : Cathode 2 : Anode

Ordering Information

Device	Shipping	memo
DSK10B	500 Unit/Bag	
DSK10B-AT1	3,000 Unit/Box	
DSK10B-BT	3,000 Unit/Box	
DSK10C	500 Unit/Bag	
DSK10C-AT1	3,000 Unit/Box	
DSK10C-BT	3,000 Unit/Box	Pb-Free
DSK10C-ET1	3,000 Unit/Box	
DSK10E	500 Unit/Bag	
DSK10E-AT1	3,000 Unit/Box	
DSK10E-BT	3,000 Unit/Box	
DSK10E-ET1	3,000 Unit/Box	

DSK10B, DSK10C, DSK10E





ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equa