

MC74AC20, MC74ACT20

Dual 4-Input NAND Gate

- Outputs Source/Sink 24 mA
- 'ACT20 Has TTL Compatible Inputs




Figure 1. Pinout: 14-Lead Packages
(Top View)

PIN ASSIGNMENT

PIN	FUNCTION
A _n , B _n , C _n , D _n	Inputs
O _n	Outputs

MAXIMUM RATINGS*


Rating	Symbol	Value	Unit
DC Supply Voltage (Referenced to GND)	V _{CC}	-0.5 to +7.0	V
DC Input Voltage (Referenced to GND)	V _{in}	-0.5 to V _{CC} + 0.5	V
DC Output Voltage (Referenced to GND)	V _{out}	-0.5 to V _{CC} + 0.5	V
DC Input Current, per Pin	I _{in}	± 20	mA
DC Output Sink/Source Current, per Pin	I _{out}	± 50	mA
DC V _{CC} or GND Current per Output Pin	I _{CC}	± 50	mA
Storage Temperature	T _{stg}	-65 to +150	°C

*Maximum Ratings are those values beyond which damage to the device may occur. Functional operation should be restricted to the Recommended Operating Conditions.




ON Semiconductor™

<http://onsemi.com>




PDIP-14
N SUFFIX
CASE 646



SO-14
D SUFFIX
CASE 751A



TSSOP-14
DT SUFFIX
CASE 948G



EIAJ-14
M SUFFIX
CASE 965

ORDERING INFORMATION

Device	Package	Shipping
MC74AC20N	PDIP-14	25 Units/Rail
MC74ACT20N	PDIP-14	25 Units/Rail
MC74AC20D	SOIC-14	55 Units/Rail
MC74AC20DR2	SOIC-14	2500 Tape & Reel
MC74ACT20D	SOIC-14	55 Units/Rail
MC74ACT20DR2	SOIC-14	2500 Tape & Reel
MC74AC20DT	TSSOP-14	96 Units/Rail
MC74AC20DTR2	TSSOP-14	2500 Tape & Reel
MC74ACT20DT	TSSOP-14	96 Units/Rail
MC74ACT20DTR2	TSSOP-14	2500 Tape & Reel
MC74AC20M	EIAJ-14	50 Units/Rail
MC74AC20MEL	EIAJ-14	2000 Tape & Reel
MC74ACT20M	EIAJ-14	50 Units/Rail
MC74ACT20MEL	EIAJ-14	2000 Tape & Reel

DEVICE MARKING INFORMATION

See general marking information in the device marking section on page 88 of this data sheet.

MC74AC20, MC74ACT20

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter		Min	Typ	Min	Unit
V _{CC}	Supply Voltage	'AC	2.0	5.0	6.0	V
		'ACT	4.5	5.0	5.5	
V _{REG}	DC Regulated Power Voltage (Ref. to GND)		0	—	V _{CC}	V
t _r , t _f	Input Rise and Fall Time (Note 1) 'AC Devices except Schmitt Inputs	V _{CC} @ 3.0 V	—	150	—	ns/V
		V _{CC} @ 4.5 V	—	40	—	
		V _{CC} @ 5.5 V	—	25	—	
t _r , t _f	Input Rise and Fall Time (Note 2) 'ACT Devices except Schmitt Inputs	V _{CC} @ 4.5 V	—	10	—	ns/V
		V _{CC} @ 5.5 V	—	8.0	—	
T _J	Junction Temperature (PDIP)		—	—	140	°C
T _A	Operating Ambient Temperature Range		-40	25	85	°C
I _{OH}	Output Current – HIGH		—	—	-24	mA
I _{OL}	Output Current – LOW		—	—	24	mA

1. V_{IN} from 30% to 70% V_{CC}; see individual Data Sheets for devices that differ from the typical input rise and fall times.
 2. V_{IN} from 0.8 V to 2.0 V; see individual Data Sheets for devices that differ from the typical input rise and fall times.

DC CHARACTERISTICS

Symbol	Parameter	V _{CC} (V)	74AC		Unit	Conditions		
			T _A = +25°C					
			Typ	Guaranteed Limits				
V _{IH}	Minimum High Level Input Voltage	3.0 4.5 5.5	1.5 2.25 2.75	2.1 3.15 3.85	V	V _{OUT} = 0.1 V or V _{CC} – 0.1 V		
V _{IL}	Maximum Low Level Input Voltage	3.0 4.5 5.5	1.5 2.25 2.75	0.9 1.35 1.65	V	V _{OUT} = 0.1 V or V _{CC} – 0.1 V		
V _{OH}	Minimum Low Level Output Voltage	3.0 4.5 5.5	2.99 4.49 5.49	2.9 4.4 5.4	V	I _{OUT} = -50 μA		
		3.0 4.5 5.5	— — —	2.56 3.86 4.86	V	*V _{IN} = V _{IL} or V _{IH} – 12 mA I _{OH} – 24 mA – 24 mA		
V _{OL}	Maximum Low Level Output Voltage	3.0 4.5 5.5	0.002 0.001 0.001	0.1 0.1 0.1	V	I _{OUT} = 50 μA		
		3.0 4.5 5.5	— — —	0.36 0.36 0.36	V	*V _{IN} = V _{IL} or V _{IH} 12 mA I _{OL} 24 mA 24 mA		
I _{IN}	Maximum Input Leakage Current	5.5	—	±0.1	±1.0	μA		
I _{OLD}	†Minimum Dynamic Output Current	5.5	—	—	75	mA		
I _{OHD}		5.5	—	—	-75	mA		
I _{CC}	Maximum Quiescent Supply Current	5.5	—	4.0	40	μA		

*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

NOTE: I_{IN} and I_{CC} @ 3.0 V are guaranteed to be less than or equal to the respective limit @ 5.5 V.

MC74AC20, MC74ACT20

AC CHARACTERISTICS

Symbol	Parameter	V_{CC}^* (V)	74AC			74AC		Unit	
			$T_A = +25^\circ C$ $C_L = 50 \text{ pF}$			$T_A = -40^\circ C$ to $+85^\circ C$ $C_L = 50 \text{ pF}$			
			Min	Typ	Max	Min	Max		
t_{PLH}	Propagation Delay	3.3 5.0	2.0 1.5	6.0 5.0	8.5 7.0	1.5 1.0	10.0 8.0	ns	
t_{PHL}	Propagation Delay	3.3 5.0	1.5 1.5	5.0 4.0	7.0 6.0	1.0 1.0	9.0 7.0	ns	

*Voltage Range 3.3 V is $3.3 \text{ V} \pm 0.3 \text{ V}$.
Voltage Range 5.0 V is $5.0 \text{ V} \pm 0.5 \text{ V}$.

DC CHARACTERISTICS

Symbol	Parameter	V_{CC} (V)	74ACT		74ACT		Unit	Conditions		
			$T_A = +25^\circ C$		$T_A = -40^\circ C$ to $+85^\circ C$					
			Typ	Guaranteed Limits	Typ	Guaranteed Limits				
V_{IH}	Minimum High Level Input Voltage	4.5 5.5	1.5 1.5	2.0 2.0	2.0 2.0		V	$V_{OUT} = 0.1 \text{ V}$ or $V_{CC} - 0.1 \text{ V}$		
V_{IL}	Maximum Low Level Input Voltage	4.5 5.5	1.5 1.5	0.8 0.8	0.8 0.8		V	$V_{OUT} = 0.1 \text{ V}$ or $V_{CC} - 0.1 \text{ V}$		
V_{OH}	Minimum High Level Output Voltage	4.5 5.5	4.49 5.49	4.4 5.4	4.4 5.4		V	$I_{OUT} = -50 \mu\text{A}$		
		4.5 5.5	— —	3.86 4.86	3.76 4.76		V	$*V_{IN} = V_{IL} \text{ or } V_{IH}$ $I_{OH} = -24 \text{ mA}$		
V_{OL}	Maximum Low Level Output Voltage	4.5 5.5	0.001 0.001	0.1 0.1	0.1 0.1		V	$I_{OUT} = 50 \mu\text{A}$		
		4.5 5.5	— —	0.36 0.36	0.44 0.44		V	$*V_{IN} = V_{IL} \text{ or } V_{IH}$ $I_{OH} = 24 \text{ mA}$		
I_{IN}	Maximum Input Leakage Current	5.5	—	± 0.1	± 1.0		μA	$V_I = V_{CC}, \text{ GND}$		
ΔI_{CCT}	Additional Max. I_{CC} /Input	5.5	0.6	—	1.5	mA		$V_I = V_{CC} - 2.1 \text{ V}$		
I_{OLD}	†Minimum Dynamic Output Current	5.5	—	—	75	mA		$V_{OLD} = 1.65 \text{ V Max}$		
		5.5	—	—	-75	mA		$V_{OHD} = 3.85 \text{ V Min}$		
I_{CC}	Maximum Quiescent Supply Current	5.5	—	4.0	40	μA		$V_{IN} = V_{CC} \text{ or } \text{GND}$		

*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

MC74AC20, MC74ACT20

AC CHARACTERISTICS

Symbol	Parameter	V _{CC} [*] (V)	74ACT			74ACT		Unit	
			T _A = +25°C C _L = 50 pF			T _A = -40°C to +85°C C _L = 50 pF			
			Min	Typ	Max	Min	Max		
t _{PLH}	Propagation Delay	5.0	2.0	6.5	9.0	1.5	10.5	ns	
t _{PHL}	Propagation Delay	5.0	2.0	5.5	9.0	1.5	10.5	ns	







*Voltage Range 5.0 V is 5.0 V ±0.5 V.

CAPACITANCE

Symbol	Parameter	Value Typ	Unit	Test Conditions
C _{IN}	Input Capacitance	4.5	pF	V _{CC} = 5.0 V
C _{PD}	Power Dissipation Capacitance	40	pF	V _{CC} = 5.0 V

MC74AC20, MC74ACT20

MARKING DIAGRAMS



A = Assembly Location

WL, L = Wafer Lot

YY, Y = Year

WW, W = Work Week