



ON Semiconductor®

<http://onsemi.com>

SFT1458

N-Channel Power MOSFET 600V, 1.0A, 13Ω, Single TP/TP-FA

Features

- On-resistance $R_{DS(on)}=10\Omega$ (typ.)
- Input Capacitance $C_{iss}=65pF$ (typ.)
- Protection Diode in
- 10V drive
- Halogen free compliance

Specifications

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Ratings	Unit
Drain to Source Voltage	V_{DSS}		600	V
Gate to Source Voltage	V_{GSS}		± 30	V
Drain Current (DC)	I_D		1	A
Drain Current (Pulse)	I_{DP}	$PW \leq 10\mu s$, duty cycle $\leq 1\%$	4	A
Allowable Power Dissipation	P_D		1	W
		$T_c=25^\circ\text{C}$	38	W
Channel Temperature	T_{ch}		150	$^\circ\text{C}$
Storage Temperature	T_{stg}		-55 to +150	$^\circ\text{C}$

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.









Electrical Characteristics at $T_a = 25^\circ\text{C}$





Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=10\text{mA}$, $V_{GS}=0\text{V}$	600			V
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS}=480\text{V}$, $V_{GS}=0\text{V}$			100	μA
Gate to Source Leakage Current	I_{GSS}	$V_{GS}=\pm 24\text{V}$, $V_{DS}=0\text{V}$			± 10	μA
Cutoff Voltage	$V_{GS(off)}$	$V_{DS}=10\text{V}$, $I_D=1\text{mA}$	3.5		4.5	V
Forward Transfer Admittance	$ y_{fs} $	$V_{DS}=10\text{V}$, $I_D=0.5\text{A}$		0.57		S
Static Drain to Source On-State Resistance	$R_{DS(on)}$	$I_D=0.5\text{A}$, $V_{GS}=10\text{V}$		10	13	Ω
Input Capacitance	C_{iss}	$V_{DS}=20\text{V}$, $f=1\text{MHz}$		65		pF
Output Capacitance	C_{oss}			20		pF
Reverse Transfer Capacitance	C_{rss}			4.5		pF
Turn-ON Delay Time	$t_{d(on)}$				6	ns
Rise Time	t_r	See specified Test Circuit.		11		ns
Turn-OFF Delay Time	$t_{d(off)}$				12	ns
Fall Time	t_f				60	ns
Total Gate Charge	Q_g	$V_{DS}=200\text{V}$, $V_{GS}=10\text{V}$, $I_D=1\text{A}$		3.8		nC
Gate to Source Charge	Q_{gs}			0.54		nC
Gate to Drain "Miller" Charge	Q_{gd}			2.3		nC
Diode Forward Voltage	V_{SD}	$I_S=1\text{A}$, $V_{GS}=0\text{V}$		0.93	1.2	V

ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.

SFT1458





SFT1458

Package Dimensions

SFT1458-H

IPAK/TP

CASE 369AL

ISSUE O


Unit : mm

1: Gate

2: Drain

3: Source

4: Drain



Package Dimensions

SFT1458-TL-H

DKPAK/TP-FA

CASE 369AH

ISSUE O


Unit : mm

1: Gate

2: Drain

3: Source

4: Drain



Pin 2 is idle pin with electrical designation only carried.


*1: Lot indication

SFT1458


Ordering & Package Information

Device	Package	Shipping	note
SFT1458-H	TP SC-64, TO-251, SOT-553, DPAK	500 pcs. / bag	Pb-Free And Halogen Free
SFT1458-TL-H	TP-FA SC-63, TO-252, SOT-428, DPAK	700 pcs. / reel	


Packing Type: TL




Marking



Electrical Connection



Switching Time Test Circuit



Note on usage : Since the SFT1458 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.