


Wireless Connectivity

Product Leaflet

Panasonic

							
Series	PAN1315B/PAN1325B	PAN1316C/PAN1326C	PAN1026A	PAN1760	PAN1761	PAN1720 / PAN1721	PAN1740
Status	Mass Production	Mass Production	Pre-Production	Mass Production	Mass Production	Mass Production	Mass Production
Part Number	ENW89829x3KF*	ENW89823x4KF*	ENW89837A5KF	ENW89847A1KF	ENW89848A1KF	ENW898xxxxKF*	ENW89846A1KF
RF Category	Bluetooth® BR/EDR Bluetooth® v2.1 + EDR class 1.5	Bluetooth® Dual Mode Bluetooth® v4.2 class 1.5	Bluetooth® Dual Mode Bluetooth® v4.2 class 2	Bluetooth® Low Energy Bluetooth® v4.1	Bluetooth® Low Energy Bluetooth® v4.1 + NFC Tag Type 3	Bluetooth® Low Energy Bluetooth® v4.0	Bluetooth® Low Energy Bluetooth® v4.2
Software / Profile	HCI	HCI	SPP and GATT	Embedded Profiles	Embedded Profiles	nBlue™ by BlueRadios Inc. / TI SW stack	Embedded Profiles
Used ICs	CC2560B	CC2564C	TC35661-551	TC35667-006	TC35670-006	CC2540 / CC2541	DA14580
Size [mm]	w/o antenna w/ antenna	9.0 x 6.5 x 1.8 9.0 x 9.5 x 1.8	15.6 x 8.7 x 1.8	15.6 x 8.7 x 1.8	15.6 x 8.7 x 1.8 (NFC antenna pin)	15.6 x 8.7 x 1.8	9.0 x 9.5 x 1.8
Rx Sensitivity [dBm]	-93	-93	-89	-91	-90	-94	-93
Tx Power (max.) [dBm]	+10	+10	+4	+0	+0	+4 / 0	+0
Power Supply [V]	1.8 to 4.8	1.8 to 4.8	2.8 to 3.6	1.8 to 3.6	1.8 to 3.6	2.0 to 3.6	2.35 to 3.3
Current Consumption (max.)	Tx, EDR: 40mA Sleep Mode: 135µA	Tx, EDR: 40mA Sleep Mode: 135µA	ACL, DH1: 46mA Sleep Mode: <2mA	Tx 5.4mA Rx: 5.4mA Sleep Mode: <1µA	Tx: 5.5mA Rx: 5.5mA Sleep Mode: <0.1µA	Tx: 23mA @ -6dBm Rx: 18mA Sleep Mode: <1µA	Tx: 4.9mA Rx: 4.9mA Sleep Mode: <1µA
Interfaces	GPIO, PCM, UART	GPIO, PCM, UART	GPIO, UART	GPIO, UART, SPI, I²C, ADC	GPIO, UART, I²C, NFC Wake-Up, etc.	GPIO, UART, USB only PAN17x0* Series	GPIO, UART, SPI, I²C, 3-axis QD, ADC
Microcontroller and Memory			ARM 7	ARM 7, 32KB on-chip RAM, 64KB EEPROM	ARM 7, 32KB on-chip RAM, 64KB EEPROM, 1.5KB EEPROM NFC memory	8051 µC, 8KB RAM, 256KB Flash	ARM Cortex M0, 32KB OTP, 42KB SRAM / external non-volatile memory
Specialty			Compatible to Toshiba Bluetooth SDK for BLE-GATT			two internal crystal	two internal crystal
Compatibility	All CC256xx* based Bluetooth modules are footprint- and pin-compatible		All TC356xx based modules are footprint- and pin-compatible			PAN172x* Series is footprint compatible with PAN1026A, PAN1760 and PAN1761	
Operating Temp. [°C]	-40 to +85	-40 to +85	-40 to +85	-40 to +85	-30 to +85	-40 to +85	-40 to +85
Evaluation Kit	EVAL_PAN1323 (EMK)	EVAL_PAN1323 (EMK)	ENW89837AxKF* (EMK)	ENW89847AVKF (EMK) ENW89847AUKF (Morpheus Board)	ENW89848AVKF (EMK)	ENW898xxAY2F* (BR KIT) ENW898xxAY1F* (TI KIT)	ENW89846AYKF (KIT) ENW89846AVKF (EMK)

Panasonic Automotive & Industrial Systems Europe GmbH
<http://eu.industrial.panasonic.com>

Status of engineering sample (ES) are expected as of the time of leaflet production. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Panasonic is under license. Other trademarks and trade names are those of their respective owners.


* x is a parameter to be defined.

- Design and specification are subject to change without notice.
- Ask Panasonic for technical specification before purchase and/or use.
- If there is any doubt regarding the safety of this product, kindly inform Panasonic immediately for technical consultation.
- Qualification of all products: CE, FCC, IC, Bluetooth® QDID if applicable.
- Different software/profile options available.

Wireless Connectivity

Product Leaflet

Panasonic

						
Series	PAN2355/PAN2357	PAN4561H	PAN9310/PAN9320	PAN9010/PAN9020	PAN9026	PAN9045/PAN9055
Status	Mass Production	Mass Production	Mass Production	Mass Production	Pre-Production	Pre-Production
Part Number	ENW5961xN3xx*	ENWC9A22xxEF*	ENW49A02x3EF (EU) ENW49A01x3EF (FCC)	ENW49801x1JF* (USB) ENW49802x1JF* (SDIO)	ENWF9201A1EF* (SDIO)	ENWF9101x1JF* (commercial grade) ENWF9101x1EF* (extended grade)
RF Category	ISM Transceiver	Mesh Networking (ZigBee® ready)	Wi-Fi Embedded 802.11 b/g/n	Wi-Fi Radio 802.11 b/g/n	Combo Radio Wi-Fi 802.11 a/b/g/n (2.4 GHz & 5.0 GHz) + Bluetooth® Dual Mode BLE v4.2 class 1	Combo Radio Wi-Fi 802.11 b/g/n (2.4 GHz) (MIMO 2x2) + Bluetooth® Dual Mode BLE v4.0 class 1
Software / Profile	n/a	SNAP® by Synapse Wireless Inc.	Full Embedded	Linux / Android Driver	Linux / Android Driver	Linux / Android Driver
Used ICs	CC1101	MC13213 + CC2591	88MC200 + 88W8782	88W8782	88W8977	88W8797
Size [mm]	8.0 x 8.2 x 1.9	35.0 x 15.0 x 3.8	29.0 x 13.5 x 2.66	22.75 x 13.5 x 2.42	17.5 x 10.0 x 2.6	26.0 x 13.5 x 2.4
Antenna Options	w/o antenna	w/ ceramic antenna or U.FL connector or bottom pad	w/ 50 Ohm bottom pad / w/ antenna	w/ 50 Ohm bottom pad / w/ antenna	w/ antenna	w/o antenna / w/ two antennas
Rx Sensitivity [dBm]	-112 @ 1.2k GFSK -104 @ 38.4k GFSK -95 @ 250k GFSK -89 @ 500k 4FSK	-98 @ 250 kbps	-98 @ 1M-DSSS -88 @ 11M-CCK -93 @ 6M-BPSK -76 @ 54M-OFDM -74 @ 65M-MCS7	-98 @ 1M-DSSS -88 @ 11M-CCK -93 @ 6M-BPSK -76 @ 54M-OFDM -74 @ 65M-MCS7	-98 @ 1M-DSSS -89 @ 11M-CCK -91 @ 6M-BPSK -76 @ 54M-OFDM -73 @ 65M-MCS7	-98 @ 1M-DSSS -88 @ 11M-CCK -93 @ 6M-BPSK -76 @ 54M-OFDM -74 @ 65M-MCS7
Tx Power (max.) [dBm]	+10	+18.5	+18 @ 11b	+18 @ 11b	+17 @ 11b	+18 @ 11b
Power Supply [V]	1.8 to 3.6	2.7 to 3.4	3.0 to 3.6	3.0 to 3.6	1.8 to 3.3	3.0 to 3.6
Current Consumption (max.)	Tx: 36 mA Rx: 18 mA Sleep Mode: <1 µA	Tx: 210 mA Rx: 48 mA Off Mode: 2 µA	Tx: 430mA @ 11Mbps Rx: 150mA @ 11Mbps Off Mode: 27mA	Tx: 400mA @ 11Mbps Rx: 105mA @ 11Mbps Power Down: 200µA	Tx: 490mA @ 11Mbps Rx: 70mA @ 11Mbps Power Down: tbd	Tx: 580mA @ 300Mbps Rx: 310mA @ 300Mbps Sleep Mode: tbd
Interfaces	GPIO, SPI	GPIO, UART, I2C	2 x UART	USB 2.0 or SDIO	SDIO 3.0, HS UART	USB 2.0, SDIO 3.0, HS UART
Microcontroller and Memory			ARM Cortex M3 1MB Flash			
Specialty			Coexistence Interface for external co-located 2.4 GHz Radios		Coexistence interface for arbitration of co-located WLAN, Bluetooth or Mobile Wireless System (e.g. LTE)	Coexistence with cellular and other 2.4 GHz on-chip Radios
Compatibility						
Operating Temp. [°C]	-40 to +85	-40 to +85	-30 to +70	0 to +70	-30 to +85	0 to +70 (commercial grade) -30 to +85 (extended grade)
Evaluation Kit	n/a	PAN4561Hx*-ETU + RF Module USB Adapter	ENW49A01AYEF (EMK)	ENW49802AYJF (KIT)	ENWF9201AZEF (ETU) ENWF9201AYEF (KIT)	ENWF9101AYEF (KIT)