

## Multiple relay module - EMUG 45- 4REL/KSR-G 24/21 - 2943767


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Relay module, multi-channel, with 4 soldered-in miniature switching relays for DC voltage with light indicator and 1 PDT each, contact for medium to large loads, input voltage 24 V DC



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 081317
Weight per Piece (excluding packing)	137.48 GRM
Custom tariff number	85364190
Country of origin	Germany

### Technical data

#### Dimensions

Width	45 mm
Height	60 mm
Depth	79 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 55 °C
---------------------------------	------------------

#### Coil side

Nominal input voltage $U_N$	24 V DC
Input voltage range in reference to $U_N$	0.8 ... 1.1
Typical input current at $U_N$	21 mA
Typical response time	7 ms
Typical release time	11 ms
Operating voltage display	Yes

## Multiple relay module - EMUG 45- 4REL/KSR-G 24/21 - 2943767

### Technical data

#### Coil side

Protective circuit	Damping diode, polarity protection Damping diode, polarity protection diode
--------------------	---

#### Contact side

Contact type	Single contact, 1-PDT
Contact material	AgNi
Maximum switching voltage	250 V AC/DC
Maximum inrush current	8 A
Limiting continuous current	6 A
Interrupting rating (ohmic load) max.	95 W (at 24 V DC)
	50 W (at 48 V DC)
	45 W (at 60 V DC)
	35 W (at 110 V DC)
	55 W (at 220 V DC)
	1500 VA (for 250 V AC)

#### General

Test voltage relay winding/relay contact	2.5 kV AC (50 Hz, 1 min.)
Operating mode	100% operating factor
Mechanical service life	Approx. $2 \times 10^7$ cycles
Standards/regulations	IEC 60664
	IEC 60664 A
	DIN VDE 0110
	DIN VDE 0109-11, draft
	DIN EN 50178/VDE 0160
	IEC 60255/DIN VDE 0435 (in relevant parts)
Pollution degree	2
Surge voltage category	III
Mounting position	any
Assembly instructions	In rows with zero spacing

#### Connection data

Connection method	Screw/plug-in connection
-------------------	--------------------------

### Classifications

#### eCl@ss

eCl@ss 4.0	27371102
eCl@ss 4.1	27371102

## Multiple relay module - EMUG 45- 4REL/KSR-G 24/21 - 2943767

### Classifications

#### eCl@ss

eCl@ss 5.0	27371001
eCl@ss 5.1	27371001
eCl@ss 6.0	27371001
eCl@ss 7.0	27371001
eCl@ss 8.0	27371001

#### ETIM

ETIM 2.0	EC000196
ETIM 3.0	EC000196
ETIM 4.0	EC000196
ETIM 5.0	EC000196

#### UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121543
UNSPSC 11	39121543
UNSPSC 12.01	39121543
UNSPSC 13.2	39121543

### Accessories

#### Accessories

Marking material - EMG-GKS 12 - 2947035



Equipment marker, width 12 mm

---

Connector set - MSTB-SET/EMUG 45- 4REL - 1780248

COMBICON connection plug set, with plug-in direction parallel to conductor axis

---

Connector set - MSTBP-SET/EMUG 45- 4REL - 1780277

COMBICON connection plug set, with plug-in direction parallel to conductor axis, with an additional test connection for a 2.0 or 2.3 mm  $\varnothing$  test plug

## Multiple relay module - EMUG 45- 4REL/KSR-G 24/21 - 2943767

### Accessories

---

Connector set - MVSTBR-SET/EMUG 45- 4REL - 1780303

COMBICON connection plug set, with plug-in direction vertical to conductor axis

---

Connector set - FRONT-MSTB-SET/EMUG 45- 4REL - 1780332

COMBICON connection plug set, with front screw connection and plug-in direction parallel to conductor axis

---

### Drawings

# Multiple relay module - EMUG 45- 4REL/KSR-G 24/21 - 2943767

Circuit diagram

