

## Cable marker - US-WMTB (44X15) - 0828773

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Cable marker, Card, white, unlabeled, can be labeled with: THERMOMARK CARD, Mounting type: Thread on, Cable diameter: >4 mm, Lettering field: 44 x 15 mm



### Product Features

- The markers, which are supplied in uniform sheets, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- The US-WMTB... UniSheet labeling range includes markers that can be secured using standard cable binders
- The perforated marking strips are easy to separate and can be easily fitted
- The sheets provide space for including function texts



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 10 pc    |
| Weight per Piece (excluding packing) | 14.0 GRM |
| Custom tariff number                 | 39204910 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 60 mm |
| Width (a)  | 15 mm |

#### Ambient conditions

|                                 |  |
|---------------------------------|--|
| Ambient temperature (operation) | -30 °C ... 80 °C   |
| Recommended storage conditions  | 10-30 °C / 40-70 % relative humidity. Storage in poly bags is recommended prior to processing. |

#### General

|            |               |
|------------|---------------|
| Color      | white         |
| Components | Silicone-free |

## Cable marker - US-WMTB (44X15) - 0828773

### Technical data

#### General

|   |                                     |
|---|-------------------------------------|
| Inflammability class according to UL 94                             | V0                                  |
| Material  | PVC                                 |
| Wipe resistance   | DIN EN 61010-1 (VDE 0411-1)         |
| Number of individual labels   | 12                                  |
| Number of individual labels per row                                 | 6                                   |
| Printability  | Thermal transfer                    |
| Device  | 5146464 THERMOMARK CARD             |
| Ink ribbon  | 5146451 THERMOMARK CARD-US-MAG1     |
|   | 0801371 THERMOMARK-RIBBON 110-TC    |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                |
| Result  | Test passed                         |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03        |
| Test duration   | 96 h                                |
| Wipe resistance test result   | Test passed                         |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02           |
| Test duration   | 96 h                                |
| Salt spray testing result   | Test passed                         |
| Alternating condensation climate with SO2 test specification        | Following DIN 50018:2013-05         |
| Climate level   | AHT 1.0 S                           |
| Cycles  | 2                                   |
| Condensation test result  | Test passed                         |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result  | Test passed                         |
| Marking mounting type   | Thread on                           |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190218 |
| eCl@ss 4.1 | 24190218 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 7.0 | 27400401 |
| eCl@ss 8.0 | 27400401 |

## Cable marker - US-WMTB (44X15) - 0828773

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC001530 |
| ETIM 5.0 | EC001530 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Accessories

#### Accessories

#### Magazine

Magazine - THERMOMARK CARD-US-MAG1 - 5146451



Magazine for the THERMOMARK CARD printer, for accommodating US cards

---

### Drawings

## Cable marker - US-WMTB (44X15) - 0828773

Feature photo



Figure may contain other products.

Feature photo



Figure may contain other products.