

Screwdriver - SZS 1,2X8,0 VDE - 1205082

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Screwdriver, slot-headed, VDE insulated, size: 1.2 x 8.0 x 175 mm, 2-component grip, with non-slip grip

The illustration shows version SZG
0,6 x 3,5

Product Features

- ✓ The tools feature ergonomic two-component safety handles
- ✓ Large contact surface of blades inside screw head
- ✓ Individually tested safety screwdrivers according to DIN EN 60900 (VDE 0682-201)
- ✓ For working on or in the vicinity of live parts up to 1000 V AC or 1500 V DC



Key commercial data

Packing unit	1 pc
GTIN	 4 017918 019129
Weight per Piece (excluding packing)	150.54 GRM
Custom tariff number	82054000
Country of origin	Czech Republic

Technical data

Dimensions

Length (b)	287 mm
Width (a)	40 mm
Blade thickness	1.2 mm
Blade width	8 mm
Blade height	175 mm

General

Screwdriver - SZS 1,2X8,0 VDE - 1205082

Technical data

General

Type	Bladed
Material	Alloyed tool steel
Test standard	DIN/ISO 2380-1 IEC 60900:2004

Classifications

eCl@ss

eCl@ss 4.0	21040401
eCl@ss 4.1	21040401
eCl@ss 5.0	21040401
eCl@ss 5.1	21040401
eCl@ss 6.0	21040401
eCl@ss 7.0	21040409
eCl@ss 8.0	21040409

ETIM

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC000158
ETIM 5.0	EC000158

UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

Approvals

Approvals

Approvals

VDE Zeichengenehmigung / GOST / VDE Zeichengenehmigung / GOST

Ex Approvals

Screwdriver - SZS 1,2X8,0 VDE - 1205082

Approvals

Approvals submitted

Approval details

VDE Zeichengenehmigung

GOST

VDE Zeichengenehmigung

GOST

Drawings

Pictogram



Catalog photo



1000 V AC/
1500 V DC

Figure may contain other products.

Screwdriver - SZS 1,2X8,0 VDE - 1205082

Dimensioned drawing

