

Screwdriver - SZS 0,8X4,0 VDE - 1212508

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Screwdriver, slot-headed, VDE insulated, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

The illustration shows version SZS
0,6 x 3,5

Product Features

- The tools feature ergonomic two-component safety handles
- Large contact surface of blades inside screw head
- Individually tested safety screwdrivers according to DIN EN 60900 (VDE 0682-201)
- For working on or in the vicinity of live parts up to 1000 V AC or 1500 V DC



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	62.0 GRM
Custom tariff number	82054000
Country of origin	Czech Republic

Technical data

Dimensions

Length (b)	198 mm
Width (a)	33 mm
Blade thickness	0.8 mm
Blade width	4 mm
Blade height	100 mm

General

Type	Bladed
	Straight
Material	Alloyed tool steel

Screwdriver - SZS 0,8X4,0 VDE - 1212508

Technical data

General

Test standard	DIN/ISO 2380-1 IEC 60900:2004
---------------	-------------------------------

Classifications

eCl@ss

eCl@ss 4.0	21043074
eCl@ss 4.1	21043074
eCl@ss 5.0	21043290
eCl@ss 5.1	21043290
eCl@ss 6.0	21043706
eCl@ss 7.0	21043706
eCl@ss 8.0	21043706

ETIM

ETIM 3.0	EC001509
ETIM 4.0	EC000158
ETIM 5.0	EC000158

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

VDE Zeichengenehmigung / GOST / GOST

Ex Approvals

Approvals submitted

Screwdriver - SZS 0,8X4,0 VDE - 1212508

Approvals

Approval details

VDE Zeichengenehmigung

GOST

GOST

Drawings

Pictogram



Catalog photo



1000 V AC/
1500 V DC

Figure may contain other products.

Screwdriver - SZS 0,8X4,0 VDE - 1212508

Dimensioned drawing

