

Miniature solid-state relay - OPT-24DC/230AC/ 1 - 2967950

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in miniature solid-state relay, power solid-state relay, 1 N/O contact, input: 24 V DC, output: 24 - 253 V AC/0.75 A

Product Features

- Vibration and shock resistant
- RT III wash tight (comparable with IP67)
- Wear-free and durable
- Switching power of up to 24 V DC/5 A
- Can be soldered on PCB
- Zero voltage switch at AC output



Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| Weight per Piece (excluding packing) | 5.52 GRM |
| Custom tariff number | 85364190 |
| Country of origin | Japan |

Technical data

Dimensions

| | |
|--------|-------|
| Width | 5 mm |
| Height | 28 mm |
| Depth | 15 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -25 °C ... 60 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |

Input data

Miniature solid-state relay - OPT-24DC/230AC/ 1 - 2967950

Technical data

Input data

| | |
|---|-------------------------|
| Nominal input voltage U_N | 24 V DC |
| Input voltage range in reference to U_N | 0.8 ... 1.2 |
| Switching threshold "0" signal, voltage | ≤ 5 V |
| Switching threshold "1" signal voltage | ≥ 10 V |
| Typical input current at U_N | 3 mA |
| Typical response time | 6 ms (at U_N) |
| Typical turn-off time | 500 μ s (at U_N) |
| Transmission frequency | 10 Hz |

Output data

| | |
|--|---|
| Output voltage range | 24 V AC ... 253 V AC |
| Limiting continuous current | 0.75 A (see derating curve) |
| Maximum inrush current | 30 A (10 ms) |
| Min. load current | 10 mA |
| Leakage current | < 1 mA |
| Max. load value | 4.5 A ² s |
| Voltage drop at max. limiting continuous current | < 1 V |
| Output circuit | 2-conductor floating, zero voltage switch |
| Type of protection | RCV circuit |
| Protective circuit/component | RCV circuit |

General

| | |
|----------------------------------|---------------------------|
| Test voltage input/output | 2.5 kV (50 Hz, 1 min.) |
| Mounting position | any |
| Assembly instructions | In rows with zero spacing |
| Operating mode | 100% operating factor |
| Designation | Standards/regulations |
| Standards/regulations | IEC 60664 |
| | EN 50178 |
| | IEC 62103 |
| Rated surge voltage / insulation | Basic insulation |
| Pollution degree | 2 |
| Surge voltage category | III |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371102 |
|------------|----------|

Miniature solid-state relay - OPT-24DC/230AC/ 1 - 2967950

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.1 | 27371102 |
| eCl@ss 5.0 | 27371001 |
| eCl@ss 5.1 | 27371001 |
| eCl@ss 6.0 | 27371604 |
| eCl@ss 7.0 | 27371604 |
| eCl@ss 8.0 | 27371604 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001504 |
| ETIM 3.0 | EC001504 |
| ETIM 4.0 | EC001504 |
| ETIM 5.0 | EC001504 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211916 |
| UNSPSC 7.0901 | 39121542 |
| UNSPSC 11 | 39121542 |
| UNSPSC 12.01 | 39121542 |
| UNSPSC 13.2 | 39121542 |

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / GOST / GL / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details



Miniature solid-state relay - OPT-24DC/230AC/ 1 - 2967950

Approvals

cUL Recognized

GOST

GL


UL Recognized

cUL Recognized


cULus Recognized

Drawings

Drilling diagram




Diagram



a = pitch division 1.25 mm and 1.27 mm

Miniature solid-state relay - OPT-24DC/230AC/ 1 - 2967950

Dimensioned drawing



Circuit diagram

