

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Touch panel with 22.9 cm (9") graphics-capable TFT widescreen display, 800 x 480 pixels, 1 x Ethernet, 2 x USB, and integrated micro browser

Product Features

- Short startup time

- Micro browser (WebVisit client) integrated as standard in all devices
- Display available in sizes from 8.9 cm (3.5") to 38.1 cm (15")
- ☑ Easy device replacement the visualization project is saved on the PLC (web server)

Key commercial data

| Packing unit | 1 pc |
|--------------------------------------|------------|
| Weight per Piece (excluding packing) | 1780.0 GRM |
| Custom tariff number | 85371099 |
| Country of origin | Germany |

Technical data

Note

| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| External dimension, width | 260 mm |
|-----------------------------------|-------------------------------|
| External dimension, height | 172 mm |
| External dimension, depth | 5 mm |
| Note regarding external dimension | Dimensions of the front plate |
| Installation dimension, width | 252 mm |
| Installation dimension, height | 164 mm |

Display

| Display | 22.9 cm/9" TFT |
|---------|----------------|



Technical data

Display

| Resolution | 800 x 480 Pixel (WVGA) |
|------------------------|-----------------------------------|
| Backlighting | LED |
| Display backlight MTBF | > 50000 h |
| Touch screen | Resistive industrial touch screen |
| Colors | 65,536 colors |

Computer data

| Processor | RISC ARM9™ CPU; 200 MHz |
|-------------------|----------------------------------|
| RAM | 64 MB SDRAM |
| Mass storage | 32 MByte flash memory |
| Interfaces | 2x USB Host 2.0 |
| Network | 1 x Ethernet (10/100 Mbps), RJ45 |
| Operating systems | Windows CE 5.0 |

General

| Mounting type | Installation in front plate |
|---------------|-----------------------------|
| Weight | 1300 g |

Ambient conditions

| Degree of protection | IP65 (front), IP20 (back) |
|--|----------------------------|
| Ambient temperature (operation) | 0 °C 50 °C |
| Ambient temperature (storage/transport) | -25 °C 70 °C |
| Permissible humidity (operation) | 20 % 85 % (non-condensing) |
| Permissible humidity (storage/transport) | 10 % 95 % (non-condensing) |
| Vibration (operation) | DIN EN 60068-2-6 |
| Shock | DIN EN 60068-2-27 |

Classifications

eCl@ss

| eCl@ss 4.0 | 27330201 |
|------------|----------|
| eCl@ss 4.1 | 27330201 |
| eCl@ss 5.0 | 27330201 |
| eCl@ss 5.1 | 27242301 |
| eCl@ss 6.0 | 27242301 |
| eCl@ss 7.0 | 27242301 |
| eCl@ss 8.0 | 27242301 |



Classifications

ETIM

| ETIM 3.0 | EC001414 |
|----------|----------|
| ETIM 4.0 | EC001414 |
| ETIM 5.0 | EC001414 |

UNSPSC

| UNSPSC 6.01 | 43172015 |
|---------------|----------|
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43211507 |
| UNSPSC 13.2 | 43201404 |

Approvals

| Approvals | S |
|-----------|---|
|-----------|---|

Approvals

 $\textit{GL / GL-SW / UL Listed / cUL Listed / GL / cULus Listed / cULus Listed / cULus Listed / cull Listed / null /$

Ex Approvals

Approvals submitted

Approval details

GL

GL-SW

UL Listed 🕦





Approvals

| cUL Listed ** | |
|---|--|
| GL | |
| cULus Listed ^e COULus Listed e COUlus Listed | |
| cULus Listed (CULus Listed (CU | |
| cULus Listed | |
| £ ((())05 | |
| | |
| | |
| | |

Accessories

Accessories

Mounting material

Mounting kit - HMI WALL MOUNTING KIT - 2701380

HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.





Accessories

Mounting kit - HMI SCB MOUNTING KIT 4 - 2701384



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

Mounting kit - HMI SCB MOUNTING KIT 6 - 2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

Mounting kit - HMI SCB MOUNTING KIT 8 - 2701387



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

Operating stylus

Touch pen - TOUCH PEN - 2701379



Touch pen for HMIs, silver coated. Delivery includes self-adhesive pen holder.

Protective foil

Protective foil - 9" DISPLAY PROTECTIVE FOIL - 2701375

Protective film set comprising 10 pieces of film for a 9" display. Including a squeegee to apply film and instructions.





Accessories

Storage medium

USB memory stick - 2 GB USB STICK - 2701382



USB memory stick, 2 GB.

Phoenix Contact 2014 © - all rights reserved http://www.phoenixcontact.com