

Surge protection device - DT-TELE-RJ45 - 2882925

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Attachment plug with surge protection for analog and digital telecommunications interfaces (VDSL up to 50 Mbps). Connection: RJ45 (RJ12/RJ11) and screw terminal block (COMBICON). Alternatively, can be snapped onto a DIN rail.

Product Features

- ✓ For analog and digital (DSL) telecommunications interface
- ✓ Connection: RJ45 socket and/or plug-in screw terminal blocks
- ✓ The adapter included enables conversion from RJ45 to RJ11 and RJ12
- ✓ DIN rail mounting possible by removing the cover cap
- ✓ International use thanks to multiple assignment



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	332.6 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Height	103 mm
Width	25 mm
Depth	63 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

General

Housing material	Zinc die-cast
------------------	---------------

Surge protection device - DT-TELE-RJ45 - 2882925

Technical data

General

Color	silver/black
Standards for air and creepage distances	IEC 60664-1
	VDE 0110-1
Mounting type	Connection-specific attachment plug and DIN rail, 35 mm
Type	Attachment plug for DIN rail mounting
Number of positions	4
Direction of action	Line-Line & Line-Ground/Shield

Protective circuit

IEC test classification	B2
	C1
	C2
	C3
	D1
VDE requirement class	B2
	C1
	C2
	C3
	D1
Maximum continuous operating voltage U_C	185 V DC
	130 V AC
Maximum continuous voltage U_C (wire-wire)	185 V DC
	130 V AC
Maximum continuous voltage U_C (wire-ground)	185 V DC
Nominal current I_N	≤ 380 mA (25 °C)
Operating effective current I_C at U_C	≤ 6 μ A
Residual current I_{PE}	≤ 4 μ A
Nominal discharge current I_n (8/20) μ s (Core-Core)	≤ 5 kA
Nominal discharge current I_n (8/20) μ s (Core-Earth)	≤ 5 kA
Total surge current (8/20) μ s	10 kA
Nominal pulse current I_{an} (10/1000) μ s (Core-Core)	100 A
Nominal pulse current I_{an} (10/1000) μ s (Core-Earth)	100 A
Nominal pulse current I_{an} (10/700) μ s (Core-Core)	150 A
Nominal pulse current I_{an} (10/700) μ s (Core-Earth)	150 A
Output voltage limitation at 1 kV/ μ s (Core-Core) static	≤ 250 V
Output voltage limitation at 1 kV/ μ s (Core-Earth) static	≤ 250 V
Residual voltage at I_n , (conductor-conductor)	≤ 120 V

Surge protection device - DT-TELE-RJ45 - 2882925

Technical data

Protective circuit

Residual voltage at I_n (conductor-ground)	≤ 120 V
Voltage protection level U_p (Core-Core)	≤ 250 V (B2 - 100 A)
	≤ 250 V (C1 - 500 A)
	≤ 250 V (C2 - 5 kA)
Voltage protection level U_p (Core-Earth)	≤ 250 V (B2 - 100 A)
	≤ 250 V (C1 - 500 A)
	≤ 250 V (C2 - 5 kA)
Response time t_A (Core-Core)	≤ 100 ns
Response time t_A (Core-Earth)	≤ 100 ns
Input attenuation a_E , sym.	typ. 0.5 dB (≤ 5 MHz)
	typ. 0.3 dB (≤ 8 MHz / 150 Ω)
	typ. 0.3 dB (≤ 2.5 MHz / 600 Ω)
Cut-off frequency f_g (3 dB), sym. in 100 Ohm system	typ. 50 MHz
Resistance in series	3.3 Ω 10 %
Surge current resistance (conductor-conductor)	C1 - 1 kV/500 A
	C2 - 10 kV/5 kA
	B2 - 4 kV/100 A
Surge current resistance (conductor-ground)	B2 - 4 kV/100 A
	C1 - 1 kV/500 A
	C2 - 10 kV/5 kA
	D1 - 1 kA

Connection data

Connection method	RJ45 / Combicon
Connection type IN	RJ45 socket
	MC 1,5/4
Connection type OUT	RJ45 socket
	MC 1,5/4
Connection method	Screw connection
Screw thread	M2
Tightening torque	0.22 Nm
Stripping length	7 mm
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	28
Conductor cross section AWG/kcmil max	16

Surge protection device - DT-TELE-RJ45 - 2882925

Technical data

Connection, equipotential bonding

Connection method	Cable connection/DIN rail
-------------------	---------------------------

Standards and Regulations

Standards/regulations	IEC 61643-21
-----------------------	--------------

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

GOST / GOST


Ex Approvals

Surge protection device - DT-TELE-RJ45 - 2882925

Approvals


Approvals submitted

Approval details



Drawings

Circuit diagram



Dimensioned drawing

