

## Reducing adapter - REDUC-M-KV-M32/M25 - 1647637


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Reducing adapter, metal, M32 to M25, including O-ring



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 941536
Weight per Piece (excluding packing)	35.29 GRM
Custom tariff number	74153300
Country of origin	Germany

### Technical data

#### Ambient conditions

Degree of protection	IP68 (Depends on the screw connection used)
Ambient temperature (operation)	-20 °C ... 80 °C

#### General

Material	Nickel-plated brass
Seal material	NBR
Material, O-ring	NBR
Thread type on connection side	M25

### Classifications

#### eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209

# Reducing adapter - REDUC-M-KV-M32/M25 - 1647637

## Classifications

### eCl@ss

eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27149109

### ETIM


ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441

### UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408

## Drawings

Dimensioned drawing



Dimensional drawing